


CANDELA DISTRIBUTION				CANDELA TABLE			LUMINANCE (cd/sq.m)			LUMENS PER ZONE		ZONAL LUMEN SUMMARY								
				0°		90°	0.00°		90.00°	ZONE	LUMENS	ZONE	UMENS	% LUMINAIRE						
				0°	775	775	0.00°	16155	16155	0° - 10°	73	0° - 20°	280	14%						
				10°	759	759	45.00°	13851	14684	10° - 20°	207	0° - 30°	587	29%						
				20°	706	711	55.00°	12966	13807	20° - 30°	307	0° - 40°	948	46%						
				30°	624	634	65.00°	12286	12609	30° - 40°	361	0° - 60°	1640	80%						
				40°	524	546	75.00°	10450	10542	40° - 50°	368	0° - 80°	2017	98%						
				50°	414	440	85.00°	7019	6413	50° - 60°	324	0° - 90°	2050	100%						
				60°	299	319				60° - 70°	244									
				70°	189	193				70° - 80°	134									
				80°	75	74				80° - 90°	33									
90°	4	2																		
CONE OF LIGHT				INDOOR COEFFICIENTS OF UTILIZATION																
MOUNTING HEIGHT	FC AT BEAM CENTER	BEAM DIA. 0°-180°	BEAM DIA. 90°-270°	pf	20%											0%				
					pc	80%											0%			
				pw	70%	50%	30%	10%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%	
6.0 m	21.5 lx	15.7 m	16.1 m	0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102
8.0 m	12.1 lx	20.9 m	21.4 m	1	109	104	100	96	106	102	98	95	98	95	92	94	91	89	90	88
10.0 m	7.8 lx	26.2 m	26.8 m	2	99	91	84	79	97	89	83	78	86	80	76	82	78	74	79	76
12.0 m	5.4 lx	31.4 m	32.2 m	3	91	80	72	66	88	79	71	65	76	69	64	73	67	63	70	66
14.0 m	4.0 lx	36.6 m	37.5 m	4	83	71	62	56	81	70	62	55	67	60	55	65	59	54	63	57
16.0 m	3.0 lx	41.8 m	42.9 m	5	76	64	55	48	74	62	54	48	60	53	47	58	52	47	57	51
18.0 m	2.4 lx	47.1 m	48.2 m	6	71	57	48	42	69	56	48	42	55	47	41	53	46	41	51	45
20.0 m	1.9 lx	52.3 m	53.6 m	7	65	52	43	37	64	51	43	37	50	42	37	48	42	37	47	41
				8	61	48	39	33	59	47	39	33	46	38	33	44	38	33	43	37
				9	57	44	35	30	56	43	35	30	42	35	30	41	34	30	40	34
				10	53	40	32	27	52	40	32	27	39	32	27	38	31	27	37	31