SAFETY INSTRUCTIONS

1. Do not use outdoors. 2. Equipment should be mounted securely in locations and at heights where it will not be readily subjected to tampering by unauthorized personnel. 3. Do not mount near gas or electric heaters. 4. Cap unused wires with enclosed wire nuts or other approved method. 5. Do not use this equipment for anything other than its intended use. 6. The use of accessory equipment not recommended by the manufacturer will void product listing and warranty and may cause an unsafe condition. 7. Use caution

when servicing batteries. 8. Any service on this equipment should be performed by qualified personnel only. 9. Make sure wire terminations are secure and leads are properly tucked in appropriate wire channels. **CONSULT A QUALIFIED ELECTRICIAN BEFORE INSTALLING**



Caution:

Disconnect AC power before servicing and installation. All electrical connections must be in accordance with NEC/CEC or your local code.



J-BOX MOUNTING

.

Loosen two set screws and remove metal template.

2.

Install EVA gasket on the back of the metal template (Note the direction of the arrow).

3.


Pull house supply wires through hole in housing back and secure housing to junction box with two mounting screws(by others).

4.

Connect Black for line, White for Neutral and bare wire for Ground to complete the wiring.

5.

Secure the fixture on the metal template with set screws.



1/2" Conduit Mounting

1.

Loosen two set screws and remove metal template.

2.

Install EVA gasket on the back of the metal template (Note the direction of the arrow).

3.

Pull house supply wires through hole in housing back and secure housing to junction box with two mounting screws(by others).

4.


Remove Knock-out with the appropriate tools, thread 1/2" conduit into the 1/2" hole.

5.

Connect Black for line, White for Neutral and bare wire for Ground to complete the wiring.

6.

Secure the fixture on the metal template with set screws.




Note: To ensure waterproof seal, apply weatherproof silicone sealantaround the edge of the wall mounting box and /or junction box. This is especially important with an uneven wall surface. Silicone all plugs and unused conduit entries.



PHOTOCELL INSTALLATION

- 1. Install photocell and wire as per diagram.
- 2. Use photocell rated for your supply voltage.



Catalog# OWP-SL-101-LED O.R.-Revision A: 12/19



 \geq

