



(On selected configuration, consult factory)

**DIMENSION:**  
 LENGTH: 44-1/2" (2X4) (1X4), 22" (2X2)  
 WIDTH: 20" (2X4) 8-1/2" (1X4), 20" (2X2)  
 DEPTH: 1-5/8"

<b>2400</b> LUMENS	<b>3400</b> LUMENS	<b>4000</b> LUMENS
<b>28</b> WATT	<b>37</b> WATT	<b>44</b> WATT

LED  
ORTK

**APPLICATION:**  
 Retrofits Recessed Troffers Lensed

- PRODUCT FEATURES:**
- Spacing criteria 0-Deg: 1.2, 90-Deg:1.3
  - Available in many lumen packages
  - Driver and wiring access without the use of tools
  - Dimming/occupancy sensor compatible

- CONSTRUCTION:**
- Brackets are manufactured from code-gauge cold-rolled steel and have white baked enamel finishes

**Reflectors:** Precision formed, high performance, 95% total reflectance specular reflector, warranted for 25 years or 91% total reflectance white pre-painted aluminum

**WARRANTY**  
 One year standard warranty on fixture  
 5 year limited warranty on LED

LED Retrofit Kit

**Ordering Information: Example: 14-ORTK-LED-4000L-DIM10-MVOLT-30K-85**

<b>FIXTURE SIZE</b> 14 - 1' X 4'	<b>SERIES</b> ORTK-Oracle LED Retrofit Kit for Troffer	<b>TYPE</b> LED	<b>LUMENS</b> 14-ORTK 2400L - (2400 lumens) 3400L - (3400 lumens) 4000L - (4000 lumens)	<b>DIMMING</b> DIM10 - 0-10V Dimming LUTH - Lutron Dimming DIMST - Step Dimming	<b>VOLTAGE</b> MVOLT 347*	<b>CCT</b> 30K - (3000K) 35K - (3500K) 40K - (4000K) 50K - (5000K)	<b>CRI</b> 85	<b>EMERGENCY</b> 0-EMG-LED

\* Consult factory for details