



(On selected configuration, consult factory)

DIMENSION:

LENGTH: 44-1/2" (2X4) (1X4), 22" (2X2)
WIDTH: 20" (2X4) 8-1/2" (1X4), 20" (2X2)
DEPTH: 1-5/8"

2400
LUMENS
28
WATT

3400
LUMENS
37
WATT

4000
LUMENS
44
WATT

LED
ORTK

APPLICATION:

Retrofits Recessed Troffers Lensed

PRODUCT FEATURES:

- Spacing criteria 0-Deg: 1.2, 90-Deg:1.3
- Available in many lumen packages
- Driver and wiring access without the use of tools
- Dimming/occupancy sensor compatible

WARRANTY

One year standard warranty on fixture
5 year limited warranty on LED

CONSTRUCTION:

- Brackets are manufactured from code-gauge cold-rolled steel and have white baked enamel finishes

Reflectors: Precision formed, high performance, 95% total reflectance specular reflector, warranted for 25 years or 91% total reflectance white pre-painted aluminum

LED Retrofit Kit

Ordering Information: Example: 22-ORTK-LED-4000L-DIM10-MVOLT-30K-85

FIXTURE SIZE	SERIES	TYPE	LUMENS	DIMMING	VOLTAGE	CCT	CRI	EMERGENCY
22 - 2' X 2'	ORTK-Oracle LED Retrofit Kit for Troffer	LED	22-ORTK 2400L - (2400 lumens) 3400L - (3400 lumens) 4000L - (4000 lumens)	DIM10 - 0-10V Dimming LUTH - Lutron Dimming DIMST - Step Dimming	MVOLT 347*	30K - (3000K) 35K - (3500K) 40K - (4000K) 50K - (5000K)	85	0-EMG-LED

* Consult factory for details