

NOMINAL LUMENS	DELIVERED LUMENS	WATTAGE
5000	6131	37 W
4000	3596	27 W
3000	4287	23 W

Based on 4000K, 90+ CRI. Actual wattage may vary +/- 5%

FEATURES

The Architectural LED Suspended Linear combines a slim profile with clean lines, making it an ideal choice for library stacks or narrow aisles. The flexibility of the luminaire allows for continuous, uniform and glare-free illumination. Available in single pendant or continuous mounting for a seamless connection from luminaire to luminaire, with adjustable mounting heights. This distinct luminaire is a perfect solution for educational, healthcare, office, commercial and retail spaces.

LUMENS	3000, 4000, 5000
CCT	30K, 35K, 40K, 50K
CRI	85+(standard), 90+
COLOR QUALITY	3 Step MacAdam Ellipse
LENGTH	2', 4', 8'
MOUNTING	Suspended or Surface
FINISH	WH (White standard), BK (Black), SI (Silver), Custom Colors
DIMMING & CONTROL	0-10V Flicker Free 1% Dimming Standard (DIM10), LUTH, DIMST, ELD010.1, ELD0DMX.1, DALI.1
EMERGENCY	10W - Up to 1000L output
LIFETIME	L70 at 167,000 Hours
OPERATING TEMPERATURE	-20° C to 50°C ambient temperature
PHOTOMETRIC TESTS	In Accordance with IES LM79-08, LM80 and TM-30, TM-21



CONSTRUCTION

CRM INSTALLATION

DRIVER ELECTRICAL INFORMATION

OPTIONS

DIMMING & DRIVER INFORMATION

DIMST - Step Dimming

WARRANTY

Five-year warranty for parts and components . (Labor not included)

LISTINGS

c-UL-us - Listed for Feed Through Wiring.

Listed for DLC, California Title 24 compliant.


c UL us Listed for Damp location

Product not allowed to be in direct contact with water, sprinkler or rain

2	OC1R	LED																
FIXTURE SIZE	SERIES	TYPE	LUMENS	DIMMING	VOLTAGE	CCT	CRI											
2 - 2'	OC1R - LED General Linear	LED	3000L - 3000 lumens 4000L - 4000 lumens 5000L - 5000 lumens	DIM10 - 0-10V Dimming *DIMST - Step Dimming *LUTH - Lutron Hilume ELD010.1 - EldoLED 0-10V ELD0DALI.1 - EldoLED DALI ELD0DMX.1 - EldoLED DMX	MVOLT 120 277 347*	30K 35K 40K 50K	85 90											
					*Consult factory for details													
REFLECTOR																		
SYM - Symmetrical Reflector White ASY - Asymmetrical Reflector White SYM-UPL - Uplight Symmetrical Reflector White																		
*Please see the next page for the reference																		
OTHER OPTIONS																		
OCGSS - Cable Gripper Suspension Kit OCVH - V Hook WG - WireGuard USA - Made in America Compliance SO5 - Power cord with 5 conductors for 0-10v dimming fixtures SO6 - Power cord with 6 conductors for 0-10V dimming and with emergency																		
EMERGENCY 0-EMG-LED-10W																		
FINISH WH- White (Standard) BK - Black SI - Silver *Custom colors available Consult factory																		
MOUNTING CRM - Continuous Row Mounting																		
WIRING OPTIONS FBF - Internal Fast Blow Fuse SBF - Internal Slow Blow Fuse RIS - Radio Interference Suppressor																		
CONTROLS																		
SIDE MOUNT OSFHU-LTW - ON/OFF Line Voltage HB011-PDX - Occupancy Sensor with 0-10V Dimming FSP-311-B-D - 0-10V continuous dimming PIR photo/motion sensor with bluetooth controloption. 411 - HB0LAPDX																		
INTEGRATED																		
OSM3D-V1W - Line Voltage Microwave Sensor OSM3D-DDW-20 - HF Microwave Sensor 0-10 20% Dim OSM3D-DDW-50 - HF Microwave Sensor 0-10 50% Dim FS-205 - Low Voltage Pir Fixture Integrated Occupancy Sensor FD-301 - Low VolatgeDaylight Dimming Photosensor - High Frequency Microwave Occupancy FM-105 Sensor with 0-10V Dimming - Fixture Sensor Power Pack FS-PPV2																		
*FD-301 & FS-205 require FS-PPV2- Power Pack																		


LUTH, ELDO10.1, ELDODALI.1, and ELDODMX.1 are available in 120V and 277V

Reference last page for Control Options




Symmetrical

SYM-UPL - Uplight Symmetrical Reflector White



Asymmetrical

ASY - Asymmetrical Reflector White



Uplight Symmetrical

SYM - Symmetrical Reflector White

INTEGRATED SENSOR AND CONTROL OPTIONS

With the IntegratedED of controls, Elite Lighting now offers its products with controls-ready performance that increases energy efficiency, smarter space planning, and the enhancement of safety and productivity in the workplace. By utilizing these controls, Elite Lighting luminaires enable your customer's facility to run smarter, with the use of an easily controlled system through any platform.


Luminaire will be shipped with Powerpacks pre-installed, ready to be IntegratedED to designated control systems

Luminaire will be shipped with Sensors installed on the luminaire, allowing for individual luminaire control. Luminaires will be ready to be IntegratedED with designated control systems

Luminaire will be shipped with Sensors to be remotely installed on the ceiling. Luminaires will be ready to be IntegratedED with designated control systems

BRAND	LEVITON	legrand
MICROWAVE INTEGRATED SENSOR	<input type="checkbox"/> OSM3D-DDW High Frequency Microwave Occupancy Sensor with 0-10V Dimming	<input type="checkbox"/> FS-205 Low Voltage Pir Fixture IntegratedED Occupancy Sensor
	<input type="checkbox"/> OSM3D-V1W Line Voltage Microwave Sensor	<input type="checkbox"/> FD-301 Low Voltage Daylight Dimming Photosensor
PIR INTEGRATED SENSOR	<input type="checkbox"/> OSFHU-LTW PIR Fixture Mount Occupancy Sensor	<input type="checkbox"/> FSP-311-B-D 0-10V continuous dimming PIR photo/motion sensor with bluetooth control option.
	<input type="checkbox"/> HB011-PDX PIR Fixture Mount Occupancy Sensor with Daylight Harvesting	

SIDE MOUNT




LEGRAND

☐ FSP-311-B-D
0-10V continuous dimming PIR photo/motion sensor with bluetooth control option.

LEVITON

☐ HB011-PDX
PIR Fixture Mount Occupancy Sensor with Daylight Harvesting
☐ OSFHU-LTW
PIR Fixture Mount Occupancy Sensor
☐ OFD1Z-IOW
IP66 PIR Sensors with Bluetooth™ Connectivity and UV Stable Plasti

IntegratedED



LEGRAND

☐ FM-105
High Frequency Microwave Occupancy Sensor with 0-10V Dimming
☐ FS-205
Low Voltage Pir Fixture IntegratedED Occupancy Sensor
☐ FD-301
Low Voltage Daylight Dimming Photosensor

LEVITON

☐ OSM3D-DDW
High Frequency Microwave Occupancy Sensor with 0-10V Dimming
☐ OSM3D-V1W
Line Voltage Microwave Sensor