



NOMINAL LUMENS	WATTAGE
3000	35 W
2000	23 W

Based on 4000K, 85+ CRI. Actual wattage may vary +/- 5%

DYNAMIC PLATFORM

SMART DIM - Dims to Warm with Smart Dim Technology simulates traditional incandescent halogen lighting through dimming, while providing the energy efficiency, high performance and longevity of LED luminaires. When the luminaire dims to warm, it makes a smooth transition across the black body radiator curve. Starting with a 100% lumen output at 3000K, down to a 1% lumen output at 1800K, and maintaining a constant CRI of 90+. It results in rich amber tones as the light dims, encouraging relaxation. An ideal source for hospitality, healthcare, restaurants, and assisted living applications.

LUMENS	2000, 3000
WARM DIM PLATFORMS	100% lumen output at 3000K, down to a 1% lumen output at 1800K
CRI	90+
COLOR QUALITY	2 Step MacAdam Ellipse
SIZE	2'x2', 2'x4'
MOUNTING	Recessed
DIMMING & CONTROL	0-10V Flicker Free 1% Dimming Standard (DIM10), LUTH, LUT2W, DIMST, ELDO10.1, ELDO10.1, DALI.1
EMERGENCY	10W - Up to 1000L output (Bodine BSL310) 20W - Up to 2000L output (Bodine BSL20)
LIFETIME	L70 at 50,000 Hours
PHOTOMETRIC TESTS	In Accordance with IES LM79-08, LM80 and TM-30, TM-21





FEATURES

The clean lines and crisp profile of the lens creates an impressionable presence, making it the perfect application for contemporary spaces. Featuring a sleek center metal extrusion that can also be painted any color, it creates a floating visual effect, providing a seamless aesthetically pleasing appearance. The angled backlit lens creates a volumetric, uniform illumination with the use of glare-free reflective surfaces, resulting in ideal visual comfort. The glare-free illumination, high efficient and sustainability of the luminaire also makes it the ideal source for corporate offices, educational, health care, commercial, and retail applications.

OPTICAL SYSTEM

The LED light engine is secured to the body of the luminaire, with the body acting as a heat sink. A proprietary design of the lens results in zero pixilation, regardless of the viewing angle, with LEDs placed to promote a uniform appearance. The result is even illumination across the space, from luminaire to luminaire.

MAINTENANCE

The door frame assembly is hinged, allowing easy access to LED boards and driver compartment, locking into place for secure closure of the luminaire. LED engines and drivers are removable and upgradable even after luminaire installation. Luminaire can be regularly and safely wiped down to ensure optimal performance.

OPTICAL SYSTEM

The LED light engine is secured to the body of the luminaire, with the body acting as a heat sink. A proprietary design of the lens results in zero pixilation, regardless of the viewing angle, with LEDs placed to promote a uniform appearance. The result is even illumination across the space, from luminaire to luminaire.

CONSTRUCTION

Body is constructed of heavy-duty 20-gauge cold rolled steel, post-painted and engineered for maximum strength and extended life. All corners interlock to prevent aesthetic damage to the luminaire, with sides and corners uniformly turned in and hemmed to remove sharp edges for safe handling and easy installation. Luminaire is supplied with multiple wiring entrances for easy daisy chain of luminaires, to add power packs, whips, or other accessories in the field, or for continuous row mounting.

FINISH

Post-painted with a 93% reflective white coat to improve luminaire efficacy, and all body components are seamlessly interlocked for added structural strength.

MOUNTING

Luminaires accommodate lay-in ceilings, Slot T, and T-bar suspension systems for 5/8" and 3/8" ceiling thicknesses. Four corner tie points are standard for safety wire support when required, with built-in earthquake clips, standard. Luminaires may be available with flange kits, surface mounted kits, and other options.

OPTIONS

Luminaires can be shipped pre-installed with whips, modular wiring systems, daylight harvesting controls, occupancy sensors, and/or power packs for individual or room control solutions.

DRIVER ELECTRICAL INFORMATION

Powered by high-quality constant-current power LED drivers which are rated for 50 to 60Hz at 120-277V input, produce less than 20% THD, and have a power factor of .90 to 1.00.

WARRANTY

Five-year warranty for parts and components. (Labor not included)

LISTINGS

c-UL-us - Listed for Feed Through Wiring.

Example: **22-LITE-LED-1-WDM-35K-18K-3000L-DIM10-MVOLT**

22	LITE-LED-1	WDM					
FIXTURE SIZE	SERIES	TECHNOLOGY	LUMENS	DIMMING	VOLTAGE	EMERGENCY	OTHER OPTIONS
22 - 2' X 2'	LITE-LED-1 - Fully Illuminated LED Troffer	WDM-35K-18K	2000L - 2000 lumens 3000L - 3000 lumens	DIM10 - 0-10V Dimming DIMST - Step Dimming LUTH - Lutron Hilume LUT2W - Lutron 2Wire ELD010.1 - EldoLED 0-10V DALI.1 - EldoLED DALI ELDODMX.1 - EldoLED DMX	120 277 MVOLT	EMG-LED-10W EMG-LED-20W	22FK 2'x2' Flange Kit FBF Internal Fast Blow Fuse SBF Internal Slow Blow Fuse RIS Radio Interference Suppressor USA Made in America Compliance

LUT2W are available in 120V only LUT2W up to 4000L

LUTH, ELD010.1, ELDODALI.1, and ELDODMX.1 are available in 120V and 277V

-Reference last page for Control Options



- 1- Luminaire will be shipped with Powerpacks pre-installed, ready to be integrated to designated control systems
- 2- Luminaire will be shipped with Sensors installed on the luminaire, allowing for individual luminaire control. Luminaires will be ready to be integrated with designated control systems
- 3- Luminaire will be shipped with Sensors to be remotely installed on the ceiling. Luminaires will be ready to be integrated with designated control systems

BRAND	EASYFIT by EnOcean	LUTRON	enlighted	LEVITON®	OSRAM	PHILIPS EasySense	legrand®
CONTROL UNIT	❑ LEDRU LED Relay Zone Controller 0-10V ¹	❑ FCJS-0-10 Lutron Vive 0-10V Individual Control Models ^{1 4}	❑ CU-4E-FMH Fixture Mount Control Unit ^{1 5}	❑ ZL027 -NOW Intellect Power Control Module ^{1 6}	❑ EN-WCM2-ZB-DR Wireless Control Module ^{1 7}	❑ XITANIUM SR LED DRIVER The Philips Advance Xitanium SR LED driver ^{1 8}	❑ LMFC-011 ON/OFF/0-10V dimming fixture controller ^{1 9}
	❑ LEDDU LED Zone Controller 0-10V ¹	❑ FCJS-ECO Lutron Vive Eco-system Individual Control Models ^{1 4}		❑ ZL027 -DLE Intellect Power Control Module ^{1 6}	❑ EN- ALC-ZB-BK-DR Wireless Area Lighting Control Module ^{1 7}		❑ FS-PP-V2 FS-PP Fixture Integrated Sensor Power Pack ^{1 9}
INTEGRAT OCCUPANCY& DAYLIGHT SENSOR	N/A	❑ DFCSJ-OEM-OCC Clear Connect (RF) and Occupancy/ Daylight Sensing ²	❑ SU-5E-IoT IoT Node Micro Sensor ❑ SU-5E-CL Connected Micro Sensor ❑ SU-5E-IL Independent Micro Sensor ❑ SU-5S-H(IoT/CL/IL) Surface Mount Sensor (Must be Specified with CU- 4E-FMH Control Unit) ²	❑ ZL00J -TOW Intellect Intelligent Fixture Control System ²	❑ EN-CLM-PIR-DD-ZB SensiLUM™ Wireless Integrated Sensor	❑ SNS200 SNS200 for grouping ²	❑ FD-301 Fixture integrated Daylight Dimming Sensor ²
				❑ ZL00J-DOW Intellect Intelligent Fixture Control System ²	❑ ZBHA- CLM-DIM-ENC Connected Lighting Module DIM ²	❑ SNS300 SNS300 for networks ²	❑ FS-205 Fixture integrated passive infrared occupancy sensor ²
*WIRELESS OCCUPANCY SENSOR	❑ EOSCU-W-E0 Occupancy Sensor - Ceiling Mounted ³	❑ LRF2-OCR2B-P-WH Ceiling mount 360° ,occupancy/vacancy sensor ³	N/A	N/A	❑ EN-SCPPH- 1500-ZB Wireless Passive Infrared Occupancy and Photo Sensors ³	N/A	❑ LMDC-100 Dual technology PIR Ceiling Mount Occupancy Sensor ³
*WIRELESS DAYLIGHT SENSOR	❑ ELLSU-W-E0 Light Level Sensor - Ceiling Mounted ³	❑ LRF2-DCRB-WH Ceiling-mount daylight sensor ³	N/A	N/A	❑ EN-SCPPH- 1500-ZB Wireless Passive Infrared Occupancy and Photo Sensors ³	N/A	❑ LMLS-400 Single zone switching and dimming digital photosensor ³
*WIRELESS OCCUPANCY & DAYLIGHT SENSOR	N/A	N/A	❑ SU-5E-IoT IoT Node Micro Sensor ❑ SU-5E-CL Connected Micro Sensor ❑ SU-5E-IL Independent Micro Sensor ❑ SU-5S-H(IoT/CL/IL) Surface Mount Sensor (Must be specified with CU- 4E-FMH Control Unit) ³	❑ ZL00J -TOW Intellect Intelligent Fixture Control System ❑ ZL00J-DOW Intellect Intelligent Fixture Control System (Must be specified with ZL027-NOW and ZL00J- DOW Control unit) ³	❑ EN-CLM- PIR-DD-ZB SensiLUM™ Wireless Integrated Sensor ❑ ZBHA- CLM-DIM-ENC Connected Lighting Module DIM (Must be specified with EN-WCM2-ZB-DR or EN- ALC-ZB-BK-DR Control Unit) ³	❑ SNS200-CMP SNS-200 for Grouping ³	N/A
ACCESORIES	N/A	N/A	❑ TMC-SU-5E Tile Mount Carrier ❑ CBL-5E-CU4-30N 30 inch Sensor cable for CU-4 and IoT Ready ❑ CBL-5E-CU4-7F 7 Foot sensor cable for CU-4 and IoT Ready Driver	N/A	N/A	N/A	N/A
NOTES	N/A	4- Luminaire will be compatible with LUTRON LRF2-OCR2B-PWH Ceiling mount 360deg occupancy/ vacancy sensor & LRF2-DCRB-WH ceiling mount daylight sensor. Sensors must be orderd through Lutron	5- Luminaire will be compatible with ENLIGHTED SU-5E-IoT, SU-5E-CL, SU-5E-IL, SU-5SH, Sensors	6- Luminaire will be compatible with LEVITON Intellect APP & Keypad room controller	7- Luminaire will be compatible with EN-SCPPH-1500-ZB Wireless passive infrared occupancy and photo sensor	8- Luminaire will be compatible with philips field and wireless switch	9- Luminaire will be compatible with DLM Room control system LMPB-100. . Sensors must be orderd through Legrand.