



NOMINAL LUMENS	WATTAGE
3000	44 W
2000	28 W

Based on 4000K, 90+ CRI. Actual wattage may vary +/- 5%

**DYNAMIC PLATFORM**

SMART DIM - Dims to Warm with Smart Dim Technology simulates traditional incandescent halogen lighting through dimming, while providing the energy efficiency, high performance and longevity of LED luminaires. When the luminaire dims to warm, it makes a smooth transition across the black body radiator curve. Starting with a 100% lumen output at 3000K, down to a 1% lumen output at 1800K, and maintaining a constant CRI of 90+. It results in rich amber tones as the light dims, encouraging relaxation. An ideal source for hospitality, healthcare, restaurants, and assisted living applications.

LUMENS	2000, 3000
WARM DIM PLATFORMS	100% lumen output at 3000K, down to a 1% lumen output at 1800K
CRI	90+
COLOR QUALITY	2 Step MacAdam Ellipse
SIZE	2'x2', 2'x4', 1'x4'
MOUNTING	Recessed
DIMMING & CONTROL	0-10V Flicker Free 1% Dimming Standard (DIM10), LUTH, LUT2W, DIMST, ELDO10.1, ELDODMX.1, DALI.1
EMERGENCY	10W - Up to 1000L output (Bodine BSL310) 20W - Up to 2000L output (Bodine BSL20)
LIFETIME	L70 at 50,000 Hours
PHOTOMETRIC TESTS	In Accordance with IES LM79-08, LM80 and TM-30, TM-21





**FEATURES**

The OD-LED blends the traditional look of an architectural volumetric troffer with a center acrylic diffuser, together with unmatched optical performance, delivering the latest in LED technology and lens innovation. The integrated LEDs are strategically angled behind the center indirect acrylic diffuser to maximize lumen output and provide even illumination across the full face of the luminaire. The consistency of the volumetric effect results in optimized visual comfort, enhancing the quality of illumination. The combination of energy savings and optical performance create the ideal choice for educational, medical, office and retail spaces.

**OPTICAL SYSTEM**

The LED light engine is secured to the body of the luminaire, with the body acting as a heat sink. A proprietary design of the lens results in zero pixilation, regardless of the viewing angle, with LEDs placed to promote a uniform appearance. The result is even illumination across the space, from luminaire to luminaire.

**MAINTENANCE**

The door frame assembly is hinged, allowing easy access to LED boards and driver compartment, locking into place for secure closure of the luminaire. LED engines and drivers are removable and upgradable even after luminaire installation. Luminaire can be regularly and safely wiped down to ensure optimal performance.

**OPTICAL SYSTEM**

The LED light engine is secured to the body of the luminaire, with the body acting as a heat sink. A proprietary design of the lens results in zero pixilation, regardless of the viewing angle, with LEDs placed to promote a uniform appearance. The result is even illumination across the space, from luminaire to luminaire.

**CONSTRUCTION**

Body is constructed of heavy-duty 20-gauge cold rolled steel, post-painted and engineered for maximum strength and extended life. All corners interlock to prevent aesthetic damage to the luminaire, with sides and corners uniformly turned in and hemmed to remove sharp edges for safe handling and easy installation. Luminaire is supplied with multiple wiring entrances for easy daisy chain of luminaires, to add power packs, whips, or other accessories in the field, or for continuous row mounting.

**FINISH**

Post-painted with a 93% reflective white coat to improve luminaire efficacy, and all body components are seamlessly interlocked for added structural strength.

**MOUNTING**

Luminaires accommodate lay-in ceilings, Slot T, and T-bar suspension systems for 5/8" and 3/8" ceiling thicknesses. Four corner tie points are standard for safety wire support when required, with built-in earthquake clips, standard. Luminaires may be available with flange kits, surface mounted kits, and other options.

**OPTIONS**

Luminaires can be shipped pre-installed with whips, modular wiring systems, daylight harvesting controls, occupancy sensors, and/or power packs for individual or room control solutions.

**DRIVER ELECTRICAL INFORMATION**

Powered by high-quality constant-current power LED drivers which are rated for 50 to 60Hz at 120-277V input, produce less than 20% THD, and have a power factor of .90 to 1.00.

**WARRANTY**

Five-year warranty for parts and components. (Labor not included)

**LISTINGS**

c-UL-us - Listed for Feed Through Wiring.

Example: **22-OD-LED-WDM-35K-18K-3000L-DIM10-MVOLT-90**

22	OD-LED	WDM							
FIXTURE SIZE	SERIES	TECHNOLOGY	LUMENS	DIMMING		VOLTAGE	CRI	EMERGENCY	OTHER OPTIONS
22 - 2' X2'	OD-LED - LED Volumetric Troffer	WDM-35K-18K	2000L - 2000 lumens 3000L - 3000 lumens	DIM10 - 0-10V Dimming DIMST - Step Dimming LUTH - Lutron Hilume LUT2W - Lutron 2Wire ELDO10.1 - EldoLED 0-10V DALI.1 - EldoLED DALI ELDODMX.1 - EldoLED DMX		120 277 MVOLT	90+	EMG-LED-10 EMG-LED-20	22FK - 2'x2' Flange Kit SBF - Internal Fast Blow Fuse RIS - Radio Interference Suppressor USA - Made in America Compliance FS-PPV2 - Fixture Sensor Power Pack FD-301 - Low Voltage Daylight Dimming Photosensor LMFC-011 - Digital Lighting Manager FS-205 - Low Voltage Pir Fixture Integrated Occupancy Sensor

LUT2W are available in 120V only LUT2W up to 4000L  
 LUTH, ELDO10-.1, ELDODALI-.1, and ELDODMX-.1 are available in 120V and 277V  
 -Reference last page for Control Options

\*FD-301 & FS-205 require FS-PPV2- Power Pack



- 1- Luminaire will be shipped with Powerpacks pre-installed, ready to be integrated to designated control systems
- 2- Luminaire will be shipped with Sensors installed on the luminaire, allowing for individual luminaire control. Luminaires will be ready to be integrated with designated control systems
- 3- Luminaire will be shipped with Sensors to be remotely installed on the ceiling. Luminaires will be ready to be integrated with designated control systems

BRAND	EASYFIT by EnOcean	LUTRON	enlighted	LEVITON®	OSRAM	PHILIPS EasySense	legrand®
CONTROL UNIT	<input type="checkbox"/> LEDRU LED Relay Zone Controller 0-10V <sup>1</sup>	<input type="checkbox"/> FCJS-0-10 Lutron Vive 0-10V Individual Control Models <sup>1,4</sup>	<input type="checkbox"/> CU-4E-FMH Fixture Mount Control Unit <sup>1,5</sup>	<input type="checkbox"/> ZL027 -NOW Intellect Power Control Module <sup>1,6</sup>	<input type="checkbox"/> EN-WCM2-ZB-DR Wireless Control Module <sup>1,7</sup>	<input type="checkbox"/> XITANIUM SR LED DRIVER The Philips Advance Xitanium SR LED driver <sup>1,8</sup>	<input type="checkbox"/> LMFC-011 ON/OFF/0-10V dimming fixture controller <sup>1,9</sup>
	<input type="checkbox"/> LEDDU LED Zone Controller 0-10V <sup>1</sup>	<input type="checkbox"/> FCJS-ECO Lutron Vive Eco-system Individual Control Models <sup>1,4</sup>		<input type="checkbox"/> ZL027 -DLE Intellect Power Control Module <sup>1,6</sup>	<input type="checkbox"/> EN-ALC-ZB-BK-DR Wireless Area Lighting Control Module <sup>1,7</sup>		<input type="checkbox"/> FS-PP-V2 FS-PP Fixture Integrated Sensor Power Pack <sup>1,9</sup>
INTEGRAT OCCUPANCY& DAYLIGHT SENSOR	N/A	<input type="checkbox"/> DFCSJ-OEM-OCC Clear Connect (RF) and Occupancy/ Daylight Sensing <sup>2</sup>	<input type="checkbox"/> SU-5E-IoT IoT Node Micro Sensor <input type="checkbox"/> SU-5E-CL Connected Micro Sensor <input type="checkbox"/> SU-5E-IL Independent Micro Sensor <input type="checkbox"/> SU-5S-H(IoT/CL/IL) Surface Mount Sensor <b>(Must be Specified with CU- 4E-FMH Control Unit)</b> <sup>2</sup>	<input type="checkbox"/> ZL00J -TOW Intellect Intelligent Fixture Control System <sup>2</sup>	<input type="checkbox"/> EN-CLM-PIR-DD-ZB SensiLUM™ Wireless Integrated Sensor	<input type="checkbox"/> SNS200 SNS200 for grouping <sup>2</sup>	<input type="checkbox"/> FD-301 Fixture integrated Daylight Dimming Sensor <sup>2</sup>
				<input type="checkbox"/> ZL00J -DOW Intellect Intelligent Fixture Control System <sup>2</sup>	<input type="checkbox"/> ZBHA- CLM-DIM-ENC Connected Lighting Module DIM <sup>2</sup>	<input type="checkbox"/> SNS300 SNS300 for networks <sup>2</sup>	<input type="checkbox"/> FS-205 Fixture integrated passive infrared occupancy sensor <sup>2</sup>
*WIRELESS OCCUPANCY SENSOR	<input type="checkbox"/> EOSCU-W-EO Occupancy Sensor - Ceiling Mounted <sup>3</sup>	<input type="checkbox"/> LRF2-OCR2B-P-WH Ceiling mount 360° ,occupancy/vacancy sensor <sup>3</sup>	N/A	N/A	<input type="checkbox"/> EN-SCPPH- 1500-ZB Wireless Passive Infrared Occupancy and Photo Sensors <sup>3</sup>	N/A	<input type="checkbox"/> LMDC-100 Dual technology PIR Ceiling Mount Occupancy Sensor <sup>3</sup>
*WIRELESS DAYLIGHT SENSOR	<input type="checkbox"/> ELLSU-W-EO Light Level Sensor - Ceiling Mounted <sup>3</sup>	<input type="checkbox"/> LRF2-DCRB-WH Ceiling-mount daylight sensor <sup>3</sup>	N/A	N/A	<input type="checkbox"/> EN-SCPPH- 1500-ZB Wireless Passive Infrared Occupancy and Photo Sensors <sup>3</sup>	N/A	<input type="checkbox"/> LMLS-400 Single zone switching and dimming digital photosensor <sup>3</sup>
*WIRELESS OCCUPANCY & DAYLIGHT SENSOR	N/A	N/A	<input type="checkbox"/> SU-5E-IoT IoT Node Micro Sensor <input type="checkbox"/> SU-5E-CL Connected Micro Sensor <input type="checkbox"/> SU-5E-IL Independent Micro Sensor <input type="checkbox"/> SU-5S-H(IoT/CL/IL) Surface Mount Sensor <b>(Must be specified with CU- 4E-FMH Control Unit)</b> <sup>3</sup>	<input type="checkbox"/> ZL00J -TOW Intellect Intelligent Fixture Control System  <input type="checkbox"/> ZL00J -DOW Intellect Intelligent Fixture Control System <b>(Must be specified with ZL027-NOW and ZL00J- DOW Control unit)</b> <sup>3</sup>	<input type="checkbox"/> EN-CLM- PIR-DD-ZB SensiLUM™ Wireless Integrated Sensor  <input type="checkbox"/> ZBHA- CLM-DIM-ENC Connected Lighting Module DIM <b>(Must be specified with EN-WCM2-ZB-DR or EN-ALC-ZB-BK-DR Control Unit)</b> <sup>3</sup>	<input type="checkbox"/> SNS200-CMP SNS-200 for Grouping <sup>3</sup>	N/A
ACCESORIES	N/A	N/A	<input type="checkbox"/> TMC-SU-5E Tile Mount Carrier <input type="checkbox"/> CBL-5E-CU4-30N 30 inch Sensor cable for CU-4 and IoT Ready <input type="checkbox"/> CBL-5E-CU4-7F 7 Foot sensor cable for CU-4 and IoT Ready Driver	N/A	N/A	N/A	N/A
NOTES	N/A	4- Luminaire will be compatible with LUTRON LRF2-OCR2B-PWH Ceiling mount 360deg occupancy/ vacancy sensor & LRF2-DCRB-WH ceiling mount daylight sensor. Sensors must be orderd through Lutron	5- Luminaire will be compatible with ENLIGHTED SU-5E-IoT, SU-5E-CL, SU-5E-IL, SU-5SH, Sensors	6- Luminaire will be compatible with LEVITON I ntellect APP & Keypad room controller	7- Luminaire will be compatible with EN-SCPPH-1500-ZB Wireless passive infrared occupancy and photo sensor	8- Luminaire will be compatible with philips field and wireless switch	9- Luminaire will be compatible with DLM Room control system LMPB-100. . Sensors must be orderd through Legrand.