



DIMENSION:
LENGTH: 47-1/2"(2X4) (1X4), 23-1/4"(2X2)
WIDTH: 4-3/8"
DEPTH: 1-1/4"



(On selected configuration, consult factory)

4000
LUMENS
38
WATT

5000
LUMENS
52
WATT

6000
LUMENS
69
WATT

8000
LUMENS
90
WATT

LED
ORDK

APPLICATION:

Retrofits Recessed Direct/Indirect

PRODUCT FEATURES:

- Spacing criteria 0-Deg: 1.2, 90-Deg:1.3
- Available in many lumen packages
- Driver and wiring access without the use of tools
- Dimming/occupancy sensor compatible

WARRANTY

One year standard warranty on fixture
5 year limited warranty on LED

CONSTRUCTION:

- Brackets are manufactured from code-gauge cold-rolled steel and have white baked enamel finishes

Reflectors: Precision formed, high performance, 95% total reflectance specular reflector, warranted for 25 years or 91% total reflectance white pre-painted aluminum

LED Retrofit Kit

Ordering Information: Example: 24-ORDK-LED-4000L-DIM10-MVOLT-30K-85

FIXTURE SIZE	SERIES	TYPE	LUMENS	DIMMING	VOLTAGE	CCT	CRI	EMERGENCY
24 - 2' X 4'	ORDK-Oracle LED Retrofit Kit for Direct/Indirect	LED	24-ORDK 4000L - (4000 lumens) 5000L - (5000 lumens) 6000L - (6000 lumens) 8000L - (8000 lumens)	DIM10 - 0-10V Dimming LUTH - Lutron Dimming DIMST - Step Dimming	MVOLT 347*	30K - (3000K) 35K - (3500K) 40K - (4000K) 50K - (5000K)	85	0-EMG-LED

* Consult factory for details