

T8/T5 FLUORESCENT DIRECT/INDIRECT LUMINAIRE (SURFACE OR SUSPENDED MOUNT)



APPLICATION:

The OB2DI Series Surface Mount Direct/Indirect Luminaire is the "Perfect" lighting solution for interior office, commercial and retail installations. Designed for general or task lighting. This economical alternative approach is the answer to meeting restrictive budgets with a modern lighting design.

PRODUCT FEATURES:

- Heavy-duty 20-gauge steel utilized throughout for durability and code compliance
- Painted high-gloss baked white enamel
- Pretreated with five-stage iron phosphate process to ensure superior paint adhesion
- Standard reflector comes in white highly reflective finish
- Shallow design is ideal for commercial and industrial spaces requiring general illumination
- Suitable for dry and damp environments
- Thermally protected, self-resetting, Class P, NPF, non-PCB and UL listed ballast
- Lightweight design enables for quick, easy installation
- NEC required ballast disconnect is standard
- CEE qualified ballast comes standard on most fixture options (Consult factory for details)

OPTIONS AND ACCESSORIES:

- Emergency ballast, motion sensors
- Reflector choices and lens option

LISTING

UL/C-UL listed to US and Canadian standard

WARRANTY

Guaranteed for one year against mechanical defects

Ordering Information > Example: 4-OB2DI-2-32-T8-ADV-10-MVOLT-EMG-T8-BX-700

4	OB2DI							
FIXTURE SIZE	SERIES	WATTAGE	VOLTAGE ¹	# OF BALLAST	BALLAST FACTOR	REFLECTOR		
4 - 4'	OB2DI-Oracle Surface Mount Direct/Indirect w/ Perforated Shield	4' FIXTURE 2-32-T8 (2 lamps/32W/T8) 2-28-T5 (2 lamps/28W/T5) 2-54-T5HO (2 lamps/54W/T5HO)	(Blank)- MVOLT (120/277) 120 277 347	(Blank)- 1 Ballast 2- 2 Ballasts	(Blank)- Normal BF HBF- High BF LBF- Low BF	(Blank)- White OB2DI-WSU- White/Slotted OB2DI-SR- Silver		
EMERGENCY BATTERY PACK OPTIONS (L. = LUMENS)								
BALLAST CONFIGURATION & CODE				ORDER CODE				
32W/T8	28W/T5	54W/T5HO	DESCRIPTION	DESCRIPTION				
(Blank)	-	-	Electronic Instant Start	EMG-T8-BX-450 Up to 450 L. for T8 or BX				
EPS	(Blank)	(Blank)	Electronic Program Start	EMG-T8-BX-600 Up to 600 L. for T8 or BX				
ADV-7	-	ADV-7	Advance Mark-7 ¹	EMG-T8-BX-700 Up to 700 L. for T8 or BX				
ADV-10	-	ADV-10	Advance Mark-10 ¹	EMG-T8-BX-1400 Up to 1400 L. for T8 or BX				
-	ADV-OPT	-	Advance Optanium ¹	EMG-T5-T5HO-700 Up to 700 L. for T5 or T5HO				
ADV-ESS	-	-	Advance Essential ¹	EMG-T5-T5HO-1300 Up to 1300 L. for T5 or T5HO				
ADV-ROVR	-	ADV-ROVR	Advance Rover ¹	EMG-SD-T8-BX-T5-T5HO-1400 Self-Diagnostic 1400 L. for T8, BX, T5 or T5HO				
LUT-EHD	LUT-EHD	LUT-EHD	Lutron Ecosystem H-Series ¹	EMG-ICE-T8-BX-T5-T5HO-1400 ICE Pack 1400 L. for T8, BX, T5 or T5HO				
LUT-2W	-	-	Lutron Tu-Wire ¹	GTD Generator Transfer Device				
LUT-EC5	LUT-EC5	-	Lutron Ecosystem ¹					
LUT-EC3	LUT-EC3	LUT-EC3	Lutron Eco-10 ¹					
LUT-TVE	-	-	Lutron Tve ¹					
LUT-H3D	LUT-H3D	LUT-H3D	Lutron Hi-Lume 3D ¹					
-	-	LUT-ECD	Lutron Ecosystem (317V Only) ¹					
WIRING OPTIONS				OTHER OPTIONS				
C3	- 6' 3-wire Flex Cable (Single Circuit)			INMS	- Motion Sensor			
C4	- 6' 4-wire Flex Cable (Double Circuit)			OCGSS	- Cable Gripper Suspension Kit			
FBF	- Internal Fast Blow Fuse			USA	- Made in America Compliance			

1 - Voltage must be specified for dimming ballast.

¹- Voltage must be specified for dimming ballast.

T8/T5
OB2DI

4' Fluorescent Direct/Indirect Luminaire