



#### INTENDED USE:

- For use in residential, commercial and hospitality markets
- For wall or vanity application
- Fixture is designed for optional up/ down directional lighting
- Baffle front cover plate is also removable for 180° illumination

#### PRODUCT FEATURES:

- Comes standard with multi-volt ballast
- Available in prismatic acrylic lens and white end caps
- Individually boxed
- Diffuser easily removed via locking nut at both ends of fixture
- Post-painted body and hemmed edges allow for safe handling and installation
- CEE qualified ballast comes standard on most fixture options (Consult factory for details)

#### OPTIONAL FEATURES:

- Dividers for up/downlight
- Front baffle cover available for light block

#### LISTING

UL/C-UL listed to US and Canadian standard

#### WARRANTY

Guaranteed for one year against mechanical defects

### Ordering Information > Example: 4-OW2B-2-28-T5-MVOLT-EMG-T5-T5HO-700

<b>4</b>	<b>OW2B</b>								
<b>FIXTURE SIZE</b>	<b>SERIES</b>	<b>WATTAGE</b>		<b>VOLTAGE</b>	<b># OF BALLAST</b>	<b>BALLAST FACTOR</b>			
4 - 4'	OW2B-Oracle Fluorescent Wall/Ceiling Bracket	4' FIXTURE 2-28-T5 (2 lamps/28W/T5) 2-54-T5HO (2 lamps/54W/T5HO) 2-32-T8 (2 lamps/32W/T8)		(Blank) - MVOLT (120/277) 120 277 347	(Blank) - 1 Ballast 2 - 2 Ballasts	(Blank) - Normal BF HBF - High BF LBF - Low BF			
<b>EMERGENCY BATTERY PACK OPTIONS (L. = LUMENS)</b>									
ORDER CODE					DESCRIPTION				
EMG-T8-BX-450					Up to 450 L. for T8 or BX				
EMG-T8-BX-600					Up to 600 L. for T8 or BX				
EMG-T8-BX-700					Up to 700 L. for T8 or BX				
EMG-T8-BX-1400					Up to 1400 L. for T8 or BX				
EMG-T5-T5HO-700					Up to 700 L. for T5 or T5HO				
EMG-T5-T5HO-1300					Up to 1300 L. for T5 or T5HO				
EMG-SD-T8-BX-T5-T5HO-1400					Self-Diagnostic 1400 L. for T8, BX, T5 or T5HO				
EMG-ICE-T8-BX-T5-T5HO-1400					ICE Pack 1400 L. for T8, BX, T5 or T5HO				
GTD					Generator Transfer Device				
* 2' = For T8 only 450 L available * 2' = For T5 no emergency option available									
<b>WIRING OPTIONS</b>					<b>OTHER OPTIONS</b>				
FBF - Internal Fast Blow Fuse					INMS - Motion Sensor				
SBF - Internal Slow-Blow Fuse					USA - Made in America Compliance				
RIS - Radio Interference Suppressor									

#### BALLAST CONFIGURATION & CODE

15W/T8	17W/T8	25W/T8	32W/T8	59W/T8	14W/T5	24W/T5HO	21W/T5	39W/T5HO	28W/T5	54W/T5HO	DESCRIPTION
(Blank)	(Blank)	-	(Blank)	(Blank)	-	-	-	-	-	-	Electronic Instant Start
EPS	EPS	(Blank)	EPS	-	(Blank)	(Blank)	(Blank)	(Blank)	(Blank)	(Blank)	Electronic Program Start

Consult Factory for ADVANCE or LUTRON dimming ballast options.