


**MULTILUMEN  
SELECTOR**

EASY 3 COLORS  
**SELECCTOR**  
3500K • 4000K • 5000K



NOMINAL LUMENS	DELIVERED LUMENS	WATTAGE
10000	11600	75 W
8000	9280	60 W
6000	5965	45 W

Based on 4000K, 90+ CRI. Actual wattage may vary +/- 5%

**FEATURES**

The Architectural LED Linear combines a slim profile with clean lines, making it an ideal choice for library stacks or narrow aisles. The flexibility of the luminaire allows for continuous, uniform and glare-free illumination. Available in single pendant or continuous mounting for a seamless connection from luminaire to luminaire, with adjustable mounting heights. This distinct luminaire is a perfect solution for educational, healthcare, office, commercial and retail spaces.

LUMENS	6000L/8000L/10000L
CCT & DYNAMIC PLATFORMS	35K/40K/50K
CRI	85+ (Standard)
MOUNTING	Suspended or Surface
DIMMING & CONTROL	0-10V Flicker Free 1% Dimming Standard (DIM10)
EMERGENCY	10W - Up to 1000L output
LIFETIME	L70 at 167,000 Hours
OPERATING TEMPERATURE	-20°C to 50°C ambient temperature
PHOTOMETRIC TESTS	In Accordance with IES LM79-08, LM80 and TM-30, TM-21



