



MULTI LUMEN EASY 3 COLORS
SELECTOR SELECCTOR
3000K • 4000K • 5000K




DIMENSIONS



TOP VIEW



FRONT VIEW



NOMINAL LUMENS	DELIVERED LUMENS	WATTAGE
9000L	9000L	60W
10000L	10000L	80W
12000L	12000L	100W

Based on 4000K, 85+ CRI. Actual wattage may vary +/- 5%

FEATURES

This LED vapor tight series is designed with ultra-durable and thoroughly sealed construction for safe splash zone wet location use and corrosion resistance. A wide beam and low-glare illumination ensure peak performance, while multi-lumen, multi-CCT, and 0-10V dimming features make for a solution that is as versatile as it is tough. Suitable for suspended, surface, and 45° corner mounting. Ideal for use across parking garage, industrial non-food processing, laboratory, cold storage, and tunnel applications in factory, warehouse, and marine vessel settings.

NSF and IP66 rated, and compliant with NEMA4X standards. Only suitable for indoor or covered applications.

Available in 2 ft, 4 ft, and 8 ft lengths.

LUMENS	9000L/10000L/12000L
CCT	35K/40K/50K
CRI	85+ Standard
COLOR QUALITY	3-Step MacAdam Ellipse
LENGTH	8 ft
MOUNTING	Suspended, Surface, and Corner Mount
DIMMING	DIM10 - 0-10V Flicker Free 5% Dimming
FINISH	White (WH), Gray (GR)
OPERATING TEMP.	-40°C (-40°F) to 40°C (104°F)
EMERGENCY	0-EMG-LED
LIFETIME	L70 at 50,000 Hours
PHOTOMETRIC	In accordance with IES LM79-08, LM80 and TM-30, TM-21

OPTICS

Features a frosted shatterproof polycarbonate (PC) lens and an environmentally friendly powder coat painted reflector for a smooth, evenly diffused illumination and UV free beam.

High efficiency LEDs with an efficacy of 130lm/W to meet DLC standards.

Luminaire available in a lumen package of 9000L/10000L/12000L for customizable intensity with a variety of uses. Three selectable color temperatures of 3500K/4000K/5000K enable different warm to cool moods and atmospheres.

CCT factory set to 5000K; lumen factory set to 12000L.

CONSTRUCTION

Housing made from a sturdy polycarbonate housing with fully gasketed IP66 construction for ingress protection against dust, water, and contaminants*.

Meets NEMA 4X standards for corrosion resistance against salt spray, fumes, and chemicals, as well as protection against damage caused by the external formation of ice.

An organic curved design eliminates sharp corners for safe handling and installation.

Lens secured by stainless steel lens clips designed with side sealing and locking technology to ensure reliable ingress protection.

Four knockouts located on luminaire back for wiring. Side wiring entrance includes a watertight wet location fitting to help protect electrical components from contact with moisture.

Integrated damp location driver located on inside of luminaire, behind LED board.

Multi-lumen and multi-CCT switches located on LED board. Available in a white finish.

* Note that the durability of polycarbonate can be affected by certain airborne contaminants such as ketones, alkaline solutions, esters, hydrocarbons, alcohols, and certain solvents and oxidizing agents.

MOUNTING

Suitable for surface, suspended, and 45° corner mount.

MAINTENANCE

Fixture may be safely sprayed clean or hosed down to undergo necessary harsh sanitation procedures.

Pinching clips on both ends of the LED board and allows for the board to be pulled out for driver access.

OPTIONS & ACCESSORIES

Snap-in surface mount bracket and v-hook for use with suspension chain included.

Available to Order Separately:

- Corner bracket for 45° corner mount
- S05 6 ft power cord
- 120V/277V plug

DRIVER & ELECTRICAL INFORMATION

Powered by high-quality constant-current power LED drivers which are rated for 50 to 60Hz at 120/277V input., produce less than 20% THD, and have a power factor of .90 to 1.00.

DIMMING

DIM10 - 0-10V 5% dimming on MVOLT 120-277V.

WARRANTY

5-year warranty for parts and components (labor not included).

LISTINGS

cUL listed.
Wet location rated.
NSF Splash Zone and Non Food Zone rated.
NEMA 4X IP66 rated.
DLC Premium listed.
RoHs - lead and mercury free.

Example: **8-OW2IP-LED-9000L/10000L/12000L-DIM10-MVOLT-35K/40K/50K-85**

8	OW2IP-LED								
SIZE	SERIES	LUMENS	DIMMING	VOLTAGE	CCT	CRI	EMERGENCY	MOUNTING	OPTION
8 - 8'	OW2IP-LED	9000L/1000L/12000L	DIM10 (0-10V)	MVOLT (120/277V)	35K/40K/50K	85	O-EMG-LED-10W (Consult Factory)	(Blank) - Surface Mount Bracket and V-hook (Included) 45D-CMB - Corner bracket for 45° corner mount CH - Heavy Duty Chain GSS - Gripper Suspension System GSSP - Gripper Suspension System with Paddles	S05 - 6ft Power Cord PCTL120 - 10' 120V Twist Lock Plug PCTL277 - 10' 277V Twist Lock Plug FSP-311-B-D - 0-10V continuous dimming PIR photo/motion HC - Radio Interference Suppressor SSL - Stainless Steel Latches SSLTP - Stainless Steel Latches with Tamper Proof Screws OSM3D-V1W - Line Voltage Microwave Sensor (integrated) OSM3D-DDW-20 - HF Microwave Sensor 0-10V 20% Dim (integrated for indoor use) OSM3D-DDW-50 - HF Microwave Sensor 0-10V 50% Dim (integrated for indoor use) OFD1Z-10W - IP66 PIR Side Mount Sensor with Bluetooth option USA - Made in America Compliance