

B26R

6" Shallow Non-IC Remodel Housing

LAMP WATTAGE: (1) MAX. 150W R40/PAR38, 120W BR40, 85W BR30, 150W A21



DESIGNED FOR 2" X 6" JOIST CONSTRUCTION




DESCRIPTION

Thermally protected, specification grade remodel recessed housing. For remodel applications where insulation can be kept 3" from housing. Accommodates up to 150W R40/PAR38, 120W BR40, 85W BR30 and 150W A21 lamps. For fast and easy installation in existing plaster or mechanical ceilings from ½" to 1-3/8" thick. Four remodel clips are easily retractable for fixture removal if necessary. Junction box is provided with eight ½" KOs and four Romex knockouts with strain relief.

SPECIFICATION

- A. HOUSING High temperature painted 22 gauge cold rolled steel construction for maximum heat dissipation and rust protection. Accommodates lamps up to 150W depending on trim used.
- B. SOCKET Medium base screw shell porcelain socket preinstalled on adjustable mounting bracket is designed to allow usage of different lamp types, as well as proper and consistent lamp positioning.
- C. INSTALLATION Four preinstalled spring clips which secure the housing firmly into ceiling to accommodate different ceiling thickness from ½" to 1-3/8".
- D. JUNCTION BOX UL listed for through-branch circuit wiring, provided with eight ½" KOs and four Romex knockouts with strain relief.
- E. THERMAL PROTECTION Standard thermal protection device guards against improper installation, overlamping and misuse of insulation material.



BEAM DIA. MEASURED AT 50% OF NADIR F.C.

FEATURES

- Thermally Protected Shallow Remodel Non-IC housing.
- · Dependable, favorable design and effortless installation.
- Unit slips through 6-1/2" ceiling opening.
- · Four preinstalled spring clips which secure the housing firmly into ceiling to accommodate different ceiling thickness from 1/2" to 1-3/8".
- · Can be installed from below the ceiling.
- · Adjustable socket bracket.
- · Wire through junction box.
- 5-1/2" height allows use in 2" x 6" joist construction.
- Preinstalled socket cap provides electrical contact protection against dust, paint and over spray.

OPTIONS AIR-SHUT

- Gasket to prevent air flow from heated or air conditioned spaces.
- . Meets all national air flow requirements.

UL AND C-UL LISTED

- For Damp location
- · For Feed-through wiring







ITEM SELECTOR: (Please check the boxes below for the option desired)


The Selection (i) least check the boxes below for the option desired)												
TYPE	AIR-SHUT	OPTION	TRIM TYPE						BAFFLE	REFLECTOR	TRIM/RING	GLASS
B26R	□ AT	☐ (W) With quick connects	□ B630	□ B616	□ B636	□ B645	□ B651	□ B688	□ W	□ CL	□ WH	☐ Green
			□ B640	□ B663	□ B642	□ B648	□ B611	□ B685	□ P	□ RG	□ BK	☐ Yellow
			□ B620	□ B664	□ B641	□ B652	□ B647	□ B696	□ SN	□ W	□ SN	□ Pink
			□ B631	□ B673	□ B656	□ B603	□ B644	□ B689	□ CP	□ MB	□ CP	□ Brown
			□ B632	□ B683	□ B657	□ B604	□ B650	□ B680	□ BZ	□ BZ	□ CH	☐ Navy Blue
			□ B607	□ B601	□ B637	□ B615	□ B622			□ CP	□ PB	☐ Orange
			□ B627	□ B601L	□ B643	□ B633	□ B623			□ SN	□ BZ	□ Blue
			□ B617	□ B605	□ B658	□ B634	□ B681			□ SHZ		☐ White
			□ B602	□ B605L	□ B659	□ B649	□ B687					□ Red
			□ B609	□ B606	□ B675	☐ AF633	□ B682					
			□ B619	□ B606L	□ B676	□ B225	□ B693					
			□ B646	□ B635	□ B612	□ B653	□ B694					

Specifications:

B26R

AIR-SHUT BAFFLE

*For custom baffle, reflector, trim ring, glass color and lens options, please consult factory,



Sample of Catalog Number: B26R-AT-W-B630-W-WH

6" Shallow **Incandescent Trims**

(LAMP WATTAGE: (1) MAX. 150W R40/PAR38, 120W BR40, 85W BR30, 150W A21)

Project Name: Type:

Note:

Catalog Number:


eitë Lighting

B630CP-CP **METAL STEPPED BAFFLE R30/PAR30**



BAFFLE FINISH: W, P, SN, CP, BZ

TRIM/RING FINISH: WH, BK, SN, CP, CH, PB. B7




B640SN-SN **METAL STEPPED BAFFLE R40/PAR38**



BAFFLE FINISH:

TRIM/RING FINISH: WH, BK, SN, CP, CH, PB. B7




B620-ORANGE GLASS TRIM



GLASS FINISH: GREEN, YELLOW PINK, BROWN, NAVY BLUE, ORANGE. WHITE, RED

B627RG-WH

REFLECTOR R40/PAR38




B631P-WH R30 PREMIUM PHENOLIC BAFFLE / METAL RING



BAFFLE FINISH:

TRIM/RING FINISH: WH, BK, SN, CP, CH, PB. B7




B632W-WH R40 PREMIUM PHENOLIC BAFFLE / METAL RING



BAFFLE FINISH:

TRIM/RING FINISH: WH, BK, SN, CP, CH,



B607CP-WH **REFLECTOR R/PAR30**



REFLECTOR FINISH: CL, RG, W, MB, CP, SN, BZ, SHZ

TRIM/RING FINISH: WH, BK, SN, CP, CH, PR R7



7-1/4"

WH, BK, SN, CP, CH, PB. B7




REFLECTOR FINISH: CL, RG, W, MB, CP, SN, BZ, SHZ







TRIM/RING FINISH: WH, BK, SN, CP, CH,



7-1/4"


B609W-WH REGRESSED EYEBALL WITH BAFFLE



BAFFLE FINISH: W, P, SN, CP, BZ

TRIM/RING FINISH: WH, BK, SN, CP, CH, PB. BZ

EYEBALL FINISH: WH, BK, SN, CP, CH, PB, BZ



B619RG-PB REGRESSED EYEBALL WITH REFLECTOR



REFLECTOR FINISH: CL, RG, W, MB, CP, SN

TRIM/RING FINISH: WH, BK, SN, CP, CH, PR B7


EYEBALL FINISH: WH, BK, SN, CP, CH, PB, BZ





BAFFLE FINISH:

TRIM/RING FINISH:



B616W-WH PAR20 REGRESSED EYEBALL W/ BAFFLE



BAFFLE FINISH: W, P, SN, CP, BZ


TRIM/RING FINISH: WH, BK, SN, CP, CH, PR R7

EYEBALL FINISH: WH, BK, SN, CP, CH, PB, BZ

B663PB PAR30 GIMBAL RING




TRIM/RING FINISH: WH, BK, SN, CP, CH, PB. BZ



B664CP PAR38 GIMBAL RING



TRIM/RING FINISH: WH, BK, SN, CP, CH, PB. BZ




PAR30 BAFFLE W/ GIMBAL RING



BAFFLE FINISH: W, P, SN, CP, BZ

TRIM/RING FINISH: WH, BK, SN, CP, CH, PB. BZ



B683CL-WH PAR30 REFLECTOR W/ GIMBAL RING



REFLECTOR FINISH: CL, RG, W, MB, CP, SN

TRIM/RING FINISH: WH, BK, SN, CP, CH, PB. BZ





Submittal form is available @ www.iuseelite.com Tel: 323-888-1973 • Fax: 323-888-1977

Specifications and Dimensions subject to change without notice.

REV: MAXILUME-SPEC-05-26-2011

6" Shallow **Incandescent Trims**

(LAMP WATTAGE: (1) MAX. 150W R40/PAR38, 120W BR40, 85W BR30, 150W A21)

Catalog Number: Project Name: Type: Note: LIGHTING

B601L










LENS: ALBALITE TRIM/RING FINISH: WHITE PLASTIC

B605PB METAL FRESNEL LENS

LENS:



FRESNEL TRIM/RING FINISH: WH, BK, SN, CP, CH, PB, BZ




B605L PLASTIC FRESNEL LENS



LENS: **FRESNEL** TRIM/RING FINISH: WHITE PLASTIC

BAFFLE W/ FRESNEL LENS



B606CP METAL DROP OPAL LENS

LENS:

ALBALITE



LENS: DROP OPAL TRIM/RING FINISH: WH, BK, SN, CP, CH, PB, BZ

B606L PLASTIC DROP OPAL LENS



DROP OPAL TRIM/RING FINISH: WHITE PLASTIC

B642CL-WH



B635P-WH **BAFFLE W/ ALBALITE LENS**



BAFFLE FINISH: W, P, SN, CP, BZ TRIM/RING FINISH:

WH, BK, SN, CP, CH, PB, BZ




7-1/4"

BAFFLE FINISH: W, P, SN, CP, BZ


B636W-WH

TRIM/RING FINISH: WH, BK, SN, CP, CH, PB, BZ



B641RG-WH REFLECTOR W/ ALBALITE LENS





REFLECTOR FINISH: CL, RG, W, MB, CP, SN. SHZ

> TRIM/RING FINISH: WH, BK, SN, CP, CH, PB. B7



REFLECTOR W/ FRESNEL LENS

B656W-WH **BAFFLE W/ FROSTED DOME SHOWER LENS**



BAFFLE FINISH: W, P, SN, CP, BZ

TRIM/RING FINISH: WH, BK, SN, CP, CH




B657CL-WH





REFLECTOR FINISH: CL, RG, W, MB, CP, SN. SHZ

TRIM/RING FINISH: WH, BK, SN, CP, CH, PB. B7




B637W-WH **BAFFLE W/ DROP OPAL LENS**



W, P, SN, CP, BZ TRIM/RING FINISH: WH, BK, SN, CP, CH, PB. BZ

BAFFLE FINISH:



B643RG-WH REFLECTOR W/ DROP OPAL LENS



REFLECTOR FINISH: CL, RG, W, MB, CP, SN. SHZ

TRIM/RING FINISH: WH. BK. SN. CP. CH PB, BZ



B658CL-WH **REFLECTOR W/ PRISMATIC LENS**



REFLECTOR FINISH: CL, RG, W, MB, CP SN. SHZ

TRIM/RING FINISH: WH, BK, SN, CP, CH,




B659CL-WH **REFLECTOR W/ FROSTED LENS**







TRIM/RING FINISH: WH, BK, SN, CP, CH,





6" Shallow **Incandescent Trims**

Note:

Catalog Number:

Project Name:

Type:

(LAMP WATTAGE: (1) MAX. 150W R40/PAR38, 120W BR40, 85W BR30, 150W A21)

e të lighting

BAFFLE W/ PRISMATIC LENS



BAFFLE FINISH:


W, P, SN, CP, BZ

TRIM/RING FINISH:

WH, BK, SN, CP, CH, PB, BZ












BAFFLE FINISH: W, P, SN, CP, BZ






SMOOTH FROST DOME SHOWER LENS





LENS: FROSTED

TRIM/RING FINISH: WH, BK, SN, CP, CH, PB, BZ




DESIGNER POINT SHOWER LENS



FROSTED/CLEAR





B648WH DESIGNER CONE SHOWER LENS











TRIM/RING FINISH: WH, BK, SN, CP, CH, PB, BZ



B652WH





SMOOTH FROST SHOWER LENS





LENS: FROSTED




B603CP

R/PAR30 OPEN TRIM



TRIM/RING FINISH: WH, BK, SN, CP, CH,




B604PB

R40/PAR38 OPEN TRIM




TRIM/RING FINISH: WH, BK, SN, CP, CH, PB, BZ



B615WH **DESIGNER PINHOLE**



TRIM/RING FINISH:




B633WH

R/PAR30 SPLAY TRIM



TRIM/RING FINISH:



B634WH

R40/PAR38 SPLAY TRIM



TRIM/RING FINISH:



B649RG-WH


PAR20 REFLECTOR



REFLECTOR FINISH: CL, RG, W, MB, CP. SN







AF633CH R/PAR30 OPEN TRIM



OPEN TRIM STEPPED BAFFLE



BAFFLE FINISH:

TRIM/RING FINISH:




B653W-WH

BAFFLE WITH BAFFLE



BAFFLE FINISH:

TRIM/RING FINISH: WH, BK, SN, CP, CH. PB



B651P-WH

PAR20 STEPPED BAFFLE



BAFFLE FINISH:









6" Shallow

Catalog Number:	
Project Name:	Type:
Note:	I'I M.










DESIGNER BAFFLE WALL WASH PAR20




R40/PAR38 WALL WASH REFLECTOR












W-WH, P-WH, SN-SN, CP-CP, BZ-BZ

COVER FINISH: WH, BK








TRIM/RING FINISH:

WH, BK, SN, CP, CH, PB, BZ

B623MB-WH






B681CP-WH

SQUARE BAFFLE TRIM



SQUARE REFLECTOR TRIM

B687CP-WH




TRIM/RING FINISH: WH, BK, SN, CP, CH, PB, BZ


COVER FINISH:

B682WH











TRIM/RING FINISH:



B694WH SQUARE PAR38 GIMBAL TRIM







B688WH SQUARE ALBALITE SHOWER TRIM








7-1/2

LENS: TRIM/RING FINISH:



B685WH SQUARE FRESNEL SHOWER TRIM





LENS:

TRIM/RING FINISH:



B696WH SQUARE DROP OIPAL SHOWER TRIM





B689WH SQUARE DESIGNER CONE SHOWER LENS






B680WH SQUARE DESIGNER POINT LENS





LENS: CLEAR TRIM/RING FINISH:





LENS: FROSTED/CLEAR TRIM/RING FINISH:

