

# **B4PLR**


# 4" Miniature Compact Fluorescent **Non-IC Remodel Housing**

**LAMP WATTAGE: UP TO 26W** 



# **DESIGNED FOR 2" X 6" JOIST CONSTRUCTION**





#### DESCRIPTION

Small aperture, thermally protected, specification grade compact fluorescent recessed housing. For remodel application non-insulated ceilings or where insulation can be kept 3" from housing. Accommodates (1) 9W, 13W, 18W or 26W compact fluorescent lamp. Four remodel clips are easily retractable for fixture removal if necessary. Junction box is provided with eight 1/2" KOs, and four Romex knockouts with strain relief.

#### **SPECIFICATION**

- A. HOUSING High temperature painted 22 gauge deep drawn single piece housing.
- B. SOCKET One vertically mounted plug-in socket. Unitized optics guarantees proper trim to housing installation. Tool-less installation adjusts from inside the housing.
- C. BALLAST Thermally protected, current controlled ballast, will produce full light output, increase lamp life with no noise and flicker. Ballast supplied is manufactured by Advance or Universal.
- D. INSTALLATION Four Preinstalled spring clips which secure the housing firmly into ceiling to accommodate ceiling thickness from 1/2" to 1-3/8".
- E. JUNCTION BOX feed through wiring with eight ½" KOs and four Romex knockouts with strain relief.

4"		Î
B4P	LR • B402CL 13W I	DTT
4'	22	8.9'
6'	11	13.3'
8'	6	17.8'
10'	4	22.2'
12'	2	26.7'
14'	1	30.1
Distance to Plane F(ft)	Initial Nadir Footcandles E(fc)	Beam Spread ø(ft)

BEAM DIA. MEASURED AT 50% OF NADIR F.C.

#### **FEATURES**

- Thermally Protected remodel fluorescent housing
- Dependable, favorable design and effortless installation.
- Unit slips through 4-1/4" ceiling opening.
- Four preinstalled spring clips which secure the housing firmly into ceiling to accommodate ceiling thicknesses from 1/2" to 1-3/8"
- · Can be installed from below the ceiling.
- Integral fluorescent ballast.
- 5-1/2" height allows use in 2" x 6" joist construction.

### **OPTIONS**

#### **AIR-SHUT**

- · Gasket to prevent air flow from heated or air conditioned spaces.
- . Meets all national air flow requirements.





**B4PLR** - ITEM SELECTOR: (Please check the boxes below for the option desired)

WATTAGE	BALLAST	VOLTAGE	EMERGENCY OPTIONS	TRIM TYPE		BAFFLE	REFLECTOR	TRIM/RING	GLASS
□ 1X9	(E) Electronic	☐ MVOLT (120/277)	☐ EMG 750 (750 Lumens) <sup>6</sup>	□ B401	□ B438	□ W	□ CL	□ WH	□ Green
□ 1X13	☐ (M) Magnetic <sup>1</sup>	□ 120	☐ EMG 1300 (1300 Lumens) <sup>6</sup>	□ B402	□ B439	□Р	□ RG	□ вк	☐ Yellow
□ 1X18*	☐ (S) Energy Star <sup>2</sup>	□ 277	☐ EMG-D-750 (750 Lumens) <sup>7</sup>	□ B406	□ B471	□ SN	□ W	□ SN	☐ Pink
□ 1X26*		□ 347	☐ ICE-1300 (1300 Lumens) <sup>8</sup>	□ B407	□ B473	□ CP	□ MB	□ CP	□ Brown
*Must use Philips PLT				□ B420	□ B444	□ BZ	□ BZ	□ CH	☐ Navy Blue
CFL lamps for 18W or 26W				□ B462			□ CP	□ PB	□ Orange
				□ B452			□ SN	□ BZ	☐ Blue
	DIMMING	AIR-SHUT	OTHER OPTIONS	□ B455			□ SHZ		☐ White
	☐ Mark 7 <sup>3</sup>	□ AT	□ FUSE 9	□ B451					□ Red
	☐ Mark 10 4		□ RIF 10	□ B454					
	☐ Lut-E (EC3D) <sup>5</sup>			□ B437					

1- (M) Magnetic = Available only in 9W fixture and not available in MVOLT • 2 - (S) Energy Star = Available on selected fixtures only, please see list above • 3 - MARK 7 = Not available in 9W, 13W, 57W, 70W • 4 - MARK 10 = Not available in 9W, 13W, 57W, 70W • 6 - EMG = Emergency battery pack w/ remote test switch • 7 - EMG-D = Emergency battery pack w/ remote test switch for damp location • 8 - ICE = Emergency battery pack w/ remote test switch operating between -18°C and 55°C • 9 - FUSE = Single slow-blow fuse • 10 - RIF = Radio interference filter

_			
Sp	ecit	icati	ions:

CL RG W MB BZ WH BK SN CP CH PB BZ Black Gold SN CP BZ Satin Nickel Copper White Black Satin Nickel Copper **B4PLR** Bronze Chrome Copper Satin Nickel BALLAST VOLTAGE AIR-SHUT **EMERGENCY** TRIM TYPE REFLECTOR RING Satin Haze

Sample of Catalog Number: B4PLR-1X26-E-MV0LT-EMG750-B401W-WH

\*For custom baffle, reflector, trim ring, glass color and lens options, please consult factor



# **CFL Trims**

( LAMP WATTAGE: **UP TO 26W** )


Catalog Number:	
Project Name:	Туре:
Note:	elite

#### B401CP-CP STEPPED BAFFLE



**BAFFLE FINISH:** W, P, SN, CP, BZ

TRIM/RING FINISH: WH, BK, SN, CP, CH,



#### B402CP-WH REFLECTOR



REFLECTOR FINISH: CL, RG, W, MB, CP. SN

TRIM/RING FINISH: WH, BK, SN, CP, CH, PB. B7



#### B406P-WH **WALL WASH WITH BAFFLE**




**BAFFLE FINISH:** W, P, SN, CP, BZ

TRIM/RING/COVER FINISH:

**ALBALITE LENS** 

**B452CP** 



#### B407CL-WH WALL WASH WITH REFLECTOR



**REFLECTOR FINISH:** CL, RG, W, MB, BZ, CP, SN, SHZ

TRIM/RING/COVER FINISH: WH. BK



#### **B420-GREEN GLASS TRIM**



**GLASS FINISH:** GREEN, YELLOW, PINK, BROWN, NAVY BLUE, ORANGE, WHITE, RED



#### B462CL-WH SEMI-FROSTED LENS WITH REFLECTOR



REFLECTOR FINISH: CL, RG, W, MB, CP. SN

TRIM/RING FINISH: WH, BK, SN, CP, CH, PB, BZ



# TRIM/RING FINISH:



WH, BK, SN, CP, CH, PB. BZ




## B455PB






TRIM/RING FINISH: WH, BK, SN, CP, CH, PB. BZ



#### B451PB **DROP OPAL LENS**



TRIM/RING FINISH: WH, BK, SN, CP, CH, PB. B7



#### B454CP-WH **CLEAR LENS WITH REFLECTOR**



REFLECTOR FINISH: CL, RG, W, MB, CP. SN

TRIM/RING FINISH: WH, BK, SN, CP, CH, PB, BZ



#### B437WH SMOOTH FROST SHOWER LITE



TRIM/RING FINISH: WH, BK, SN, CP, CH, PB. B7



#### B438WH **DESIGNER SHOWER LITE**




TRIM/RING FINISH: WH, BK, SN, CP, CH, PB. B7



#### **B439WH** SMOOTH FROST DOME SHOWER LITE



TRIM/RING FINISH: WH, BK, SN, CP, CH, PB. BZ



#### B471CP-WH **SQUARE STEPPED BAFFLE**



**BAFFLE FINISH:** W, P, SN, CP, BZ

TRIM/RING FINISH: WH, BK, SN, CP, CH, PB. BZ




#### B473CP-WH **SQUARE REFLECTOR**



REFLECTOR FINISH: CL, RG, W, MB, CP. SN

TRIM/RING FINISH: WH, BK, SN, CP, CH,



#### B444CL-WH

#### **SQUARE FROSTED LENS WITH REFLECTOR**



REFLECTOR FINISH: CL, RG, W, MB, CP. SN

TRIM/RING FINISH: WH, BK

