
# B5-GU24-RIC


# 5" Compact Fluorescent GU24 IC **Remodel Housing**

LAMP WATTAGE: (1) MAXIMUM 26W GU24





### **DESIGNED FOR 2" X 8" JOIST CONSTRUCTION**



#### DESCRIPTION

Thermally protected, IC rated specification grade remodel recessed housing. For remodeling installations where housing will be in direct contact with insulation. For fast and easy installation in existing plaster or mechanical ceilings from 1/2" to 1-3/8" thick. Four remodel clips are easily retractable for fixture removal if necessary. Junction box is provided with eight ½" KOs and four Romex knockouts with a strain relief. Accommodates up to 26W GU24 lamps.

#### **SPECIFICATION**

- A. HOUSING Die-formed, all aluminum construction for maximum heat dissipation and rust protection.
- B. SOCKET GU24 BASE is screwed to the top of housing but can be removed to snap into socket supporting trims
- C. INSTALLATION Four Preinstalled spring clips which secure the housing firmly into ceiling and accommodate ceiling thickness from ½" to 1-3/8".
- $\textbf{D. JUNCTION BOX}\ \text{- UL}\ \text{listed for feed through wiring,}$ provided with eight 1/2" KOs and four Romex knock-outs with strain relief.
- E. THERMAL PROTECTION Standard thermal protection device guards against improper installation, overlamping and misuse of insulation material.

# **120V**



**GU24 SOCKET** 

### **FEATURES**

- . Thermally Protected IC Remodel housing.
- Dependable, favorable design and effortless installation.
- Unit slips through 5-½" ceiling opening.
- Four Preinstalled spring clips which secure the housing firmly into ceiling to accommodate ceiling thickness from 1/2" to 1-3/8".
- · Can be installed from below the ceiling.
- 7" height allows use in 2" x 8" joist construction.
- · Wire through junction box.

## **OPTIONS**

### AIR-SHUT

- Gasket to prevent air flow from heated or air conditioned spaces.
- . Meets all national air flow requirements.
- Lamp must be ordered separately (please consult factory)

### **UL AND C-UL LISTED**

- For Damp location
- For Feed-through wiring
- · For Direct contact with insulation







B5-GU24-RIC - ITEM SELECTOR: (Please check the boxes below for the option desired)

WATTAGE	VOLTAGE	AIR-SHUT	OTHER OPTION	TRIM TYPE		BAFFLE	REFLECTOR	TRIM/RING	GLASS
Maximum lamp wattage 19W, see specific trims for details	□ 120	□ AT	☐ W - With Quick Connector	□ B530	□ B542	□ W	□ CL	□ WH	□ Green
				□ B507	☐ B504L	□Р	□ RG	□ BK	☐ Yellow
				□ B565	☐ B501L	□ SN	□ W	□ SN	□ Pink
				□ B520	☐ B505L	□ CP	□ MB	□ СР	□ Brown
				□ B525		□ BZ	□ BZ	□ CH	☐ Navy Blue
				□ B504			□ CP	□ PB	☐ Orange
				□ B501			□ SN	□ BZ	□ Blue
				□ B505			□ SHZ		☐ White
				□ B535					□ Red
				□ B536					
				□ B541					

**Specifications:** 

B5-GU24-RIC VOI TAGE AIR-SHUT OPTIONS TRIM TYPE REFLECTOR BAFFI F RING GLASS BAFFLE W W P Bla REFLECTOR TRIM/RING CL RG W MB BZ CP SN WH BK SN CP CH PB BZ Black Satin Nickel Satin Nickel Black Bronze Copper Polish Brass Satin Nickel

Sample of Catalog Number: B5-GU24-RIC-AT-W-B530W-WH

\*For custom baffle, reflector, trim ring, glass color and lens options, please consult factory