



B5IC

5" Universal IC Housing

LAMP WATTAGE: (1) MAXIMUM 75W R/PAR30, 60W A19, 65W BR30



DESIGNED FOR 2" X 8" JOIST CONSTRUCTION



Catalog Number:	
Project Name:	Type:
Note:	

DESCRIPTION
 New construction, thermally protected, IC rated specification grade recessed housing. Accommodates up to 75W PAR30, R30 lamps, 60W A19 lamps and 65W BR30 lamps. Furnished with preinstalled adjustable bar hangers. Junction box is provided with four ½" KOs, one ¾" KO and four Romex knockouts with strain relief.


SPECIFICATION
A. HOUSING - Die-formed all aluminum construction for maximum heat dissipation and rust protection. Adjusts vertically in plaster frame to accommodate ½" to 1-3/8" ceiling.

B. SOCKET - Medium base screw shell porcelain socket snaps into trim to allow usage of different lamp types, as well as proper and consistent lamp positioning.

C. BAR HANGERS - Preinstalled bar hangers allow housing to be positioned and locked at any point within a 24" joist span. They can be positioned on either the long or short axis of the housing and can be shortened for 12" joists. They contain a double-headed real nail for 20° downward angle for better contact, and the 90° pivoting mounting plate makes installation fast and accurate. Bar hangers can fit onto T-Bar spline with additional slots and holes for special mounting methods if necessary.

D. JUNCTION BOX - UL listed for through-branch circuit wiring and has four ½" KOs, one ¾" KO and four Romex knockouts with true pry-out slots and strain clamps.

E. THERMAL PROTECTION - Standard thermal protection device guards against improper installation, overlampping and misuse of insulation material.



- FEATURES**
- Thermally Protected IC housing.
 - Wire through junction box.
 - Preinstalled adjustable bar hanger.
 - Dependable, favorable design and effortless installation.
 - 7" height allows use in 2" x 8" joist construction.
 - Special screw on the frame locks bar hangers in place which prevents the housing from any movement once installed.
 - Preinstalled socket cap provides electrical contact protection against dust, paint and over spray.

- OPTIONS**
AIR-SHUT
- Gasket to prevent air flow from heated or air conditioned spaces.
 - Meets all national air flow requirements.

- UL AND C-UL LISTED**
- For Damp location
 - For Feed-through wiring
 - For Direct contact with insulation



ITEM SELECTOR: (Please check the boxes below for the option desired)

TYPE	AIR-SHUT	OPTION	TRIM TYPE		BAFFLE	REFLECTOR	TRIM/RING	GLASS
B5IC	<input type="checkbox"/> AT	<input type="checkbox"/> (W) With quick connects	<input type="checkbox"/> B530	<input type="checkbox"/> B541	<input type="checkbox"/> W	<input type="checkbox"/> CL	<input type="checkbox"/> WH	<input type="checkbox"/> Green
			<input type="checkbox"/> B507	<input type="checkbox"/> B542	<input type="checkbox"/> P	<input type="checkbox"/> RG	<input type="checkbox"/> BK	<input type="checkbox"/> Yellow
			<input type="checkbox"/> B563	<input type="checkbox"/> B504L	<input type="checkbox"/> SN	<input type="checkbox"/> W	<input type="checkbox"/> SN	<input type="checkbox"/> Pink
			<input type="checkbox"/> B502	<input type="checkbox"/> B501L	<input type="checkbox"/> CP	<input type="checkbox"/> MB	<input type="checkbox"/> CP	<input type="checkbox"/> Brown
			<input type="checkbox"/> B520	<input type="checkbox"/> B505L	<input type="checkbox"/> BZ	<input type="checkbox"/> BZ	<input type="checkbox"/> CH	<input type="checkbox"/> Navy Blue
			<input type="checkbox"/> B573		<input type="checkbox"/> CP	<input type="checkbox"/> PB	<input type="checkbox"/> Orange	
			<input type="checkbox"/> B504		<input type="checkbox"/> SN	<input type="checkbox"/> BZ	<input type="checkbox"/> Blue	
			<input type="checkbox"/> B501		<input type="checkbox"/> SHZ		<input type="checkbox"/> White	
			<input type="checkbox"/> B505				<input type="checkbox"/> Red	
			<input type="checkbox"/> B535					
			<input type="checkbox"/> B536					

Specifications:

B5IC	-	-	-	-	-	-	-
	AIR-SHUT	OPTION	TRIM TYPE	BAFFLE	REFLECTOR	TRIM/RING	GLASS

Sample of Catalog Number: B5IC-AT-W-B530-W-WH

BAFFLE	REFLECTOR	TRIM/RING
W White	CL Chrome	WH White
P Black	RG Gold	BK Black
SN Satin Nickel	W White	SN Satin Nickel
CP Copper	MB Black	CP Copper
BZ Bronze	BZ Bronze	CH Chrome
	CP Copper	PB Polish Brass
	SN Satin Nickel	BZ Bronze
	SHZ Satin Haze	

*For custom baffle, reflector, trim ring, glass color and lens options, please consult factory.



Submittal form is available @ www.iuseelite.com
 Tel: 323-888-1973 • Fax: 323-888-1977

Specifications and Dimensions
 subject to change without notice.
 REV: ELITE LIGHTING-SPEC-06-29-2011

5" Incandescent Trims

(LAMP WATTAGE: 75W R/PAR30, 60W A19, 65W BR30)

Catalog Number:

Project Name:

Type:


Note:

elite LIGHTING

**B530CP-CP
STEPPED BAFFLE**




AVAILABLE COLOR COMBINATIONS:
CP-CP, SN-SN, W-WH, P-WH, P-BK, BZ-BZ




**B507RG-WH
REFLECTOR**




AVAILABLE COLOR COMBINATIONS:
CP-CP, W-WH, RG-WH, MB-WH, CL-WH, MB-BK, RG-PB, CL-CH



**B563PB
PAR30 GIMBAL TRIM**




TRIM/RING FINISH:
WH, BK, SN, CP, CH, PB, BZ



**B502SN
EYEBALL**




TRIM/RING FINISH:
WH, BK, SN, CP, CH, PB, BZ



**B520-NAVY BLUE
GLASS TRIM**




GLASS FINISH:
GREEN, YELLOW, PINK, BROWN, NAVY BLUE, ORANGE, WHITE, RED



**B573W-WH
PAR30 BAFFLE W/ GIMBAL RING**



AVAILABLE COLOR COMBINATIONS:
CP-CP, SN-SN, W-WH, P-WH, P-BK




**B504WH
SHOWER TRIM**



FOR
WET
LOCATION

TRIM/RING FINISH:
WH, BK, SN, CP, CH, BZ




**B501CP
METAL ALBALITE LENS**



FOR
WET
LOCATION

TRIM/RING FINISH:
WH, BK, SN, CP, CH, BZ




**B505SN
METAL FRESNEL LENS**



FOR
WET
LOCATION

TRIM/RING FINISH:
WH, BK, SN, CP, CH, BZ




**B535P-WH
BAFFLE WITH ALBALITE LENS**



FOR
WET
LOCATION

AVAILABLE COLOR COMBINATIONS:
CP-CP, SN-SN, W-WH, P-WH, P-BK




**B536W-WH
BAFFLE WITH FRESNEL LENS**



FOR
WET
LOCATION

AVAILABLE COLOR COMBINATIONS:
CP-CP, SN-SN, W-WH, P-WH, P-BK




**B541RG-WH
REFLECTOR WITH ALBALITE LENS**



FOR
WET
LOCATION

AVAILABLE COLOR COMBINATIONS:
CP-CP, W-WH, RG-WH, MB-BK, CL-WH, MB-BK, RG-PB, CL-CH




**B542CL-WH
REFLECTOR WITH FRESNEL LENS**



FOR
WET
LOCATION

AVAILABLE COLOR COMBINATIONS:
CP-CP, W-WH, RG-WH, MB-BK, CL-WH, MB-BK, RG-PB, CL-CH




**B504L
PLASTIC SHOWER TRIM**



FOR
WET
LOCATION

TRIM/RING FINISH:
WHITE PLASTIC




**B501L
PLASTIC ALBALITE LENS**



FOR
WET
LOCATION

TRIM/RING FINISH:
WHITE PLASTIC




**B505L
PLASTIC FRESNEL LENS**



FOR
WET
LOCATION

TRIM/RING FINISH:
WHITE PLASTIC



elite LIGHTING

Submittal form is available @ www.iuseelite.com
Tel: 323-888-1973 • Fax: 323-888-1977

Specifications and Dimensions
subject to change without notice.

REV: MAXILUME-SPEC-05-26-2011