B5R 5" Universal Non-IC Remodel Housing

Catalog Number:

Project Name:

Note:


Type:

СІІС і і с н ті м с

LAMP WATTAGE: (1) MAXIMUM 75W R/PAR30, 60W A19, 65W BR30



DESIGNED FOR 2" X 8" JOIST CONSTRUCTION





ITEM SELECTOR: (Please check the boxes below for the option desired)

<u>□</u>
A
B
5-3/4"

DESCRIPTION Thermally protected, IC rated specification grade remodel recessed housing. For remodeling installations where housing will be in direct contact with insulation. For fast and easy installation in existing plaster or mechanical ceilings from 1/2" to 1-3/8" thick. Four remodel clips are easily retractable for fixture removal if necessary. Junction box is provided with eight 1/2" KOs and four Romex knockouts with a strain relief. Accommodates up to 75W PAR30, R30 lamps, 60W A19 lamps and 65W BR30 lamps.

SPECIFICATION

A. HOUSING - Die-formed, all aluminum construction for maximum heat dissipation and rust protection.

B. SOCKET - Medium base screw shell porcelain socket snaps into trim to allow usage of different lamp types, as well as proper and consistent lamp positioning.

C. INSTALLATION - Four Preinstalled spring clips which secure the housing firmly into ceiling and accommodate ceiling thickness from 1/2" to 1-3/8".

D. JUNCTION BOX - UL listed for feed through wiring, provided with eight 1/2" KOs and four Romex knockouts with strain relief.

E. THERMAL PROTECTION - Standard thermal protection device guards against improper installation, overlamping and misuse of insulation material.

5" B5R • B507CL 75W PAR30 FL LAMP 3' 222 26" 6' 52" 56 25 79" 9 Initial Nadir otcandles E(fc eam ad ø(ft)

BEAM DIA. MEASURED AT 50% OF NADIR F.C.

FEATURES

- Thermally Protected Non-IC remodel housing.
- · Dependable, favorable design and effortless installation.
- Unit slips through 5-1/2" ceiling opening.
- · Four Preinstalled spring clips which secure the housing firmly into ceiling to accommodate ceiling thickness from 1/2" to 1-3/8".
- · Can be installed from below the ceiling.
 - 7" height allows use in 2" x 8" joist construction.
 - · Wire through junction box.
 - Preinstalled socket cap provides electrical contact protection against dust, paint and over spray.

OPTIONS AIR-SHUT

- · Gasket to prevent air flow from heated or air conditioned spaces.
- · Meets all national air flow requirements.

UL AND C-UL LISTED

- For Damp location
- For Feed-through wiring

ТҮРЕ	AIR-SHUT	OPTION	TRIM TYPE		BAFFLE	REFLECTOR	TRIM/RING	GLASS
15R	□ AT	(W) With quick connects	□ B530	□ B541	D W	🗆 CL	🗆 WH	🗆 Green
			□ B507	□ B542	D P	🗆 RG	🗆 ВК	Yellow
			□ B563	□ B504L	□ SN	□ w	□ SN	Pink
			□ B502	□ B501L	□ CP	🗆 MB	□ CP	Brown
			□ B520	□ B505L	🗆 BZ	🗆 BZ	🗆 СН	Navy Blue
			□ B573			🗆 СР	D PB	□ Orange
			□ B504			□ SN	🗆 BZ	Blue
			□ B501			🗆 SHZ		□ White
			□ B505					🗆 Red
			□ B535					
			□ B536					
Specification 35R	s:		□ B536				P Black RG G SN Satin Nickel W V	CTOR TRIM/RIN Dhrome WH Wh Sold BK Bla White SN Sat Black CP CoP
bon	AIR-SHUT	OPTION TRIM TYP	BAFFLE	REFLECTOR	TRIM/RING	GLASS	BZ Bronze BZ E CP C	Bronze CH Chrom Copper PB Polish Satin Nickel BZ Bronze



Submittal form is available @ www.iuseelite.com Tel: 323-888-1973 • Fax: 323-888-1977

subject to change without notice.

REV: ELITE LIGHTING-SPEC-06-29-2011

5" **Incandescent Tri**

(LAMP WATTAGE: 75W R/PAR30, 60W A19, 65

6-1/2

6-1/2

 \longrightarrow

11

6-1/4"

elite

6-1/4"

B530CP-CP

STEPPED BAFFLE

AVAILABLE COLOR COMBINATIONS: CP-CP, SN-SN, W-WH, P-WH, P-BK, BZ-BZ

B520-NAVY BLUE

GLASS TRIM

GLASS FINISH: GREEN, YELLOW, PINK, BROWN, NAVY

BLUE, ORANGE, WHITE, RED

B505SN

METAL FRESNEL LENS

TRIM/RING FINISH: WH, BK, SN, CP, CH, BZ

B542CL-WH

AVAILABLE COLOR COMBINATIONS:

CP-CP, W-WH, RG-WH, MB-BK, CL-WH, MB-BK, RG-PB, CL-CH

REFLECTOR WITH FRESNEL LENS

10

6-1/4

6-1/4

	Catalog Number:								
Trims	Project I	lame:	Туре:	Туре:					
A19, 65W BR30)	Note:								
B507RG-WH REFLECTOR		B563PB Par30 Gimbal Trim	B502SM EYEBAI						
AVAILABLE COLOR COMBINATIONS: CP-CP, W-WH, RG-WH, MB-WH, CL-WH, MB-BK, RG-PB, CL-CH	0-1/2"	TRIM/RING FINISH: WH, BK, SN, CP, CH, PB, BZ		ING FINISH: SN, CP, CH,	6-1/4"				
B573W-WH Par30 Baffle W/ Gimbal R	ING	B504WH Shower Trim		B501CP METAL ALBALITE LENS					
AVAILABLE COLOR COMBINATIONS: CP-CP, SN-SN, W-WH, P-WH, P-BK	6-1/4" Botation	TRIM/RING FINISH: WH, BK, SN, CP, CH, BZ	TRIM/RI WH, BK, CH, BZ	J C	-1/4"				
B535P-WH BAFFLE WITH ALBALITE LENS	8	B536W-WH BAFFLE WITH FRESNEL LENS	B541R0 REFLEC	G-WH TOR WITH ALBALITE L	ENS				
	FOR								
AVAILABLE COLOR COMBINATIONS: CP-CP, SN-SN, W-WH, P-WH, P-BK	6-1/4"	AVAILABLE COLOR COMBINATIONS: CP-CP, SN-SN, W-WH, P-WH, P-BK		MB-BK, MB-BK,	6-1/4"				
B504L Plastic shower trim		B501L Plastic Albalite Lens	B505L PLASTI	C FRESNEL LENS					
	FOR								
TRIM/RING FINISH: WHITE PLASTIC		TRIM/RING FINISH:	TRIM/R	ING FINISH:					

Submittal form is available @ www.iuseelite.com Tel: 323-888-1973 • Fax: 323-888-1977

6-1/4

6-1/4"

6-1/4"