B62PLRIC


6" Dual Lamp CFL IC Remodel Housing

Catalog Number:	
Project Name:	Туре:
Note:	elite

LAMP WATTAGE: UP TO 2X13W



DESIGNED FOR 2" X 8" JOIST CONSTRUCTION



B62PLRIC - ITEM SELECTOR: (Please check the boxes below for the option desired)

DESCRIPTION

compact fluorescent recessed housing. For remodeling installations where housing will be in direct contact with insulation. Accommodates (2) 13W compact fluorescent lamp. For fast and easy installation in existing plaster or mechanical ceilings from ½" to 1-3/8" thick. Four remodel clips are easily retractable for fixture removal if necessary. Junction box is provided with eight 1/2" KOs and four

A. HOUSING - Die-formed all aluminum construction for maximum heat dissipation and rust protection.

B. SOCKET - Two vertically mounted plug-in socket. Unitized optics guarantees proper trim to housing installation. Tool-less installation adjusts from inside the housing.

C. BALLAST - Thermally protected, current controlled ballast, will produce full light output, increase lamp life with no noise and flicker. Ballast supplied is manufactured by Advance.

D. INSTALLATION - Four Preinstalled spring clips which secure the housing firmly into ceiling to accommodate ceiling thickness from 1/2" to 1-3/8".

E. JUNCTION BOX - E feed through wiring and provided with eight 1/2"KOs and four Romex knockouts with





Title 24 Approved only if ordered with electronic





Thermally protected, IC rated specification grade remodel Romex knockouts with strain relief.

BEAM DIA, MEASURED AT 50% OF NADIR F.C.

B62PLRIC • B701CL 2X13W DTT

26

12

11

6

3

9.2'

13.6'

18.1

22.5

27.0

30.4

FEATURES

- Thermally Protected remodel compact fluorescent IC housing.
- Integral fluorescent ballast.

6"

4'

6'

8'

10 12

14

- Unit slips through 6-1/2" ceiling opening.
- Four Preinstalled spring clips which secure the housing firmly into ceiling to accommodate ceiling thickness from 1/2" to 1-3/8"
- · Can be installed from below the ceiling.
- · Adjustable socket bracket.
- · Wire through junction box.
- Dependable, favorable design and effortless installation.
- 7-1/4" height allows use in 2" x 8" joist construction.

OPTIONS

AIR-SHUT

- · Gasket to prevent air flow from heated or air conditioned spaces
- . Meets all national air flow requirements.

ballast and Air-Shut.

WATTAGE	BALLAST	VOLTAGE	EMERGENCY OPTIONS	TRIM TYPE			BAFFLE	REFLECTOR	TRIM/RING	GLASS
□ 2X13W	☐ (E) Electronic	□ 120	☐ EMG 750 (750 Lumens) ⁶	□ B701	□ B706	□ B736	□ W	□ CL	□ WH	□ Green
	☐ (S) Energy Star ²	□ 277	☐ EMG 1300 (1300 Lumens) ⁶	□ B702	□ B706L	□ B757	□ P	□ RG	□ вк	☐ Yellow
			☐ EMG-D-750 (750 Lumens) ⁷	□ B620	□ B707	□ B758	□ SN	□ W	□ SN	☐ Pink
			☐ ICE-1300 (1300 Lumens) ⁸	□ B703	□ B707L	□ B760	□ СР	□ MB	□ CP	□ Brown
				□ B704	□ B743	□ B759	□ BZ	□ BZ	□ CH	☐ Navy Blue
				☐ B751	□ B756	□ B788		□ CP	□ PB	☐ Orange
	DIMMING	AIR-SHUT	OTHER OPTIONS	□ B752	□ B741	□ B785		□ SN	□ BZ	☐ Blue
	☐ Mark 7 ³	□ AT	□ FUSE 9	□ B753	□ B742	□ B796		□ SHZ		☐ White
			☐ RIF 10	□ B754	□ B737	□ B780				□ Red
				□ B705	□ B755	□ B789				
				□ B705L	□ B735					

(Note: CA Title 24 approved only if ordered with electronic ballast and Air-Shut.) 1- (M) Magnetic = Available only in 9W fixture and not available in MVOLT • 2 - (S) Energy Star = Available on selected fixtures only, please see list above • 3 - MARK 7 = Not available in 9W, 13W, 57W, 70W • 4 - MARK 10 = Not available in 9W, 13W, 57W, 70W, must specify voltage • 5 - LUT-E (ECSD) = Not available in 9W, 13W, 57W, 70W • 6 - EMG = Emergency battery pack w/ remote test switch • 7 - EMG-D = Emergency battery pack w/ remote test switch for damp location • 8 - ICE = Emergency battery pack w/ remote test switch • 7 - EMG-D = Emergency battery pack w/ remote test switch for damp location • 8 - ICE = Emergency battery pack w/ remote test switch • 7 - EMG-D = Emergency battery pack w/ remote test switch • 7

BK SN CP CH Black RG Gold Black **Specifications:** SN CP BZ Satin Nickel Copper W MB BZ White Black Satin Nickel Copper **B62PLRIC** Bronze Chrome Copper Satin Nickel Polish Brass BALLAST VOLTAGE AIR-SHUT **EMERGENCY** TRIM TYPE REFLECTOR RING SN SHZ Satin Haze

Sample of Catalog Number: B62PLRIC-2X13W-E-120-EMG750-B701CL-WH

*For custom baffle, reflector, trim ring, glass color and lens options, please consult factor



CFL Trims

(LAMP WATTAGE: UP TO 2X13W)

Catalog Number: Project Name: Type: Note: eitë Lighting

B701CP-WH **CONE REFLECTOR**



AVAILABLE COLOR COMBINATIONS: CL-WH, CL-CH, SHZ-WH, RG-WH, W-WH, MB-WH, CP-CP, SN-SN



B702P-RG-WH **CONE REFLECTOR/BAFFLE TRIM**



BAFFLE FINISH: W, P

REFLECTOR FINISH: CL. RG


TRIM/RING FINISH: WH, BK, SN, CP, CH, PB, BZ



B620-NAVY BLUE GLASS TRIM



GLASS FINISH: GREEN, YELLOW PINK, BROWN, NAVY BLUE ORANGE WHITE, RED



B703RG-WH **WALL WASH REFLECTOR**



REFLECTOR FINISH: CL, RG, W, MB, CP, SN

COVER FINISH: WH. BK



B704W-CL REFLECTOR BAFFLE WALL WASH



BAFFLE FINISH:

REFLECTOR FINISH: CL, RG

COVER FINISH: WH, BK




B751WH

SMOOTH FROST DOME SHOWER LENS



LENS: **FROSTED**

TRIM/RING FINISH: WH, BK, SN, CP, CH, PB. BZ



B752WH

DESIGNER POINT SHOWER LENS



TRIM/RING FINISH: WH, BK, SN, CP, CH, PB. BZ

FROSTED/CLEAR




B753WH

DESIGNER CONE SHOWER LENS



LENS: **FROSTED**

TRIM/RING FINISH: WH, BK, SN, CP, CH, PB. BZ




B754WH SMOOTH FROST SHOWER LENS



LENS: FROSTED

TRIM/RING FINISH: WH, BK, SN, CP, CH, PB, BZ



B705CP

METAL ALBALITE LENS



TRIM/RING FINISH: WH, BK, SN, CP, CH, PB, BZ



B705L

LENS:

PLASTIC ALBALITE LENS



LENS: ALBALITE

TRIM/RING FINISH: WHITE PLASTIC



B706PB

METAL FRESNEL LENS



LENS: FRESNEL

TRIM/RING FINISH: WH, BK, SN, CP, CH, PB, BZ



B706L **PLASTIC FRESNEL LENS**



LENS: FRESNEL

TRIM/RING FINISH: WHITE PLASTIC



B707CP

LENS:

ALBALITE

METAL DROP OPAL LENS



DROP OPAL

TRIM/RING FINISH: WH, BK, SN, CP, CH, PB. BZ



B707L

PLASTIC DROP OPAL LENS



B743RG-WH

REFLECTOR W/ DROP OPAL LENS



REFLECTOR FINISH: CL, RG, W, MB, CP. SN







CFL Trims

(LAMP WATTAGE: UP TO 2X13W)

Catalog Number: Project Name: Type: Note:

B756CL-WH **REFLECTOR W/ PRISMATIC LENS**















B742CL-WH REFLECTOR W/ FRESNEL LENS







BAFFLE W/ DROP OPAL LENS

\A\/ = |

LIGHTING

REFLECTOR FINISH: CL, RG, W, MB, CP, SN





REFLECTOR FINISH: CL, RG, W, MB, CP. SN

TRIM/RING FINISH: WH, BK, SN, CP, CH, PR R7

B735P-WH



REFLECTOR FINISH: CL, RG, W, MB, CP. SN TRIM/RING FINISH:

WH, BK, SN, CP, CH, PB. BZ

B736W-WH



BAFFLE FINISH: W, P, SN, CP, BZ TRIM/RING FINISH: WH, BK, SN, CP, CH,

B757W-WH

B737W-WH



B755W-WH **BAFFLE W/ PRISMATIC LENS**

















BAFFLE W/ FROSTED DOME SHOWER LENS

BAFFLE FINISH: W, P, SN, CP, BZ

TRIM/RING FINISH: WH, BK, SN, CP, CH, PB. BZ





TRIM/RING FINISH: WH, BK, SN, CP, CH, PB. BZ



BAFFLE FINISH: W, P, SN, CP, BZ

TRIM/RING FINISH: WH, BK, SN, CP, CH, PB. BZ



BAFFLE FINISH: W, P, SN, CP, BZ TRIM/RING FINISH: WH, BK, SN, CP, CH, PB. BZ



B758CL-WH REFLECTOR W/ FROSTED DOME SHOWER LENS





B760W-WH **BAFFLE W/ FROSTED LENS**





B759CL-WH REFLECTOR W/ FROSTED LENS








REFLECTOR FINISH: CL, RG, W, MB, CP, SN

TRIM/RING FINISH: WH, BK, SN, CP, CH, PB, BZ





TRIM/RING FINISH: WH, BK, SN, CP, CH, PB, BZ

B796WH

LENS:





TRIM/RING FINISH: WH, BK, SN, CP, CH,



B788WH


SQUARE ALBALITE SHOWER LENS





LENS:

TRIM/RING FINISH:



B785WH **SQUARE FRESNEL LENS**









SQUARE SMOOTH FROST DOME LENS



B780WH







LENS: FROSTED











SQUARE DESIGNER POINT LENS







B789WH **SQUARE DESIGNER CONE LENS**





LENS: FROSTED

TRIM/RING FINISH:

