### **BL20N-E**

### 2" Miniature Low Voltage "Noise-Free" **Non-IC Housing**

#### LAMP WATTAGE: (1) MAXIMUM 12V 50W MR16






# 12-1/2" 2-3/4"

Small aperture low voltage, thermally protected new construction housing. Three remodel clips which can be accessed from below the ceiling, are easily retractable for fixture removal if necessary. Accommodates up to 50W MR16 lamps. Junction box is provided with three 1/3" KOs.

#### SPECIFICATION

- 1. HOUSING High-tempered twenty-two (22) gauge deep drawn single piece aluminum housing. Accommodates lamps up to 50W depending on trim used.
- 2. TRANSFORMER Class II dimming electronic transformer placed in the junction box.
- 3. BAR HANGERS Preinstalled bar hangers allow housing to be positioned and locked at any point within a 24" joist span and can be shortened for 12" joists. They contain a double-headed real nail for secure attachment into the joist. Bar hanger nails are installed on a 20° downward angle for better contact, and the 90° pivoting mounting plate makes installation fast and accurate. Bar hangers can fit onto T-Bar spline with additional slots and holes for special mounting methods if necessary.
- 4. JUNCTION BOX listed for through-branch cir-cuit wiring and has two 1/2" KOs.



REAM DIA MEASURED AT 50% OF NADIR E.C.

#### **FEATURES**

- · Integral low voltage electronic transformer to prolong lamp life and increase lighting quality.
- Thermally Protected Non-IC housing
- Three preinstalled spring clips which secure the housing firmly into ceiling to accommodate different ceiling thickness from 1/2" to 1-3/8".
- · Designed for accent and task lighting applications
- Dependable, favorable design and effortless installation
- 4-1/4" height allows use in 2" x 6" joist construction
- Preinstalled adjustable bar hanger

#### OPTIONS

- 1. AIR-SHUT
- · Gasket to prevent air flow from heated or air conditioned spaces.
- . Meets all national air flow requirements.





BL20N-E - ITEM SELECTOR: (Please check the boxes below for the option desired)

WATTAGE	BALLAST	VOLTAGE	TRIM TYPE	BAFFLE	REFLECTOR	TRIM RING	MR 16 LENS FILTER	
□ 20W	☐ (E) Electronic	□ 120	□ B1214	□ W	□ CL	□ WH	☐ BP8MR16-BL (Blue)	☐ BP8MR16-FR (Frosted)
□ 35W			□ B1215	□ P	□ RG	□ BK	☐ BP8MR16-GR (Green)	☐ BP8MR16-SP (Spread)
□ 50W			□ B1201	□ SN	□ W	□ SN	☐ BP8MR16-PI (Pink)	☐ BP8MR16-SF (Soft Focus)
			□ B1202	□ CP	□ MB	□ СР	☐ BP8MR16-PU (Purple)	☐ BP8MR16-HC (Honey Comb)
		OPTION	□ B1203	□ BZ	□ BZ	□ CH	☐ BP8MR16-DL (Day Light)	☐ BP8MR16-LI (Linear)
		☐ AT (Air-Shut)	□ B1204		□ CP	□ РВ	☐ BP8MR16-YE (Yellow)	☐ BP8MR16-SOL (Solite)
			□ B1209		□ SN	□ BZ	☐ BP8MR16-AM (Amber)	☐ BP8MR16-CL (Clear)
			□ B1212		□ SHZ		☐ BP8MR16-OR (Orange)	☐ BP8MR16-UV (Ultraviolet)
			□ B1213				☐ BP8MR16-RE (Red)	
			□ B1263					
			□ B1262					

#### **Specifications:**

BL20N-E

BALLAST REFLECTOR BAFFLE REFLECTOR TRIM/RING CL RG Black SN CP BZ SN CP CH White Satin Nickel Black Bronze Polish Brass Satin Nickel R7 Satin Haze

\*For custom baffle, reflector, trim ring, glass color and lens options, please consult factory.



Sample of Catalog Number: BL20N-E-20W-E-B1201-W-WH-BP8MR16-BL

Submittal form is available @ www.iuseelite.com Tel: 323-888-1973 • Fax: 323-888-1977

Specifications and Dimensions subject to change without notice

## 2"

# **Low Voltage Trims**


( LAMP WATTAGE: 50W 12V MR16 )

Catalog Number:	
Project Name:	Туре:
Note:	alitä:

#### B1214P-BK Adjustable Stepped Baffle (35° Tilt)




AVAILABLE COLOR COMBINATIONS: CP-CP, SN-SN, W-WH, P-WH, P-BK, BZ-BZ



#### B1215RG-WH ADJUSTABLE REFLECTOR (35° TILT)




AVAILABLE COLOR COMBINATIONS: CP-CP, W-WH, RG-WH, MB-WH, CL-WH, MB-BK, RG-PB, CL-CH



#### B1201P-BK REGRESSED STEPPED BAFFLE




AVAILABLE COLOR COMBINATIONS: CP-CP, SN-SN, W-WH, P-WH, P-BK, BZ-BZ



B1202RG-WH REFLECTOR



AVAILABLE COLOR COMBINATIONS: CP-CP, W-WH, RG-WH, MB-WH, CL-WH, MB-BK, RG-PB, CL-CH



#### B1203BK ADJUSTABLE SLOT APERTURE



B1204PB
ADJUSTABLE EYEBALL WALL WASH (35° TILT)



B1209CL-WH CROSSBLADE REFLECTOR



B1212CP ADJUSTABLE GIMBAL RING (35° TILT)



B1213WH ADJ. REGRESSED GIMBAL RING (35° TILT)



B1263P-BK BAFFLE SHOWER TRIM



B1262RG-WH REFLECTOR SHOWER TRIM



BAFFLE		REFI	LECTOR	TRIM RING		
W	White	CL	Chrome	WH	White	
Р	Black	RG	Gold	BK	Black	
SN	Satin Nickel	W	White	SN	Satin Nickel	
CP	Copper	MB	Black	CP	Copper	
ΒZ	Bronze	CP	Copper	CH	Chrome	
		SN	Satin Nickel	PB	Polish Brass	
				BZ	Bronze	

<sup>\*</sup>For custom baffle, reflector, trim ring, glass color and lens options, please consult factory.

