
BL30IC


3" Compact Low Voltage IC Housing

Catalog Number:	
Project Name:	Type:
Note:	elite

LAMP WATTAGE: (1) MAXIMUM 12V 20W MR16








DESCRIPTION

Small aperture, low voltage, thermally protected IC rated, specification grade recessed housing designed for new construction. Accommodates up to 20W MR16 lamps. Furnished with preinstalled adjustable bar hangers. Junction box is provided with four ½" KOs, one ¾" KO and four Romex knockouts with strain relief.

SPECIFICATION

- **A. OUTER HOUSING** Die-formed aluminum construction for maximum heat dissipating air chamber on top of the housing. Junction box could be accessed from inside and outside housing.
- **B. INNER HOUSING** Deep-drawn single piece aluminum construction for maximum heat dissipation and rust protection. Adjusts vertically in plaster frame to accommodate ½" to 1-3/8" ceiling.
- **C. TRANSFORMER** Enhanced in heat dissipating cover, to provide noise free operation. Attached to junction box cover so it may be serviced from below the ceiling. Thermally protected.
- E-Class II dimming electronic transformer (LighTech part #LET 75 BF)
- **D. BAR HANGERS** Preinstalled bar hangers allow housing to be positioned and locked at any point within a 24" joist span and can be shortened for 12" joists. They are designed to be hammered directly without using nails or screws and could be fit onto T-Bar spline for easy installation and quick alignment.
- **E. JUNCTION BOX** listed for through-branch cir-cuit wiring and has four ½" KOs, one ¾" KO and four Ro-mex knockouts with true pry-out slots and strain clamps.



BEAM DIA. MEASURED AT 50% OF NADIR F.C

FEATURES

- Integral low voltage transformer to prolong lamp life and increase lighting quality.
- . Thermally Protected IC housing.
- · Designed for accent and task lighting applications.
- · Wire through junction box.
- · Preinstalled adjustable bar hangers.
- · Dependable, favorable design and effortless installation.
- Special screw on the frame locks bar hangers in place which prevents the housing from any movement once installed.

OPTIONS

- 1. AIR-SHUT
- Gasket to prevent air flow from heated or air conditioned spaces.
- Meets all national air flow requirements.





BL30IC - ITEM SELECTOR: (Please check the boxes below for the option desired)

WATTAGE	BALLAST	TRIM TYPE				BAFFLE	REFLECTOR	TRIM RING	MR 16 LENS FILTER	
□ 20W	☐ (E) Electronic	☐ B1351 ¹	☐ B1372 ²	□ B1395	□ B1303	□ W	□ CL	□ WH	☐ BP8MR16-BL (Blue)	☐ BP8MR16-FR (Frosted)
		☐ B1353 ¹	☐ B1374 ²	□ B1390	□ B1314	□ P	□ RG	□ BK	☐ BP8MR16-GR (Green)	☐ BP8MR16-SP (Spread)
		☐ B1354 ¹	☐ B1375 ²	□ B1391	□ B1315	□ SN	□ w	□ SN	☐ BP8MR16-PI (Pink)	☐ BP8MR16-SF (Soft Focus)
		☐ B1355 ¹	☐ B1376 ²	□ B1320	□ B1362	□ CP	□ MB	□ CP	☐ BP8MR16-PU (Purple)	☐ BP8MR16-HC (Honey Comb)
	VOLTAGE	☐ B1356¹	□ B1396	□ B1325	□ B1352	□ BZ	□ BZ	□ CH	☐ BP8MR16-DL (Day Light)	☐ BP8MR16-LI (Linear)
	□ 120	☐ B1357 ¹	□ B1378	□ B1324	□ B1306		□ CP	□ PB	☐ BP8MR16-YE (Yellow)	☐ BP8MR16-SOL (Solite)
		☐ B1358 ¹	□ B1379	□ B1301	□ B1312		□ SN	□ BZ	☐ BP8MR16-AM (Amber)	☐ BP8MR16-CL (Clear)
		☐ B1359 ¹	□ B1383	□ B1302	□ B1368		□ SHZ	☐ CH¹	☐ BP8MR16-OR (Orange)	☐ BP8MR16-UV (Ultraviolet)
	OPTION	☐ B1360 ¹	□ B1380	□ B1316	□ B1304			☐ SS ²	☐ BP8MR16-RE (Red)	
	☐ AT (Air-Shut)	☐ B1370 ²	□ B1384	□ B1326	□ B1377					
		☐ B1371 ²	□ B1386	□ B1366	□ B1313					

1 = CH - Chrome finished • 2 = SS - Stainless Steel finished

 *For custom baffle, reflector, trim ring, glass color and lens options, please consult factory.



Sample of Catalog Number: BL30IC-20W-E-B1301-W-WH-BP8MR16-BL

Submittal form is available @ www.iuseelite.com

3" Low Voltage Trims

(LAMP WATTAGE: 75W 12V MR16 / 50W 120V GU10)

Catalog Number:	
Project Name:	Туре:
Note:	

B1351CH RUBY I



0.D.: 3-7/8" **FINISH TRIM:** CH (CHROME)

B1353CH RUBY II



0.D.: 3-7/8" **FINISH TRIM:** CH (CHROME)

B1354CH SAPPHIRE I



O.D.: 3-7/8"

FINISH TRIM: CH (CHROME)

B1355CH SAPPHIRE II



0.D.: 3-7/8"

FINISH TRIM: CH (CHROME)

B1356CH EMERALD



0.D.: 3-7/8" FINISH TRIM: CH (CHROME)

B1357CH EMERALD II



O.D.: 3-7/8"

FINISH TRIM: CH (CHROME)

B1358CH TOPAZ I



0.D.: 3-7/8" **FINISH TRIM:** CH (CHROME)

B1359CH TOPAZ II



0.D.: 3-7/8" **FINISH TRIM:** CH (CHROME)

B1360CH ONYX



0.D.: 3-7/8" FINISH TRIM: CH (CHROME)

B1370SS ADJ. STAINLESS STEEL GIMBAL TRIM



0.D.: 3-7/8" **FINISH TRIM:** SS (STAINLESS STEEL)

B1371SS STAINLESS STEEL LENSED TRIM



0.D.: 3-7/8"

FINISH TRIM: SS (STAINLESS STEEL)

STAINLESS STEEL EYEBALL TRIM



0.D.: 3-7/8"

FINISH TRIM: SS (STAINLESS STEEL)

SQUARE BAFFLE W/ SQUARE TRIM RING

B1374SS

ADJ. STAINLESS STEEL SQUARE GIMBAL TRIM



0.D.: 3-7/8"

FINISH TRIM: SS (STAINLESS STEEL)

B1375SS

0.D.:

STAINLESS STEEL SQUARE EYEBALL TRIM



J.: 3-7/8"

FINISH TRIM: SS (STAINLESS STEEL)

B1376SS Adj. Stainless Steel Square Eyeball Trim



0.D.: 3-7/8"

FINISH TRIM: SS (STAINLESS STEEL)



TRIM FINISH: WH, BK, SN, CP, CH, PB, BZ



Submittal form is available @ www.iuseelite.com Tel: 323-888-1973 • Fax: 323-888-1977 Specifications and Dimensions subject to change without notice.

REV: MAXILUME-SPEC-05-26-2011

Low Voltage Trims


(LAMP WATTAGE: 75W 12V MR16 / 50W 120V GU10)

Catalog Number:	
Project Name:	Type:
Note:	 عالک

B1378SN-SN STEPPED BAFFLE (35° TILT)




AVAILABLE COLOR COMBINATIONS:CP-CP, SN-SN, W-WH, P-WH, P-BK, BZ-BZ



B1379CL-WH **REFLECTOR (35° TILT)**




AVAILABLE COLOR COMBINATIONS: CL-WH, CL-SN, RG-WH, MB-WH, W-WH,MB-BK, RG-PB, SN-SN, CL-CH, CP-CP, CP-WH, SN-WH



B1383WH SLOT APERTURE (35° TILT)



TRIM FINISH: WH, BK, SN, CP, CH, PB, BZ



B1384P-WH **FULLY ADJUSTABLE W/ BAFFLE**



(35° TILT, 359° ROTATION)

AVAILABLE COLOR COMBINATIONS: W-WH, P-WH, P-BK CP-CP, SN-SN, BZ-BZ

B1395CL-SN



B1380WH FULLY ADJUSTABLE (35° TILT, 359° ROT.)



TRIM FINISH: WH, BK, SN, CP, CH, PB, BZ




B1386WH

FULLY ADJUSTABLE (75° TILT, 359° ROT.)





TRIM FINISH: WH, BK, SN, CP, CH, PB, BZ



B1390WH-PEACH METROPOLITAN ICE LITE



TRIM FINISH: WH, BK, SN, CP, CH, PB







SEMI-FROSTED SHOWER TRIM

REFLECTOR FINISH:





B1391P-WH PINHOLE WITH BAFFLE




AVAILABLE COLOR COMBINATIONS: CP-CP, SN-SN, W-WH, P-WH, P-BK, BZ-BZ



B1301CP-CP STEPPED BAFFLE




AVAILABLE COLOR **COMBINATIONS:** CP-CP, SN-SN, W-WH, P-WH, P-BK, BZ-BZ



B1302CP-WH REFLECTOR



AVAILABLE COLOR **COMBINATIONS:** CP-CP, CP-WH, W-WH, RG-WH, SN-SN, SN-WH, MB-WH, CL-WH, MB-BK



B1316CL-WH **REFLECTOR (35° TILT)**



AVAILABLE COLOR CL-WH, CL-SN, CL-PB



B1326CL-WH THE ILLUMINATOR II



B1366CL-WH THE ILLUMINATOR



RG-PB, CL-CH, CL-SN B1303WH **SLOT APERTURE**



B1314P-WH PINHOLE WITH BAFFLE






elité LIGHTING

3" Low Voltage Trims

Catalog Number:	
Project Name:	Туре:
Note:	alitä:





*For custom baffle, reflector, trim ring, glass color and lens options, please consult factory.