

BL6R

6" Low Voltage Non-IC Remodel Housing

LAMP WATTAGE: (1) MAXIMUM 12V 75W MR16/PAR36







Catalog Number: Project Name: Type: Note:


DESCRIPTION

Low voltage, thermally protected remodel housing. For remodel application where insulation can be kept 3" from housing. For fast and easy installation in existing plaster or mechanical ceilings from ½" to 1-1/8" thick. Four remodel clips are easily retractable for fixture removal if necessary. Accommodates up to 75W MR16 lamps or PAR36 lamps. Junction box is provided with four ½" KOs, one ¾" KO and four Romex knockouts with strain relief.

SPECIFICATION

A. HOUSING - High temperature painted 22 gauge deep drawn single piece housing. Accommodate lamps up to 75W depending on trim used.

- **B. TRANSFORMER** Enhanced in heat dissipating cover, to provide noise free operation. Attached to junction box cover so it may be serviced from below the ceiling. Thermally protected.
- M-Class H dimming magnetic transformer.
- **E**-Class II dimming electronic transformer (LighTech part #LET 75 BF)
- TOR-Class H dimming toroidal transformer, providing 35% more lumens than traditional transformers. Constructed of M3 grade silicone steel. (Must use dimmers rated for electromagnetic transformer)
- **C. JUNCTION BOX** Is provided with eight $\frac{1}{2}$ " KOs and four Romex knockouts with strain relief.
- **D. INSTALLATION** Four remodel clips are easily retractable for fixture removal if necessary.



BEAM DIA, MEASURED AT 50% OF NADIR F.C.

FEATURES

- \bullet Integral low voltage magnetic transformer improves lamp life and lighting quality.
- Thermally Protected Non-IC housing.
- Designed for accent and task lighting applications.
- · Wire through junction box.
- · Dependable, favorable design and effortless installation.
- Unit slips through 6-1/2" ceiling opening.
- Four Preinstalled spring clips which secure the housing firmly into ceiling to accommodate ceiling thickness from ½" to 1-3/8".

OPTIONS

- 1. AIR-SHUT
- Gasket to prevent air flow from heated or air conditioned spaces.
- Meets all national air flow requirements.





BL6R - ITEM SELECTOR: (Please check the boxes below for the option desired)

TEM DELEGIONE (I lease check the boxes below to the object)										
WATTAGE	BALLAST	VOLTAGE	TRIM TYPE		BAFFLE	REFLECTOR	TRIM RING	MR 16 LENS FILTER		
□ 20W-MR16	☐ (M) Magnetic	□ 120	□ B1601	□ B1620	□ W	□ CL	□ WH	☐ BP8MR16-BL (Blue)	☐ BP8MR16-FR (Frosted)	
☐ 35W -MR16	☐ (E) Electronic	□ 277	□ B1607	□ B1621	□Р	□ RG	□ BK	☐ BP8MR16-GR (Green)	☐ BP8MR16-SP (Spread)	
☐ 50W -MR16	☐ (TOR) Toroidal*		□ B1627	□ B1619	□ SN	□ W	□ SN	☐ BP8MR16-PI (Pink)	☐ BP8MR16-SF (Soft Focus)	
☐ 75W -MR16			□ B1605	□ B1663	□ CP	□ MB	□ CP	☐ BP8MR16-PU (Purple)	☐ BP8MR16-HC (Honey Comb)	
☐ 35W -PAR36		OPTION	□ B1608	□ B1673	□ BZ	□ BZ	□ CH	☐ BP8MR16-DL (Day Light)	☐ BP8MR16-LI (Linear)	
□ 50W -PAR36		☐ AT (Air-Shut)	□ B1606	□ B1683		□ CP	□ PB	☐ BP8MR16-YE (Yellow)	☐ BP8MR16-SOL (Solite)	
			□ B1602	□ B1643		□ SN	□ BZ	☐ BP8MR16-AM (Amber)	☐ BP8MR16-CL (Clear)	
			□ B1603	□ B1644		□ SHZ		☐ BP8MR16-OR (Orange)	☐ BP8MR16-UV (Ultraviolet)	
			□ B1651	□ B1642				☐ BP8MR16-RE (Red)		
			□ B1661	□ B1664						
			□ B1656	□ B1665						
			□ B1645							

*TOR -Toroidal available only in BL6R-50W-TOR-120V

Specifications:

BL6R

WATT BALLAST VOLTAGE OPTION TRIM TYPE BAFFLE REFLECTOR TRIM/RING FILTER (1) FILTER (2)

*For custom baffle, reflector, trim ring, glass color and lens options, please consult factory.

Black

REFLECTOR

BZ CP SN WH BK SN CP CH

PB BZ Black Satin Nickel


Coppe

BAFFLE

Satin Nickel

W P SN CP BZ

Submittal form is available @ www.iuseelite.com Tel: 323-888-1973 • Fax: 323-888-1977



Sample of Catalog Number: BL6R-20W-E-B1607W-WH-BP8MR16-BL

Low Voltage Trims

(LAMP WATTAGE: 75W 12V MR16 / 50W-PAR36)

Catalog Number:	
Project Name:	Туре:
Note:	elite

B1601W-WH **ADJUSTABLE SPOT (30° TILT)**







RING FINISH: WH, BK, SN, CP, CH, PB, BZ

B1607CP-CP

STEPPED BAFFLE (30° TILT)






REFLECTOR FINISH: CL. RG. W. MB. CP







TRIM FINISH: WH, BK, SN, CP, CH, PB, BZ




B1608WH **SURFACE ADJUSTABLE (75° TILT)**

RING FINISH:

WH, BK, SN, CP, CH, PB, BZ



B1606BK SURFACE ADJUSTABLE (45° TILT)



B1602WH **SLOT APERTURE (30° TILT)**




TRIM FINISH:


B1603P-WH PINHOLE BAFFLE



B1651P-WH STEPPED BAFFLE



B1661W-WH **ADJUSTABLE EYEBALL**




TRIM FINISH:





TRIM FINISH: WH, BK, SN, CP, CH, PB, BZ






TRIM FINISH: WH, BK, SN, CP, CH, PB, BZ


SEMI FROSTED SHOWER TRIM (30° TILT)




ADJUSTABLE SPOT (90° TILT)



ADJUSTABLE SPOT (30° TILT)




PAR36 GIMBAL RING



6" **Low Voltage Trims**

Catalog Number:	
Project Name:	Туре:
Note:	elite



BAFFLE		REF	LECTOR	TRIM RING		
W	White	CL	Chrome	WH	White	
P	Black	RG	Gold	BK	Black	
SN	Satin Nickel	W	White	SN	Satin Nickel	
CP	Copper	MB	Black	CP	Copper	
BZ	Bronze	CP	Copper	CH	Chrome	
		SN	Satin Nickel	PB	Polish Brass	
				BZ	Bronze	

*For custom baffle, reflector, trim ring, glass color and lens options, please consult factory.