

TRIM: 6101 REFLECTOR

MAX. LAMP WATTAGE: 150W-A21 / 150W PAR38 / 13W LED PAR30





- **A. Min. Height** = 8-1/2" Max. Height = 9-1/4" **B.** Trim Aperture = 6-1/8"
- **C. Cut-out** = 6-3/4"
- **D. Trim Outside Diameter** = 7-3/8"
- **E. Width** = 12-7/8"
- F. Length = 15"

DESCRIPTION

This fixture can support the use of LED PAR replacement lams.

- 1. SOCKET CUP Die-cast aluminum with medium base pulse rated porcelain socket with nickel-plated screw shell, effectively provides heat dissipation and ventilation. Unitized optics guarantees proper trim to housing installation. Tool-less installation and adjustability from either outside the housing or inside the housing allows the fixture to accommodate three different lamp sizes.
- 2. MOUNTING BRACKET Constructed from 16-gauge steel. Butterfly style mounting brackets accommodConstructed from 16-gauge steel. Can be installed with ¾" or 1-½" lathing channel, ½" EMT, or with optional C-channel mounting bars (Part# BP31) ordered separately. Housing can be adjusted from the inside of the ceiling.
- 3. RETAINING SPRINGS Precision tooled springs secure trim to mounting frame, for effortless and tool-less installation.
- 4. JUNCTION BOX Is UL listed for through-branch circuit wiring and has four ½" KO's, one 34" KO and four Romex knockouts with pry-out slots and strain clamps. Junction Box are accessible from below, no tools required.
- 5. THERMAL PROTECTOR Meets UL requirements. Standard thermal protection device guards against improper installation, over lamping and misuse of insulation material.
- **6. MOUNTING FRAME** Die-formed construction for maximum heat dissipation and rust protection.

OPTICS

- 7. REFLECTOR Self-flanged .050" aluminum reflector with low iridescent finish. Reflector provides 45-degree lamp-to-reflector image cutoff.
- 8. GROOVE BAFFLE Self-flanged one-piece aluminum with concentric rings.
- 9. LENS Choice of either tempered clear, tempered prismatic or tempered frosted lens fastened with two torsion springs for easy re-lamping. UL listed for wet or damp location.

LISTING

/UL listed for through-branch circuit wiring and damp locations. Wet location





Please visit our website for the most updated information on each product.

ITEM SELECTOR: (Please check the boxes below for the option desired)

Lumen values rated at 3000K color temprature.

TYPE	LAMP LUMEN	VOLTAGE	ANGLE	COLOR TEMPRATURE	TRIM TYPE & DESCRIPTION		REFLECTOR	BAFFLE	GLASS
C6INC	☐ PAR30-500L	120	☐ SP (10°)	☐ 27K	6101 Reflector	6109 Deco Glass Ring	☐ CL-WH	☐ W-CL-WH	Blue
	☐ PAR30-800L	□ 277	☐ WS (15°)	□ 30K	☐ 6102 Baffle with Reflector	☐ 6110 Double Ring Glass	☐ CL-SCH	☐ P-CL-WH	Green
	☐ PAR38-600L	(277 is not	☐ NF (25°)	☐ 40K	6103 Reflector with Fresnel Glass Lens	6111 Triple Ring Glass	☐ SHZ-SHZ	☐ W-WH	Red
	☐ PAR38-800L	dimmable)	☐ FL (40°)		6104 Reflector with Prismatic Glass Lens	☐ 6121 Stardust Deco Ring GLass	☐ SHZ-WH	☐ P-WH	☐ Frost
	PAR38-1000L				6105 Baffle with Fresnel Glass Lens	☐ 6122 Euro Deco Ring GLass	☐ WT-WH		
	PAR38-1300L				6106 Baffle with Prismatic Glass Lens	☐ 6123 Prism Deco Ring GLass	☐ W-WH		
	□ NO LAMP				6107 Wall Wash	☐ 6124 Geo Deco Ring GLass	☐ MB-WH		
					6108 Crossblade	☐ 6125 Central Etched Float GLass			
	OTHER OPTION				6112 Baffle with Frosted Glass Lens	☐ 6126 Diffusing Screen Wall Wash			
	☐ BP31				6113 Baffle with Tempered Clear Glass	☐ 6127 Geo Deco Ring GLass			
	(24" C-Channel				6114 Reflector with Frosted Glass Lens				
	Bar Hangers)				☐ 6115 Reflector with Tempered Clear Glass				

Specifications:

C6INC

OPTIONS TRIM TYPE REEL ECTOR BAFFI F VOI TAGE GLASS

WWW.MAXILUME.COM • TEL 1-877-375-5555 • FAX 1-877-375-3333



 $_{\perp}$

SHZ Satin Haze

XX09, XX10 and

6"



TRIM FINISH:

- WT-WH CL-WH
- CL-SCH W-WH • SHZ-SHZ • MB-WH
- SHZ-WH



A= 7-1/8' **B**= 7-3/8'



TRIM FINISH:

- W-CL-WH
- P-CL-WH







TRIM FINISH:

- CL-WH WT-WH CL-SCH W-WH
- SHZ-SHZ MB-WH

Reflector with Frosted Glass Lens

• SHZ-WH

6114







- WT-WH CL-WH
- CL-SCH W-WH
- SHZ-SHZ MB-WH
- SHZ-WH



6103

Reflector with Fresnel Glass Lens



TRIM FINISH:

- WT-WH CI -WH
- CL-SCH W-WH
- SHZ-SHZ MB-WH
- SHZ-WH



6104

Reflector with Prismatic Glass Lens



TRIM FINISH:

- WT-WH CI -WH
- CL-SCH W-WH
- SHZ-SHZ MB-WH • SHZ-WH







• SHZ-WH



6115 Reflector with Tempered Clear Glass

TRIM FINISH:

- CL-WH WT-WH
- CL-SCH W-WH
- SHZ-SHZ MB-WH • SHZ-WH



Baffle with Tempered Clear Glass



6105

Baffle with Fresnel Glass Lens

WET



TRIM FINISH:

• W-WH • P-WH









Baffle with Prismatic Glass Lens



TRIM FINISH:

- W-WH
- P-WH













6112

Baffle with Frosted Glass Lens



TRIM FINISH: • W-WH

6111



Triple Ring Glass









TRIM FINISH:







Deco Glass Reflector



REFLECTOR FINISH: CL, WT, MB, SHZ, W

RING FINISH: WH, SCH, SHZ










RING FINISH: WH, SCH, SHZ



6110 Double Ring Glass



REFLECTOR FINISH: CL, WT, MB, SHZ, W

RING FINISH: WH, SCH, SHZ







REFLECTOR FINISH: CL, WT, MB, SHZ, W

RING FINISH:

WH, SCH, SHZ



REFLECTOR FINISH:





CL, WT, MB, SHZ, W



REFLECTOR FINISH: CL, WT, MB, SHZ, W

RING FINISH: WH, SCH, SHZ









REFLECTOR FINISH: CL, WT, MB, SHZ, W **RING FINISH:** WH, SCH, SHZ

*Also available in: 6126___-Diffusing Screen Wall Wash

Geo Deco Ring Glass

6124

6127



REFLECTOR FINISH: CL, WT, MB, SHZ, W

RING FINISH: WH, SCH, SHZ *Also available in:

Geo Deco Ring Glass



