
# **ELV-75**

**DESCRIPTION:** This quiet 75W-12V electronic step-down transformer is designed to be used with low voltage lighting systems and is protected against overload, short circuit and over heat and has a 2 year guarantee.

#### **SPECIFICATIONS:**

INPUT	120V 60Hz
OUTPUT AT MAX. LOAD	11.5V 40kHz
MAXIMUM LOAD	75W
MINIMUM LOAD W/O DIMMER	10W
MINIMUM LOAD WITH DIMMER	20W
INPUT CURRENT AT MAXIMUM LOAD	0.6A
OUTPUT CURRENT AT MAXIMUM LOAD	6A
POWER FACTOR MIN.	0.95
DIMMABLE	V
AVAILABLE COLORS:	·






# **SRI2-80M**

**DESCRIPTION:** This quiet 80VV-12V electronic step-down transformer is designed to be used with low voltage lighting systems and is protected against overload, short circuit and over heat and has a 2 year guarantee.

### **SPECIFICATIONS:**

INPUT	120V 60HZ
OUTPUT AT MAX. LOAD	11.7V 40KHZ
MAXIMUM LOAD	80W
MINIMUM LOAD W/O DIMMER	10W
MINIMUM LOAD WITH DIMMER	20W
OUTPUT CURRENT AT MAXIMUM LOAD	7A
POWER FACTOR MIN.	0.95
DIMMABLE	<b>/</b>
WATERPROOF POTTING	V
ALUMINUM CASING	<b>/</b>




### ELV-75P

**DESCRIPTION:** This quiet 75W-12V plug-in electronic step-down transformer is designed to be used with low voltage lighting systems and is protected against overload, short circuit and over heat and has a 2 year guarantee.

### **SPECIFICATIONS:**

INPUT	120V 60Hz
OUTPUT AT MAX. LOAD	11.5V 40kHz
MAXIMUM LOAD	75W
MINIMUM LOAD W/O DIMMER	20W
MINIMUM LOAD WITH DIMMER	20W
INPUT CURRENT AT MAXIMUM LOAD	0.6A
OUTPUT CURRENT AT MAXIMUM LOAD	6A
POWER FACTOR MIN.	0.95
DIMMABLE	V
AVAILABLE COLORS:	

■ BLACK ○ WHITE



## **SR24-80M**

**DESCRIPTION:** This quiet 80W-24V electronic step-down transformer is designed to be used with low voltage lighting systems and is protected against overload, short circuit and over heat and has a 2 year guarantee.

### **SPECIFICATIONS:**

INPUT	120V 60HZ
OUTPUT AT MAX. LOAD	23.2V 40KHZ
MAXIMUM LOAD	80W
MINIMUM LOAD W/O DIMMER	10W
MINIMUM LOAD WITH DIMMER	20W
INPUT CURRENT AT MAXIMUM LOAD	3.4A
OUTPUT CURRENT AT MAXIMUM LOAD	3.2A
POWER FACTOR MIN.	0.95
DIMMABLE	V
RFI PROTECTION COMPATIBLE WITH FCC LIMITS	V
WATERPROOF POTTING	V
PC PLASTIC CASING	V

