
ELV-75

DESCRIPTION: This quiet 75W-12V electronic step-down transformer is designed to be used with low voltage lighting systems and is protected against overload, short circuit and over heat and has a 2 year guarantee.

SPECIFICATIONS:

INPUT	277V 60Hz
OUTPUT AT MAX. LOAD	11.5V 40kHz
MAXIMUM LOAD	75W
MINIMUM LOAD W/O DIMMER	10W
MINIMUM LOAD WITH DIMMER	20W
INPUT CURRENT AT MAXIMUM LOAD	0.6A
OUTPUT CURRENT AT MAXIMUM LOAD	6A
POWER FACTOR MIN.	0.95
DIMMABLE	*
AVAILABLE COLORS:	
BLACK WHITE	






SRI2-80M

DESCRIPTION: This quiet 80W-12V electronic step-down transformer is designed to be used with low voltage lighting systems and is protected against overload, short circuit and over heat and has a 2 year guarantee.

SPECIFICATIONS:

INPUT	277V 60HZ
OUTPUT AT MAX. LOAD	11.7V 40KHZ
MAXIMUM LOAD	80W
MINIMUM LOAD W/O DIMMER	10W
MINIMUM LOAD WITH DIMMER	20W
OUTPUT CURRENT AT MAXIMUM LOAD	7A
POWER FACTOR MIN.	0.95
DIMMABLE	
WATERPROOF POTTING	1
ALUMINUM CASING	-




ELV-75P

DESCRIPTION: This quiet 75W-12V plug-in electronic stepdown transformer is designed to be used with low voltage lighting systems and is protected against overload, short circuit and over heat and has a 2 year guarantee.

	S	P	E	C	I	FI	C	A	T	0	N	S:	
--	---	---	---	---	---	----	---	---	---	---	---	----	--

INPUT	277V 60Hz
OUTPUT AT MAX. LOAD	11.5V 40kHz
MAXIMUM LOAD	75W
MINIMUM LOAD W/O DIMMER	20W
MINIMUM LOAD WITH DIMMER	20W
INPUT CURRENT AT MAXIMUM LOAD	0.6A
OUTPUT CURRENT AT MAXIMUM LOAD	6A
POWER FACTOR MIN.	0.95
DIMMABLE	
AVAILABLE COLORS:	
BLACK WHITE	



SR24-80M

DESCRIPTION: This quiet 80W-24V electronic step-down transformer is designed to be used with low voltage lighting systems and is protected against overload, short circuit and over heat and has a 2 year guarantee.

SPECIFICATIONS:

INPUT	277V 60HZ
OUTPUT AT MAX. LOAD	23.2V 40KHZ
MAXIMUM LOAD	80W
MINIMUM LOAD W/O DIMMER	10W
MINIMUM LOAD WITH DIMMER	20W
INPUT CURRENT AT MAXIMUM LOAD	3.4A
OUTPUT CURRENT AT MAXIMUM LOAD	3.2A
POWER FACTOR MIN.	0.95
DIMMABLE	1
RFI PROTECTION COMPATIBLE WITH FCC LIMITS	1
WATERPROOF POTTING	×
PC PLASTIC CASING	×

