



FEATURES

This fixture is an excellent choice when an attractive emergency light is required. In cases of AC power loss, it provides a minimum of 90 minutes illumination. A trouble-free lead-calcium battery is provided with the fixture.

BODY

- Durable 20 gauge steel trim plate in white or black finish
- Trim securely attached to housing with spring clips

MOUNTING

- Bar hangers on the back box for recessed mount
- Compatible with drywall or drop ceiling mount installations (Bar hangers included)

LAMP

- (2) 5.4W fully adjustable par type lamp heads

ELECTRICAL

- Dual 120/277 voltage
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing
- LVD (low voltage disconnect) prevents battery from deep discharge

BATTERY

- 6V maintenance-free, rechargeable Sealed lead acid battery
- Internal solid-state transfer switch automatically connects the internal battery to lamp heads for minimum 90-minute emergency illumination
- Fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours

TESTING

- Test button indicator light shows high charge and readiness for operation

LISTED

- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes
- UL listed for dry locations (25°C)

OPTION

- **SDT:** Self-diagnostic test feature performs monthly, biannually, and annually tests to ensure reliable operation and to meet electrical and life safety codes



ITEM SELECTOR: (Please check the boxes below for the option desired)

CATALOG#	HOUSING COLOR	OPTIONS
ELM-870	<input type="checkbox"/> W - White	<input type="checkbox"/> SDT - Self-Diagnostic
	<input checked="" type="checkbox"/> B - Black	

SPECIFIED:

ELM-870 _____ - _____
HOUSING COLOR OPTION