
ELM-LED-861

LED Emergency Light with Battery Back-Up & Self-Diagnostic

Emergency	Ι	igh	nting
	_	8-	5



0	4	- 75"
- 10" —		



FEATURES

This fixture is an excellent choice when an attractive emergency light is required. In cases of AC power loss, it provides a minimum of 90 minutes illumination. A trouble-free lead-calcium battery is provided with the fixture. The LED heads may be adjusted through the full range of motion because of the special swivel-track design.

VUUS

- The thermoplastic housing of the product makes it corrosion-proof and scratch-and impactresistant.
- UV-stabilization prevents discoloration of the product.
- Compartment shaped by injection.
- Power may be supplied via wall or ceiling

FACE

• The face has two square LED heads that are fit into bevels on either side and each has a reflector and diffuser

MOUNTING

Unique "snap-together" universal mounting design permits top, back and side mounting.
Necessary hardware and canopy are provided electrical

ELECTRICAL

- 120V or 277V Dual Input
- Reset is automatic
- Hassle-free wiring without the need for additional hardware

LAMPS

- 1W (8 LED's x 0.125) per head
- Emergency Light Fixtures: Two moveable glare free light heads that have a positioning lock.

BATTERY

- Indicator light shows high charge and readiness for operation
- 6V, 4 amp-hour sealed-lead acid battery works during power failures
- Replaceable and requires no maintenance
- When completely charged, supplies emergency power for 90 minutes.

TESTING

- Test Button
- Solid state line latched low voltage disconnect to avoid deep discharge
- Safeguarded against short circuits
- Power is automatically interrupted in cases of brown-out

LISTED

- UL 924, NFPA, NEC, State & Municipal
- Damp location approved

ELM-LED-861 - ITEM SELECTOR: (Please check the boxes below for the option desired)

Н	OUSING COLOR	CANOPY			
	W - White	UNIVERSAL MOUNT TO WALL OR CEILING			
	B - Black	UNIVERSAL MOUNT TO WALL OR GEILING			



ELM-LED-861

HOUSING COLOR







A division of **Elite Lighting**

Submittal form is available @ www.maxilume.com Tel: 323-888-1973 • Fax: 323-888-1977