ELX-505

LED Die-Cast Exit Sign With 2 Circuits

Catalog Number:	
Project Name:	Type:
Note:	MAXILUME ARCHITECTURAL LIGHTING

Architectural







FEATURES

This fixture is ideal for applications that require energy efficiency and an attractive die-cast aluminum signage. The long-lasting LEDs in this product consume less than 3 watts of energy and are rated for a life of up to 25 years without a drop in illumination. It takes advantage of a self-generated source of power available on site in emergencies.

BODY

- Molded from solid die-cast aluminum housing that makes it corrosion-proof and UV-stabilized to resist discoloration.
- The standard finish is brushed aluminum face with matte black housing.

FACE

- Knockout directional chevrons
- One face is supplied; extra ones are optional
- Letters are 6" and emit color in all directions

MOUNTING

- Unique "snap-together" universal mounting design permits top, back and side mounting. Necessary hardware and canopy are provided electrical
- The chevron directional indicator knockouts and mounting hardware are totally hidden from view.

ELECTRICAL

- 120V or 277V input
- · Consumes only 2 watts of power
- LED light source
- Protected against short circuits and power surges
- Second circuit allows the use of alternate power sources in emergencies

LISTED

- UL 924, NFPA, NEC, State & Municipal
- Damp location approved

ELX-505 - ITEM SELECTOR: (Please check the boxes below for the option desired)

LETTER COLOR	HOUSING COLOR	FACE COLOR	NUMBER OF FACES
☐ G - Green	AL - Natural Aluminum	AL - Natural Aluminum	□ 1 - FACE
□ R - Red	□ W - White	□ W - White	□ 2 - FACE
	□ B - Black	□ B - Black	





Specified:

ELX-505

ETTER COLOR HOUSING COLOR

NO. OF FACE



A division of **Elite Lighting**

Submittal form is available @ www.maxilume.com Tel: 323-888-1973 • Fax: 323-888-1977