# **ELX-616 LED Salida Exit Sign**

Architectural

SIDE

**Catalog Number:** 

**Project Name:** 

Type:



### **FEATURES**

Note:

This fixture is an excellent choice when fast installation and an attractive appearance are priorities. Its long-lasting LEDs consume less than two watts of energy and are rated for a life of up to 25 years. If AC power is lost, the fixture provides at least 90 minutes of illumination and will automatically recharge after discharge. The operation of this product can easily be monitored and controlled with the use of a conveniently located test switch that indicates charge and diagnostic state.

#### BODY

• The thermoplastic housing of the product makes it corrosion-proof and scratch-and impactresistant.

- UV-stabilization prevents discoloration of the product.
- Every fixture includes a canopy, extra faceplate, and replaceable chevron directional indicator knockouts for control of direction.
- Components shaped by precision injection molding and has 1/2" knockouts for the supply of power.

#### FACE

- 6" high text with color diffusion
- Knockout directional chevrons
- Single or dual construction. Lettered face is available for applications where dual face is chosen.

#### **ELECTRICAL**

- · Consumes only 2 watts of power
- Long-lasting LED sources
- LED lights continue to function while the battery is working
- 120V or 277V dual input with battery back-up

### BATTERY

- Nickel Cadmium, or Ni-Cad, battery
- Internal solid-state wiring for charging purposes
- Indicator light reflects high-Charge and ready operation

Submittal form is available @ www.maxilume.com

Tel: 323-888-1973 • Fax: 323-888-1977

- Testing button
- Automatic reset
- · Safeguarded against short circuits and brown-outs
- Disconnection is necessary for full discharge
- Solid-state internal circuitry for charging

• LED and PC circuits have a rating of about 25 years without a drop in illumination

#### LISTED

- UL 924, NFPA, NEC, State & Municipal
- Damp location approved

ELX-616 - ITEM SELECTOR: (Please check the boxes below for the option desired)

LETTER COLOR	HOUSING COLOR	FACES	CANOPY
🗌 G - Green	🔲 W - White		ACE UNIVERSAL MOUNT TO WALL OR CEILING
🗆 <b>R</b> - Red	🗆 <b>B</b> - Black	(2) OPTIONAL BLANK FACE Included	
Specified:		I	
ELX-616	-		
	LETTER COLOR	HOUSING COLOB	

Specifications and Dimensions subject to change without notice.



HOUSING COLOR

A division of

Elite Lighting

SAL

S WALL

6-1/4

Þ

12-1/2

CEILI

## LIFE SPAN