

ELX-618

Recessed LED Edge-Lit with Emergency Battery Back-Up with Self-Diagnostic

Architectural


Catalog Number:

Project Name:

Type:

Note:

MAXILUME
ARCHITECTURAL LIGHTING



FEATURES

This fixture is intended for use in applications where performance and appearance are high priorities. In the event of AC power failure, the fixture provides at least 90 minutes of illumination. The product uses long-life LEDs, which consume very little energy - less than 3 watts - and it has a rated life of up to 25 years with no drop in illumination.

BODY

- This fixture is made from injection-molded acrylic panels that are supported by a small extruded aluminum frame.
- Aluminum and acrylic panel compartments.
- 2-Piece flexible aluminum that contains the PC board, battery, LED source, and the upper end of the acrylic face.
- Pre-installed bar hangers

FACE

- Single- and double-faced exit lights are available.
- An appealing exterior is the result of the precisely designed edges of the acrylic face.
- 6" letters in red or green colors are within the cover. Adhesive chevrons are also provided.

RECESSED MOUNTING

- Unique mounting design permits ceiling mounting.
- Fits into wall or ceiling w/ opening 13-5/8" L X 4-1/2" W X 3-1/3" D.
- Adjustable T-bar hangers adapt mounting tray for mounting in suspended ceilings or variable size framed openings.
- Plug-in wire connections and self-captive mounting screws
- For wall mount, kit must be order separately (ELX-618-WALL-KIT)

ELECTRICAL


- Universal 120V or 277V Dual Input
- Normally 3 Watts, 5 Watts in Emergency Use
- Light source - Led Strips

BATTERY

- Internal solid-state wiring for charging purposes
- Ni-cad battery
- Minimum 90 minutes of illumination
- Indicator light will reflect high charge and readiness for operation
- Test Button
- Short-circuit safeguard
- Brown-out safeguard
- Disconnection for full discharge

LISTED

- UL 924, NFPA, NEC, State & Municipal
- Damp location approved



ELX-618 - ITEM SELECTOR: (Please check the boxes below for the option desired)

LETTER COLOR	HOUSING COLOR	NUMBER OF FACES	PANEL COLOR
<input type="checkbox"/> G - Green	<input type="checkbox"/> AL - Natural Aluminum	<input type="checkbox"/> 1 - FACE	<input type="checkbox"/> CLEAR ACRYLIC
<input type="checkbox"/> R - Red	<input type="checkbox"/> W - White	<input type="checkbox"/> 2 - FACE	<input type="checkbox"/> MIRROR
	<input type="checkbox"/> B - Black		



Specified:

ELX-618 _____ - _____ - _____ - _____
LETTER COLOR HOUSING COLOR NO. OF FACE PANEL COLOR

*2 face is only available for Mirror panel option

MAXILUME
ARCHITECTURAL LIGHTING

A division of
Elite Lighting

Submittal form is available @ www.maxilume.com
Tel: 323-888-1973 • Fax: 323-888-1977

Specifications and Dimensions
subject to change without notice.

REV: MAXILUME-SPEC-03-10-2011