

ELX-637

New York City Approved LED Aluminum Recessed Edge-Lit Exit Sign

Architectural Exit Sign







Catalog Number: Project Name: Note: Type:

ILLUMINATION

- Ultra bright, energy efficient, long life Red LED.
- UV-stabilized ultra-clear acrylic edge-lit panel provides consistent, uniform illumination.
- Double face utilizes factory installed silver or white mylar background panel.
- New York City compliant 8" EXIT letters.

ELECTRICAL

- Dual 120/277 voltage standard. Optional multi-tap 208/220/240 voltage available.
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- 4.8V long life, maintenance-free, rechargeable NiCad battery.
- Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

MOUNTING

- Compatible with drywall or drop ceiling mount installations. Bar hangers included.
- Wall mount capability optional.

HOUSING

- Premium-grade, extruded aluminum housing.
- Extruded aluminum trim assembly is easily detachable from below, providing accessibility for service or maintenance. Available in black or white powder-coated finishes.
- Self-adhesive chevron appliques and guide template provided for directional indication.

OPTION

- SPV: UL Listed for special voltage option.
- WM: Allows for the unit to be wall recessed mounted.

WARRANTY/LISTING

- Five year warranty on all electronics and housing. Battery prorated for five years.
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
- UL Listed for damp locations (0°C − 50°C).









ELX-637 - ITEM SELECTOR: (Please check the boxes below for the option desired)

LETTER COLOR	HOUSING COLOR	PANEL COLOR	NO. OF FACE	BATTERY	OPTION
□ R - Red	AL - Aluminum W - White B - Black	CL - Clear MR - Mirror W - White	□ 1 - Face □ 2 - Face	□ AC Input	□ WM - Wall Mount □ SPV - 208/220/240V (50/60 Hz

SPECIFIED:

*2 face is only available for Mirror panel option

ELX-637 -____ - ____ - ____ - ____ - ____ - ____ - ____ - ____ OPTION

