
ELX-LED-603-G/R-W

Universal Exit Sign Red - Green





Switch from Red to Green Default Factory Setting: Red



FEATURES

This product is ideal when an exit sign is required. Its design makes it suitable for use above doors. Field-selectable switch enables the sign to change from red to green and vice-versa.

BODY

- Injection-molded thermoplastic housing
- Plastic enclosure with 5VA flammability rating
- Compact and decorative design
- Easy configuration for quick installation

FACE

- Single and double face configuration
- Sign letters are 6" in height with a 3/4"stroke width. Snap-in/out direction indicators.

MOUNTING

- Suitable for wall, side and ceiling mount
- · Universal J-Box mount pattern on back plate

ELECTRICAL

- 120/277VAC 60Hz dual voltage input optional
- Battery low voltage protection
- Solid-State transfer circuit
- · Test switch and battery charging indicator
- · Maintenance free Ni-cad battery
- 24hours recharge
- 90mins discharge

BATTERY

- High temperature type Ni-cad battery
- Recharge battery if kept in stock for 9 months or longer
 For details refer to "BATTERY STOCK AND RECHARGE GUIDELINE".

OPTION

Manual test function

ILLUMINATION

- Field selectable red or green sign with matched color diffuser
- Default factory setting: red

COMPLIANCE

- UL listed and meet or exceed all requirements in NFPA 70, NFPA 101 life safety code
- Complies with CEC title 20 efficiency regulations.
- Suitable for 50°F-104°F ambient temperature
- Suitable for damp location











A division of **Elite Lighting**

ORDERING CHART

ELX-LED-603-

Please reference options below

Finish	
☐ W (White) ☐ B (Black)	
SPECIFIED:	

HOUSING COLOR