## ELX-LED-723

# ALL LED RUNNING MAN SIGN & EMERGENCY LIGHTPIPE THERMOPLASTIC COMBO

Catalog Number:	
Project Name:	
Note:	Туре:



### **OPTIONS**

 SDT: Self-diagnostic feature performs monthly, biannual, and annual tests to ensure reliable operation and meets electrical and life safety codes.

### **ELECTRICAL**

- Dual 120/347 voltage.
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- 4.8V long life, maintenance-free, rechargeable NiCd battery.
- Remote capacity of 3.0 watts standard.
- Internal solid-state transfer switch automatically connects the internal battery to LED board/light pipe for minimum 90-minute emergency illumination.
- Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

### **MOUNTING**

- EZ-snap mounting canopy included for top or end mount.
- Universal knockout pattern on back plate for wall mount.
- Field selectable, universal directional indication provided with three (Right, Left and No Arrow) pictogram legends.

### **ILLUMINATION**

- Ultra bright, energy efficient, white LED emergency lighting.
- 4.5 watt (36 LEDs x 0.125 watts) per light pipe.
- Adjustable high performance, smooth, chrome-plated, metallized reflector and acrylic, UV-stabilized "light pipe" lens for optimal light distribution.
- Ultra bright, energy efficient, long lasting white LED provides even, fully illuminated panel.

# 9 3½" 14" 14"

### HOUSING

 Injection-molded, engineering grade, 5VA flame retardant, high-impact resistant, thermoplastic in white or black finishes.

### **WARRANTY/LISTING**

- Five year warranty on all electronics and housing. Battery prorated for five years.
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
- CSA listed for damp locations (0°C 50°C).
- Meets or exceeds CSA C22.2 No. 141.15 standard requirements for Emergency lighting equipment.

**ELX-LED-723** - ITEM SELECTOR: (Please check the boxes below for the option desired)

HOUSING COLOR	No of FACES	OPTIONS
W - White B - Black	2 - Universal Single / Double Face	RC - Remote Capable (standard) SDT - Self-Diagnostics

SPECIFIED:

ELX-LED-723

HOUSING COLOR No of FACES OPTIONS

STANDARD









