




Specifications of Round Instant Flexilight:

Structure	Voltage	Max. Loading Length (Color)	Cutting Unit (Color)	Bulb Spec.	Number of Bulbs/Unit	Wattage
	12V	30'	4'	3.0V 0.07A 0.21W	12	2.52W/foot
	24V	60'	8'	3.0V 0.07A 0.21W	12	2.52W/foot
	110-120V	240'	24'	6.5V 0.07A 0.46W	12	3W/foot

Packages Available

Item Number	Length	Package
ERIF-120-150	150'	/Roll
ERIF-24-150*	150'	/Roll
ERIF-12-150**	150'	/Roll

ERIF - 120 - 150 - COLOR

Item No. Voltage Length Specify color

(Available in 150' Rolls only, no custom cut)

NOTE: EACH ROLL INCLUDES; 3pcs ERIFXXX Power Cords, 3pcs F3 Splice Connectors, 3pcs F4 End Caps

Round Instant Flexilight Accessories:

- ERIF1-120V Round Instant Flexilight 6ft. Power Cord w/ Power Connector
- ERIF1-24V* Round Instant Flexilight 6ft. Power Cord w/ Power Connector
- ERIF1-12V** Round Instant Flexilight 6ft. Power Cord w/ Power Connector
- F3 Round Instant Flexilight Splice Connector
- F4 Round Instant Flexilight End Caps
- F5 Round Instant Flexilight Tie Strap
- F6 Round Instant Flexilight Mounting Clips
- F7 Round Instant Flexilight Suction Cup
- F8 Round Instant Flexilight 6ft. Channel
- F9 Round Instant Flexilight Easy Splice Connector
- F10 Round Instant Flexilight Y-cord
- F11 Round Instant Flexilight T-connector
- F14 Round Instant Flexilight Splice Connector
- F103 Round Instant Flexilight PVC Connector
- F22 Round Instant Flexilight PVC T-Connector
- F23 Round Instant Flexilight PVC X-Connector

ERIFI



F3



F4



F5



F6



F7



F8



F9



F10



F11



F14



F22



F23



F103



Standard Controller

MODEL	VOLTAGE AVAILABLE	MAX. LENGTH	FUNCTIONS
ERWL-2C-110	120V	150 FT.	Static/Flashing
ERWL-2C-24A*	24V	60 FT.	Static/Flashing
ERWL-2C-12A**	12V	30 FT.	Static/Flashing

(*Requires 24V AC power source)

(**Requires 12V AC power source)

