

## FEATURES

- :: Adjustable rotating ends for flexible aiming.
- :: Louvered design maximizes performance while reducing glare.
- :: Easy lamp replacement by removing a few twist screws.
- :: Ideal for wall washing, direct/ indirect down lighting and floodlighting.
- :: Uses the latest fluorescent lamp technology for energy efficiency.

## SPECIFICATIONS

### BALLAST

Quick start electronic ballast is thermally protected and current controlled. Will maximize light output without jeopardizing lamp life. Prevents flickering.

### ELECTRICAL


Fixture conforms to UL 1570.

### FINISH


U.V. coated rust resistance. Painted parts finished with polyester powder coating. Extruded Aluminum housing.

### COLORS


- :: AWH=White
- :: ABK=Black



ET-PL-2X55



ET-PL-2X40



ET-PL-2X18

FIXTURE	DESCRIPTION - LAMP TYPE	WATTAGE PER LAMP	FIXTURE DIMENSIONS
ET-PL-2X18	CFL-120V, (2) 18W, 2G11 base, 4-pin	18W	6" D X 6" W X 14-1/2" L
ET-PL-2X40	CFL-120V, (2) 40W, 2G11 base, 4-pin	40W	6" D X 6" W X 27-1/2" L
ET-PL-2X55	CFL-120V, (2) 55W, 2G11 base, 4-pin	55W	6" D X 6" W X 27-1/2" L