

FEATURES

- :: Adjustable rotating ends for flexible aiming.
- :: Louvered design maximizes performance while reducing glare.
- :: Easy lamp replacement by removing a few twist screws.
- :: Ideal for wall washing, direct/ indirect down lighting and floodlighting.
- :: Uses the latest fluorescent lamp technology for energy efficiency.

SPECIFICATIONS

BALLAST

Quick start electronic ballast is thermally protected and current controlled. Will maximize light output without jeopardizing lamp life. Prevents flickering.

ELECTRICAL


Fixture conforms to UL 1570.

FINISH


U.V. coated rust resistance. Painted parts finished with polyester powder coating. Extruded Aluminum housing.

COLORS


- :: AWH=White
- :: ABK=Black



ET-PL-2X55



ET-PL-2X40



ET-PL-2X18

FIXTURE	DESCRIPTION - LAMP TYPE	WATTAGE PER LAMP	FIXTURE DIMENSIONS
ET-PL-2X18	CFL-120V, (2) 18W, 2G11 base, 4-pin	18W	6" D X 6" W X 14-1/2" L
ET-PL-2X40	CFL-120V, (2) 40W, 2G11 base, 4-pin	40W	6" D X 6" W X 27-1/2" L
ET-PL-2X55	CFL-120V, (2) 55W, 2G11 base, 4-pin	55W	6" D X 6" W X 27-1/2" L