


Rotate 355° Tilt 85°



| SERIES    | LUMENS | WATTAGE |
|-----------|--------|---------|
| FG-R-T7-1 | 500lm  | 9W      |

Based on 4000K, 90+ CRI. Actual wattage may vary +/- 5%

### GROOVE CURVE 'SQUARE TRACK LIGHT' SERIES

Compact, modern, and fully adjustable the FG-R-T7-1 Square Track Lights feature nearly a full range of motion with 355° rotation and 85° tilt, ideal for task or accent lighting. Optional Narrow Flood, Flood, and Wide Flood TIR optics provide precise beam control and reduce glare. Through track head positioning and mounting distance, the FG-R-T7-1 can be utilized as a wall wash, wall grazer, task, or downlight. Available with various CCT options. Suitable for individual installation or assorted combination with other Groove Curve track luminaires for convenient, dynamic illumination.

|                   |                                                                                                               |
|-------------------|---------------------------------------------------------------------------------------------------------------|
| SERIES            | Groove Curve - 'Square Track Light' series                                                                    |
| SIZE              | 2"                                                                                                            |
| OPERATING VOLTAGE | 48V DC                                                                                                        |
| OUTPUT VOLTAGE    | 120-277V AC                                                                                                   |
| CCT               | 2700K, 3000K, 3500K, 4000K, 5000K                                                                             |
| CRI               | 90+                                                                                                           |
| COLOR QUALITY     | 2-Step MacAdam Ellipse                                                                                        |
| OPTICS            | Narrow Flood 28°, Flood 50°, Wide Flood 80°                                                                   |
| FINISH            | ● WH-BK (White+Black) ● BK-BK (Black)                                                                         |
| DIMMING           | DIM10 - (0-10V Dimming), DIMTR, DALI 2, BLE                                                                   |
| LIFETIME          | L70 at 60,000 Hours                                                                                           |
| LISTING           | 5-year pro-rated warranty. ETL Listed. Title 24 Compliant. Assembled in America. Class 2, Title 24 JA8 listed |
| PHOTOMETRIC TESTS | In accordance with IES LM79-08, LM80 and TM-30, TM-21                                                         |

## FEATURES OF GROOVE FAMILY

The Groove Curve 48V Track System offers seamless curved track solutions for modern lighting design.

**FLEXIBLE AND CREATIVE:** Groove Curve connects curved and straight tracks at various angles and diameters to create complete circular shapes and custom curved layouts.

**VERSATILE AND PRECISE:** Groove Curve tracks support a wide range of interchangeable luminaires with flexible adapters to allow easy repositioning and replacement.

Available in Trimless Recessed, Ceiling Mount, and Suspended Mount options. Fixtures can be mounted individually or in continuous runs for curved paths of smooth, uninterrupted illumination.

## THE ORIGINAL GROOVE 48V DC TRACK SYSTEM

The Groove 48V DC track system combines sleek, minimal profiles with the convenience and versatility of easily interchangeable click-in track heads.

Designed for easy customization, Groove is available with a suite of in-line linear, adjustable linear, spot, pendant, cylinder, and suspended track heads which can be seamlessly clicked-in or removed to meet the needs of any project, current or future. Track head accessories include a variety of field-changeable optics, including TIR and diffuser options, and even spot, flood, snoot, and wall-wash accessories.

As a result, Groove can be used for accent, task, and general illumination in galleries and museums or hospitality, retail, corporate, and residential spaces.

- Single drivers can power runs up to 65' long at 480 watts
- Discreet integrated or remote driver options keep track lines clean
- Connector accessories like T, X, and L corners can be used to tailor designs into custom rectangular, square, or linear patterns, or even build wall to ceiling or wrap configurations
- Multiple lumen packages and distribution options available
- Available in Trimless Recessed, Recessed Flanged, Ceiling/ Surface, and Suspended options
- Suspended and surface mounting options can be used for wood, drywall or T-Bar ceilings

For more details refer to individual track head spec sheets.

## CONSTRUCTION

All Groove track heads are engineered for long lifespans and reduced maintenance through the use of coolLED's Advanced Thermodynamic Design, which includes an extruded aluminum body, a hidden die-cast heat sink, and thermal management system.

## LED MODULE PERFORMANCE

The Groove Blade System's luminaires are equipped with 2-step McAdam Eclipse LEDs, which provide consistent color across all fixtures, and 90+CRI. The LEDs are available in a variety of kelvin temperature options.

## DRIVERS

The Groove Blade System is powered by constant voltage drivers with a rating of 50/60Hz at a 120/277V input and a 48V output. They produce less than 20% THD, have a 90% power factor, and are thermally protected for additional safety. Driver wattages range from 75W to 450W and can power up to 65' of track. Groove drivers can be installed internally within the track or remotely mounted, and are available in 0-10V 1% Dimming, Dali Dimming, or 120V On/ Off Non-Dimming Driver. Please see Groove track system spec sheets for a complete list of drivers and capabilities.

## FINISH

Luminaires are available in a powder-coated black or white post-paint finish. They may also be issued in custom RAL colors upon request. Consult the factory to find out which custom colors can be accommodated.

## DIMMING INFORMATION

DIM10 - 0-10V dimming on either MVOLT 120, 277. Dimmable down to 1% of initial lumens, standard. Available in 75W, 100W, 150W, and 240W.

DIMTR - Electronic low voltage dimming. Available in 120V.

DALI - DALI DT6 dimming down to 1% Available in 75W, 100W, 150W, and 240W.

EldoLED PowerDrive dimming down to 0.1%. Please see the EldoLED website for wiring diagrams and a full list of compatible DMX and DALI control systems.

## WARRANTY

5-year warranty for parts and components (labor not included).

| EXAMPLE:  |                                                                                                         |                                                                                                                                                              |                             |                                                                                        |                                                                                                               |
|-----------|---------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------|----------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------|
| SERIES    | OPTICS                                                                                                  | CCT                                                                                                                                                          | CRI                         | FINISH                                                                                 | OPTION                                                                                                        |
| FG-R-T7-1 | <input type="checkbox"/> NFL=28°<br><input type="checkbox"/> FL=50°<br><input type="checkbox"/> WFL=80° | <input type="checkbox"/> 27K<br><input type="checkbox"/> 30K<br><input type="checkbox"/> 35K<br><input type="checkbox"/> 40K<br><input type="checkbox"/> 50K | <input type="checkbox"/> 90 | <input type="checkbox"/> WH-BK (White+Black)<br><input type="checkbox"/> BK-BK (Black) | <input type="checkbox"/> 48V<br><input type="checkbox"/> 48V-BLE (Bluetooth)<br>*Power supply must be ordered |







## ANSI/IES TM-30-18 Color Rendition Report

Source: LED-PCB

Manufacturer:

Date: 2024/12/3

Model: CRI:90 CCT:3000K



Notes: This is a recommended method for displaying ANSI/IES TM-30-18 information.

$x$  0.4339

$y$  0.4033

$u'$  0.2489

$v'$  0.5206

CIE 13.3-1995  
(CRI)

$R_a$  93


$R_g$  52

Colors are for visual orientation purposes only. Created with the ANSI/IES TM-30-18 Calculator Version 2.00.

GROOVE CURVE LUMINAIRE OPTIONS



FG-R-L4R-8  
Linear Downlight



FG-LS-3  
Linear Silicone 3ft



FG-LS-6  
Linear Silicone 6ft



FG-LS-9  
Linear Silicone 9ft



FG-R-T1-1  
Recessed Track Light



FG-R-T2-2  
Cylinder



FG-R-T3-1  
Cylinder



FG-R-T3-2  
Cylinder




FG-R-T4-1  
Beam Adjustable Cylinder



FG-R-T4-2  
Beam Adjustable Cylinder



FG-R-T5-1  
Flat Round



FG-R-T5-2  
Flat Round



FG-R-T6-1  
Flat Square



FG-R-T7-1  
Square Track Light




FG-R-T7-2  
Rectangle Track Light



FG-R-T8-1  
Track Globe



FG-R-T9-1  
Track Globe



FG-R-T10-1  
Track Downlight




FG-R-T11-1  
Globe



FG-R-WL-1  
Wall Light



FG-R-LL-1  
Line Light



FG-R-TRJ-1  
Form Projector



FG-R-TRJ-2  
Gobo Projector



FG-R-P1-1/2  
Pendant



FG-R-P3-1/2  
Pendant



FG-R-P4-1  
Pendant Globe



FG-R-P4-2  
Pendant Globe



FG-R-P4-3  
Pendant Globe



FG-R-P5-1  
Globe




FG-R-P9-1  
Pendant Flat Round

**FG-R-T7-1-NFL-40K-90**

TEST NO.: **220062**

INPUT WATTS: **9.6** LUMENS: **494** EFFICACY: **51** BEAM ANGLE: **28** SPACING CRITERIA: **0.58**



**CANDELA TABLE**

|     | 0°   | 90°  |
|-----|------|------|
| 0°  | 1377 | 1377 |
| 10° | 1206 | 929  |
| 20° | 538  | 323  |
| 30° | 160  | 105  |
| 40° | 43   | 27   |
| 50° | 0    | 0    |
| 60° | 0    | 0    |
| 70° | 0    | 0    |
| 80° | 0    | 0    |
| 90° | 0    | 0    |

**LUMINANCE (cd/sq.m)**

|        | 0.00°    | 90.00°   |
|--------|----------|----------|
| 0.00°  | 20974795 | 20974795 |
| 45.00° | 436953   | 287282   |
| 55.00° | 0        | 0        |
| 65.00° | 0        | 0        |
| 75.00° | 0        | 0        |
| 85.00° | 0        | 0        |

**LUMENS PER ZONE**

| ZONE      | LUMENS |
|-----------|--------|
| 0° - 10°  | 117    |
| 10° - 20° | 199    |
| 20° - 30° | 113    |
| 30° - 40° | 49     |
| 40° - 50° | 16     |
| 50° - 60° | 0      |
| 60° - 70° | 0      |
| 70° - 80° | 0      |
| 80° - 90° | 0      |

**ZONAL LUMEN SUMMARY**

| ZONE     | UMENS | % LUMINAIRE |
|----------|-------|-------------|
| 0° - 20° | 316   | 64%         |
| 0° - 30° | 429   | 87%         |
| 0° - 40° | 478   | 97%         |
| 0° - 60° | 494   | 100%        |
| 0° - 80° | 494   | 100%        |
| 0° - 90° | 494   | 100%        |

**CONE OF LIGHT**

| MOUNTING HEIGHT | FC AT BEAM CENTER | BEAM DIA. 0°-180° | BEAM DIA. 90°-270° |
|-----------------|-------------------|-------------------|--------------------|
| 6.0 ft          | 38.3 fc           | 3.3 ft            | 3.3 ft             |
| 8.0 ft          | 21.5 fc           | 4.4 ft            | 4.4 ft             |
| 10.0 ft         | 13.8 fc           | 5.4 ft            | 5.5 ft             |
| 12.0 ft         | 9.6 fc            | 6.5 ft            | 6.5 ft             |
| 14.0 ft         | 7.0 fc            | 7.6 ft            | 7.6 ft             |
| 16.0 ft         | 5.4 fc            | 8.7 ft            | 8.7 ft             |
| 18.0 ft         | 4.3 fc            | 9.8 ft            | 9.8 ft             |
| 20.0 ft         | 3.4 fc            | 10.9 ft           | 10.9 ft            |


**INDOOR COEFFICIENTS OF UTILIZATION**

| pf | 20% |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     | 0%  |    |
|----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|
| pc | 80% |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |     | 0%  |    |
| pw | 70% | 50% | 30% | 10% | 70% | 50% | 30% | 10% | 50% | 30% | 10% | 50% | 30% | 10% | 50% | 30% | 10% | 0% |
| 0  | 118 | 118 | 118 | 118 | 115 | 115 | 115 | 115 | 110 | 110 | 110 | 105 | 105 | 105 | 101 | 101 | 101 | 99 |
| 1  | 113 | 111 | 109 | 107 | 111 | 109 | 107 | 105 | 105 | 103 | 102 | 101 | 100 | 99  | 98  | 97  | 96  | 94 |
| 2  | 109 | 105 | 102 | 99  | 107 | 103 | 100 | 98  | 100 | 98  | 95  | 97  | 95  | 93  | 95  | 93  | 92  | 90 |
| 3  | 105 | 99  | 95  | 92  | 103 | 98  | 94  | 91  | 96  | 92  | 90  | 93  | 91  | 89  | 91  | 89  | 87  | 86 |
| 4  | 101 | 95  | 90  | 87  | 99  | 93  | 89  | 86  | 91  | 88  | 85  | 90  | 87  | 84  | 88  | 85  | 83  | 82 |
| 5  | 97  | 90  | 85  | 82  | 95  | 89  | 85  | 82  | 88  | 84  | 81  | 86  | 83  | 80  | 85  | 82  | 80  | 78 |
| 6  | 93  | 86  | 81  | 78  | 92  | 85  | 81  | 78  | 84  | 80  | 77  | 83  | 79  | 77  | 82  | 78  | 76  | 75 |
| 7  | 90  | 82  | 78  | 74  | 89  | 82  | 77  | 74  | 81  | 77  | 74  | 80  | 76  | 73  | 79  | 75  | 73  | 72 |
| 8  | 87  | 79  | 74  | 71  | 86  | 79  | 74  | 71  | 78  | 73  | 71  | 77  | 73  | 70  | 76  | 72  | 70  | 69 |
| 9  | 84  | 76  | 71  | 68  | 83  | 76  | 71  | 68  | 75  | 71  | 68  | 74  | 70  | 68  | 73  | 70  | 67  | 66 |
| 10 | 81  | 73  | 68  | 65  | 80  | 73  | 68  | 65  | 72  | 68  | 65  | 71  | 68  | 65  | 71  | 67  | 65  | 64 |

**FG-R-T7-1-FL-40K-90**

TEST NO.: **220062**

INPUT WATTS: **9.5** LUMENS: **584** EFFICACY: **61** BEAM ANGLE: **50** SPACING CRITERIA: **0.90**



**CANDELA TABLE**

|     | 0°  | 90° |
|-----|-----|-----|
| 0°  | 809 | 809 |
| 10° | 805 | 745 |
| 20° | 679 | 509 |
| 30° | 330 | 191 |
| 40° | 64  | 35  |
| 50° | 0   | 0   |
| 60° | 0   | 0   |
| 70° | 0   | 0   |
| 80° | 0   | 0   |
| 90° | 0   | 0   |

**LUMINANCE (cd/sq.m)**

|        | 0.00°    | 90.00°   |
|--------|----------|----------|
| 0.00°  | 12313518 | 12313518 |
| 45.00° | 627972   | 375146   |
| 55.00° | 0        | 0        |
| 65.00° | 0        | 0        |
| 75.00° | 0        | 0        |
| 85.00° | 0        | 0        |

**LUMENS PER ZONE**

| ZONE      | LUMENS |
|-----------|--------|
| 0° - 10°  | 76     |
| 10° - 20° | 199    |
| 20° - 30° | 196    |
| 30° - 40° | 90     |
| 40° - 50° | 22     |
| 50° - 60° | 0      |
| 60° - 70° | 0      |
| 70° - 80° | 0      |
| 80° - 90° | 0      |

**ZONAL LUMEN SUMMARY**

| ZONE     | UMENS | % LUMINAIRE |
|----------|-------|-------------|
| 0° - 20° | 276   | 47%         |
| 0° - 30° | 471   | 81%         |
| 0° - 40° | 561   | 96%         |
| 0° - 60° | 584   | 100%        |
| 0° - 80° | 584   | 100%        |
| 0° - 90° | 584   | 100%        |

**CONE OF LIGHT**

| MOUNTING HEIGHT | FC AT BEAM CENTER | BEAM DIA. 0°-180° | BEAM DIA. 90°-270° |
|-----------------|-------------------|-------------------|--------------------|
| 6.0 ft          | 22.5 fc           | 5.7 ft            | 5.7 ft             |
| 8.0 ft          | 12.6 fc           | 7.6 ft            | 7.5 ft             |
| 10.0 ft         | 8.1 fc            | 9.5 ft            | 9.4 ft             |
| 12.0 ft         | 5.6 fc            | 11.4 ft           | 11.3 ft            |
| 14.0 ft         | 4.1 fc            | 13.3 ft           | 13.2 ft            |
| 16.0 ft         | 3.2 fc            | 15.2 ft           | 15.1 ft            |
| 18.0 ft         | 2.5 fc            | 17.1 ft           | 17.0 ft            |
| 20.0 ft         | 2.0 fc            | 19.0 ft           | 18.8 ft            |

**INDOOR COEFFICIENTS OF UTILIZATION**

| pf | 20% |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     | 0%  |    |
|----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|
| pc | 80% |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |     | 10% | 0% |
| pw | 70% | 50% | 30% | 10% | 70% | 50% | 30% | 10% | 50% | 30% | 10% | 50% | 30% | 10% | 50% | 30% | 10% | 0% |
| 0  | 118 | 118 | 118 | 118 | 115 | 115 | 115 | 115 | 110 | 110 | 110 | 105 | 105 | 105 | 101 | 101 | 101 | 99 |
| 1  | 113 | 110 | 108 | 106 | 110 | 108 | 106 | 104 | 104 | 103 | 101 | 101 | 99  | 98  | 97  | 96  | 95  | 94 |
| 2  | 108 | 103 | 100 | 97  | 106 | 102 | 98  | 96  | 99  | 96  | 93  | 96  | 93  | 91  | 93  | 91  | 90  | 88 |
| 3  | 103 | 97  | 93  | 89  | 101 | 96  | 92  | 88  | 93  | 90  | 87  | 91  | 88  | 86  | 89  | 86  | 84  | 83 |
| 4  | 98  | 91  | 86  | 83  | 97  | 90  | 86  | 82  | 88  | 84  | 81  | 86  | 83  | 80  | 85  | 82  | 79  | 78 |
| 5  | 94  | 86  | 81  | 77  | 92  | 85  | 80  | 77  | 84  | 79  | 76  | 82  | 78  | 75  | 81  | 77  | 75  | 73 |
| 6  | 90  | 82  | 76  | 72  | 88  | 81  | 76  | 72  | 79  | 75  | 71  | 78  | 74  | 71  | 77  | 73  | 70  | 69 |
| 7  | 86  | 77  | 72  | 68  | 84  | 77  | 71  | 68  | 75  | 71  | 67  | 74  | 70  | 67  | 73  | 69  | 67  | 65 |
| 8  | 82  | 73  | 68  | 64  | 81  | 73  | 67  | 64  | 72  | 67  | 64  | 71  | 66  | 63  | 70  | 66  | 63  | 62 |
| 9  | 78  | 70  | 64  | 60  | 77  | 69  | 64  | 60  | 68  | 63  | 60  | 67  | 63  | 60  | 67  | 63  | 60  | 59 |
| 10 | 75  | 66  | 61  | 57  | 74  | 66  | 61  | 57  | 65  | 60  | 57  | 64  | 60  | 57  | 64  | 60  | 57  | 56 |

**FG-R-T7-1-WFL-40K-90**

TEST NO.: **220062**


INPUT WATTS: **9.4**

LUMENS: **427**

EFFICACY: **45**

BEAM ANGLE: **80**

SPACING CRITERIA: **1.06**



**CANDELA TABLE**

|     | 0°  | 90° |
|-----|-----|-----|
| 0°  | 332 | 332 |
| 10° | 323 | 334 |
| 20° | 300 | 346 |
| 30° | 219 | 294 |
| 40° | 74  | 131 |
| 50° | 0   | 0   |
| 60° | 0   | 0   |
| 70° | 0   | 0   |
| 80° | 0   | 0   |
| 90° | 0   | 0   |

**LUMINANCE (cd/sq.m)**

|        | 0.00°   | 90.00°  |
|--------|---------|---------|
| 0.00°  | 5058376 | 5058376 |
| 45.00° | 716267  | 1391186 |
| 55.00° | 0       | 0       |
| 65.00° | 0       | 0       |
| 75.00° | 0       | 0       |
| 85.00° | 0       | 0       |

**LUMENS PER ZONE**

| ZONE      | LUMENS |
|-----------|--------|
| 0° - 10°  | 32     |
| 10° - 20° | 94     |
| 20° - 30° | 137    |
| 30° - 40° | 118    |
| 40° - 50° | 47     |
| 50° - 60° | 0      |
| 60° - 70° | 0      |
| 70° - 80° | 0      |
| 80° - 90° | 0      |

**ZONAL LUMEN SUMMARY**

| ZONE     | UMENS | % LUMINAIRE |
|----------|-------|-------------|
| 0° - 20° | 126   | 29%         |
| 0° - 30° | 262   | 61%         |
| 0° - 40° | 380   | 89%         |
| 0° - 60° | 427   | 100%        |
| 0° - 80° | 427   | 100%        |
| 0° - 90° | 427   | 100%        |

**CONE OF LIGHT**

| MOUNTING HEIGHT | FC AT BEAM CENTER | BEAM DIA. 0°-180° | BEAM DIA. 90°-270° |
|-----------------|-------------------|-------------------|--------------------|
| 6.0 ft          | 9.2 fc            | 8.7 ft            | 8.6 ft             |
| 8.0 ft          | 5.2 fc            | 11.6 ft           | 11.4 ft            |
| 10.0 ft         | 3.3 fc            | 14.4 ft           | 14.3 ft            |
| 12.0 ft         | 2.3 fc            | 17.3 ft           | 17.1 ft            |
| 14.0 ft         | 1.7 fc            | 20.2 ft           | 20.0 ft            |
| 16.0 ft         | 1.3 fc            | 23.1 ft           | 22.9 ft            |
| 18.0 ft         | 1.0 fc            | 26.0 ft           | 25.7 ft            |
| 20.0 ft         | 0.8 fc            | 28.9 ft           | 28.6 ft            |

**INDOOR COEFFICIENTS OF UTILIZATION**

| pf | 20% |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     | 0%  |    |
|----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|
| pc | 80% |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |     | 10% | 0% |
| pw | 70% | 50% | 30% | 10% | 70% | 50% | 30% | 10% | 50% | 30% | 10% | 50% | 30% | 10% | 50% | 30% | 10% | 0% |
| 0  | 116 | 116 | 116 | 116 | 114 | 114 | 114 | 114 | 109 | 109 | 109 | 104 | 104 | 104 | 100 | 100 | 100 | 98 |
| 1  | 111 | 108 | 105 | 103 | 108 | 106 | 104 | 101 | 102 | 100 | 98  | 98  | 97  | 95  | 95  | 94  | 93  | 91 |
| 2  | 105 | 100 | 96  | 92  | 103 | 98  | 94  | 91  | 95  | 92  | 89  | 92  | 90  | 87  | 89  | 87  | 85  | 84 |
| 3  | 99  | 93  | 87  | 83  | 97  | 91  | 86  | 83  | 89  | 85  | 81  | 86  | 83  | 80  | 84  | 81  | 79  | 77 |
| 4  | 94  | 86  | 80  | 76  | 92  | 85  | 79  | 75  | 83  | 78  | 74  | 81  | 77  | 73  | 79  | 75  | 73  | 71 |
| 5  | 88  | 80  | 74  | 69  | 87  | 79  | 73  | 69  | 77  | 72  | 68  | 75  | 71  | 68  | 74  | 70  | 67  | 65 |
| 6  | 83  | 74  | 68  | 63  | 82  | 73  | 68  | 63  | 72  | 67  | 63  | 70  | 66  | 62  | 69  | 65  | 62  | 60 |
| 7  | 79  | 69  | 63  | 58  | 78  | 68  | 63  | 58  | 67  | 62  | 58  | 66  | 61  | 58  | 65  | 61  | 57  | 56 |
| 8  | 75  | 65  | 58  | 54  | 73  | 64  | 58  | 54  | 63  | 58  | 54  | 62  | 57  | 53  | 61  | 57  | 53  | 52 |
| 9  | 71  | 60  | 54  | 50  | 69  | 60  | 54  | 50  | 59  | 54  | 50  | 58  | 53  | 50  | 57  | 53  | 50  | 48 |
| 10 | 67  | 57  | 51  | 47  | 66  | 56  | 50  | 47  | 55  | 50  | 46  | 55  | 50  | 46  | 54  | 49  | 46  | 45 |