





### **Constant Voltage TRIAC Dimmable Driver**


Output constant voltage / AC input: 108-132VAC / High efficiency up to 85% / Protection against short circuit / Overvoltage protection / Integrated junction box for hardwire installation / Fully isolated metal case - cooling by air convection / 5-year warranty / Suitable for dry or damp locations - IP20.

#### PN:HBL096-120-12-D

| Model           | Input Voltage | Output Voltage | Wattage | Rated Current | Frequency | Location                | Certificate  |
|-----------------|---------------|----------------|---------|---------------|-----------|-------------------------|--------------|
| HBL096-120-12-D | 108-132VAC    | 12VDC          | 96W     | 8A            | 50/60Hz   | Dry or<br>Damp location | ETL, Class 2 |

TRIAC Dimming for 108VAC / Non-Dimming for 132VAC

#### **DIMENSIONS**




## **Constant Voltage TRIAC Dimmable Driver**


Constant voltage mode / Universal AC input / Full range AC 120-277V / ETL Certification, Class P power unit / Protections: short circuit, overload, overvoltage / Fully isolated aluminum case / Suitable for dry or damp locations.

### PN:HBL150-AW-12-DI

| Model           | Input Voltage | Output Voltage | Wattage | Rated Current | Frequency | Location                | Certificate  |
|-----------------|---------------|----------------|---------|---------------|-----------|-------------------------|--------------|
| HBL150-AW-12-DI | 120-277VAC    | 12VDC          | 150W    | 12.5A         | 50/60Hz   | Dry or<br>Damp location | ETL, Class P |

TRIAC Dimming for 120VAC / Non-Dimming for 277VAC













## **Constant Voltage TRIAC Dimmable Driver**

Constant Voltage Mode with Universal AC input / full range from AC 120-277V / Strong compatibility and flicker-free dimming / ETL certification, Class 2 power unit / Protections against short circuit, overload, and overvoltage / Fully isolated aluminum case with IP20 level / Suitable for dry or damp locations.

### PN: HBL040-AW-12-DA

| Model           | Input Voltage | Output Voltage | Wattage | Rated Current | Frequency | Location                | Certificate  |
|-----------------|---------------|----------------|---------|---------------|-----------|-------------------------|--------------|
| HBL040-AW-12-DA | 120-277VAC    | 12VDC          | 40W     | 3.33A         | 50/60Hz   | Dry or<br>Damp location | ETL, Class 2 |


TRIAC Dimming for 120VAC / Non-Dimming for 277VAC


### PN: HBL060-AW-12-DA

| Model           | Input Voltage | Output Voltage | Wattage | Rated Current | Frequency | Location                | Certificate  |
|-----------------|---------------|----------------|---------|---------------|-----------|-------------------------|--------------|
| HBL060-AW-12-DA | 120-277VAC    | 12VDC          | 60W     | 5A            | 50/60Hz   | Dry or<br>Damp location | ETL, Class 2 |

TRIAC Dimming for 120VAC / Non-Dimming for 277VAC

#### **DIMENSIONS**













# **Connecting Diagram**

