




HH4SQ-LED-TWH-50K-27K-1200L-MD-HH4-4614-CL-WH

TEST NO.: **LM-63-2002**

INPUT WATTS: **21.8** LUMENS: **1274** CRI: **90+** EFFICACY: **58** CCT: **4000K** SPACING CRITERIA: **1.22**

Candle Power Distribution (Candelas)



Zonal Lumens Summary

Zone	Lumens	%Lamp	%Fixt
0-20	298.96	N.A.	23.50
0-30	636.30	N.A.	50.00
0-40	960.10	N.A.	75.40
0-60	1242.4	N.A.	97.50
0-80	1271.84	N.A.	99.90
0-90	1273.65	N.A.	100.00

Luminance (Average candela/M²)

Angle in Degrees	Average		
	0°	45°	90°
45	34247	39080	24534
55	17658	12818	13229
65	8993	4126	2100
75	1975	1015	525
85	2993	1691	256

Lumens Per Zone

Zone	Lumens
0-10	74.71
10-20	224.25
20-30	337.34
30-40	323.80
40-50	197.44
50-60	84.85
60-70	25.26
70-80	4.18
80-90	1.82

Candela Tabulation

0	Q
0	771.83
5	775.73
15	773.44
25	674.50
35	475.00
45	249.71
55	104.44
65	39.19
75	5.27
85	2.69
90	1.40

Coefficients of Utilization - Zonal Cavity Method

Effective Floor Cavity Reflectance 0.20

Cone of Light		
4.0	48.2	6.5 ft.
8.0	12.1	13.0 ft.
12.0	5.36	19.4 ft.
16.0	3.01	25.9 ft.
20.0	1.93	32.4 ft.
24.0	1.34	38.9 ft.
Distance to Plane	Initial Footcandle at Nadir	Beam diameter

BEAM DIA. MEASURED AT 50% OF NADIR F.C.




RC	RW	80%				70%				50%				30%				10%				0%			
		70%	50%	30%	10%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%			
0	0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	102	100					
1	1	112	109	106	104	110	107	104	102	103	101	99	99	97	96	96	94	93	91						
2	2	105	100	95	91	103	98	93	90	94	91	88	91	88	86	89	86	84	82						
3	3	99	91	85	80	96	89	84	80	87	82	78	84	80	77	82	79	76	74						
4	4	92	83	77	72	90	82	76	71	80	74	70	76	73	69	76	72	69	67						
5	5	86	76	69	64	85	75	69	64	74	68	63	72	67	63	70	66	62	61						
6	6	81	70	63	58	79	70	63	58	68	62	58	66	61	57	65	60	57	55						
7	7	76	65	58	53	75	64	58	53	63	57	52	62	56	52	60	56	52	50						
8	8	71	60	53	48	70	60	53	48	58	52	48	57	52	48	56	51	48	46						
9	9	67	56	49	44	66	55	49	44	54	48	44	53	48	44	53	48	44	42						
10	10	64	52	46	41	62	52	45	41	51	45	41	50	45	41	49	44	41	39						

RC - Ceiling Cavity Reflectance RW - Wall Reflectance



CONTROL OPTIONS

With the integration of controls, Elite Lighting now offers its products with controls-ready performance that increases energy efficiency, smarter space planning, and the enhancement of safety and productivity in the workplace. By utilizing these controls, Elite Lighting luminaires enable your customer's facility to run smarter, with the use of an easily controlled system through any platform.

CONTROL PROTOCOLS	SMART WHITE	LEDENGIN	LUMENETIX	
<p><input type="checkbox"/> ELITE-CONNECT (EC-WC-TWH-HW-MVOLT) - Hard-wired, 0-10V, 120/277V wall mounted controller for CCT Tuning and Intensity Dimming through Simple Touch screen pad, provided by Elite Lighting. Programmable for up to 3-scenes, with a dimming range down to 1%. Applicable for office spaces, hospitality, educational, healthcare, and retail merchandising.</p> 	✓	✓	N/A	
<p><input type="checkbox"/> DIM10 (0-10V 1% Dimming Standard) In order to Control the Color Tuning and dimming option with 0-10V driver you must dedicate two control inputs, one for the Dimming Control and another for CCT Tuning. Can be dimmed and tuned with 2 wall box dimmers and compatible with most control systems and/or daylight harvesting systems.</p> <p><input type="checkbox"/> DIM10-LUTRON Compatible with Lutron GRAFIK Eye QS or GRAFIK Eye 3000 by using two GRX-TVI Lutron 0-10V Dimming interfaces; one to tune and another to control dimming. Also compatible with Lutron VIVE system by using two FCJS-010 PowPak or FCJS-ECO EcoSystem PowPak modules per fixture; one to tune and one to control dimming.</p> 	✓	✓	✓	
<p><input type="checkbox"/> DMX (Available on Elite, LED Engin and Lumenetix platforms) - Compatible with Digital Multiplex Controller, Available with two options: DMX-512: Standard DMX Controller and DMX-RDM: DMX Controller with Remote Device Management.</p>	✓	✓	✓	
<p><input type="checkbox"/> LUTECO Compatible with Lutron EcoSystem. Compatible with Lutron GRAFIK Eye EcoSystem, Lutron Energi Saver node EcoSystem, or Lutron Quantum systems.</p>	✓	N/A	✓	
<p><input type="checkbox"/> BLE - Dimming and CCT can be controlled via Bluetooth using an app, via Smartphones or tablets. Lumenetix (Araya5 Module) platform has a range of 8000K to 1650K (RGBW-LTX-80K-16K). For simple deployment, Lumenetix platform allows up to five scenes to be pre-programmed into the module and recalled at the venue using the Lumenetix App. Commissioning of the module and reprogramming of scenes are done via the wireless Lumenetix App, via Smartphone that connects to the embedded radio control via DMX512-RDM, LUTECO, BLE, DALI, DLM.</p>		N/A	✓	✓
<p><input type="checkbox"/> DALI Compatible with Digital Addressable Lighting Interface, available with two options: DT6 and DT8.</p>	✓	✓	✓	
<p><input type="checkbox"/> DLM The combination of the Blanco 3 with DLM from Legrand Wattstopper enables simple commissioning, synonymous with DLM and the enhanced features and flexibility.</p>	N/A	N/A	✓	