

SQUARE & FEATURES SPECIFICATIONS

Architectural High Lumen LED Downlight

HH4SQ-LED
2000 LUMENS

4"

Square



VIBRANT	TYPE	LUMENS/DRIVER				VOLTAGE	OPTICS	CCT	CRI	EMERGENCY	TRIM TYPE	REFLECTOR/ RING FINISH
		900L SERIES	1200L SERIES	1500L SERIES	2000L SERIES							
HH4SQ-LED	☐	☐ 900L-DIM10	☐ 1200L-DIM10	☐ 1500L-DIM10	☐ 2000L-DIM10	☐ 120	☐ WD (70°-75°)	☐ CW	☐ 85+	☐ EMG-LED Typical lumen output of the fixture is up to 1000L in emergency mode. Contact the factory for details.	☐ LED-4607 ☐ LED-4614 ☐ LED-4615	☐ CL-WH ☐ CL-SCH ☐ SHZ-SHZ ☐ SHZ-WH ☐ W-WH ☐ MB-WH ☐ WT-WH
		☐ 900L-DIMTR ¹	☐ 1200L-DIMTR ¹	☐ 1500L-DIMTR ¹	☐ 2000L-DIMTR ¹	☐ 277	☐ MD (55°-60°)	☐ WW	☐ 90+			
		☐ 900L-LUTTH ²	☐ 1200L-LUTTH ²	☐ 1500L-LUTTH ²	☐ 2000L-LUTTH ²	☐ 347	☐ ND (35°-40°)	☐ TL				
		☐ 900L-LUT2W ¹	☐ 1200L-LUT2W ¹	☐ 1500L-LUT2W ¹	☐ 2000L-LUT2W ¹	(DIM10 only)		☐ RG				
		☐ 900L-ELD010-1 ²	☐ 1200L-ELD010-1 ²	☐ 1500L-ELD010-1 ²	☐ 2000L-ELD010-1 ²							
		☐ 900L-ELD0DALI-1 ²	☐ 1200L-ELD0DALI-1 ²	☐ 1500L-ELD0DALI-1 ²	☐ 2000L-ELD0DALI-1 ²							
		☐ 900L-ELD0DMX-1 ²	☐ 1200L-ELD0DMX-1 ²	☐ 1500L-ELD0DMX-1 ²	☐ 2000L-ELD0DMX-1 ²							

¹ LUT2W and DIMTR are available in 120V only

² LUTH, ELD010-1, ELD0DALI -1, and ELD0DMX-1 are available in 120V and 277V

RG (Red Glow) Vibrant series are available up to 1500L only

REFLECTOR		RING
CL - Clear	WT -Wheat	WH Self-Flange White
SHZ -Satin Haze	MB -Black	SCH Self-Flange Chrome
(Low Irridescent)	W -White	SHZ Satin Haze

**For custom baffle, reflector, trim ring, glass color and lens options, please consult factory.*

4 INCH SQUARE ARCHITECTURAL HIGH LUMEN LED DOWNLIGHT