


**MOS-6601**  
Open Reflector



**MOS-6614**  
Reflector with  
Frosted Glass Lens



**MOS-6607**  
Wall Wash Reflector  
with Diffuse Lens



**EX-TL-6601**  
Trimless Open  
Reflector



**EX-TL-6614**  
Trimless Reflector with  
Frosted Glass Lens



**EX-TL-6607**  
Trimless Wall Wash Reflector  
with Diffuse Lens

REFLECTOR/  
FLANGE COLORS



CL-WH



CL-SCH



SHZ-WH



SHZ-SHZ





WT-WH



W-WH



MB-BK



A: Height = 7-3/8"  
B: Trim Aperture = 6"  
C: Cut-Out = 6-1/2"  
D: Trim Outside Dia = 7-1/8"  
G: Width = 16"  
H: Length = 32" Min: 21"

NOMINAL LUMENS	DELIVERED LUMENS	WATTAGE
4000	4001	43 W
3000	2713	32 W
2000	1872	17 W
1500	1498	14 W
1200	971	10 W
900	-	-

Based on 4000K, 90+CRI with semi-specular chrome reflector.  
Actual wattage may vary +/-5%

## FEATURES

A highly sustainable and ultra-efficient architectural LED downlight that provides even, glare-free illumination. Available in a range of finishes and lumen packages, it is ideally suited for use in corporate office space, hospitality, healthcare, commercial, academic, churches and retail.


## OPTICS AND REFLECTOR

The reflector has a 45° visual cutoff, and is shipped standard with a Solite lens in a smooth frosted finish. Spun from 0.05" thick aluminum, with a 1-step anodized finish, and available in different colors or custom RAL finishes. Reflector flange options include self-flanged and white painted flange.

LUMENS	900, 1200, 1500, 2000, 3000*, 4000 (Custom lumen packages available)
CCT & DYNAMIC PLATFORMS	27K, 30K, 35K, 40K, 50K, Tunable White, Dims to Warm, RGB + White
CRI	90+ Standard, 98+ Optional
COLOR QUALITY	2 Step MacAdam Ellipse
DISTRIBUTIONS	MD (Medium Distribution) - 45° visual cutoff
TRIM OPTIONS	Downlight, Wall Wash, Wet Location
REFLECTOR COLORS	CL (Semi-Specular Chrome), SHZ (Low Iridescent Satin Haze), WT (Wheat), WH (White), MB (Black)
FLANGE COLORS	Self-Flanged WH (White), SCH (Semi-Specular Chrome), SHZ (Low Iridescent Satin Haze), BK (Black)
DIMMING	0-10V Flicker Free 1% Dimming Standard (DIM10), LUTH, LUTFTB, LUT2W, ELDO10.1, ELDDMX.1, ELDDALI.1, DIMTR
EMERGENCY	10W - Up to 1000L Output 20W - Up to 2000L Output EMG-LED-G2-10W-SDT - Self Diagnostic (Consult Factory)
LIFETIME	L70 at 102,000 Hours
PHOTOMETRIC TESTS	In Accordance with IES LM79-08, LM80 and TM-30, TM-21

\* Only Available on 85+ CRI

MD: Medium  
Candlepower Distribution Curve



Reference IES files for additional distribution curve information.



### THERMAL MANAGEMENT SYSTEM

Passive cooling Diecast Aluminum Heat Sink, LED light engine and driver are replaceable, upgradeable, and can be accessed from below the ceiling. The consistency in the quality of light is delivered with precision performance by the use of a unique locking mechanism that aligns the reflector with the light engine.

### MOUNTING FRAME & BRACKETS

The downlight mounting frame is a fabricated assembly constructed of 16-gauge steel, with C-channel mounting brackets, included. The versatility of the mounting bracket allows for an adjustability of up to 28" horizontally, and 2-3/4" vertically, locking into place. With the added die-formed construction of the mounting frame, it provides maximum heat dissipation and rust protection.

### DRIVER ELECTRICAL INFORMATION

The LED driver is rated for 50 to 60Hz at 120V/277V, also available in 347V input, produces less than 20%THD, has a power factor between 90% and 100%, and is thermally protected for additional safety. Junction box and Driver can be accessed from below the ceiling and above the ceiling. Junction Box is Listed for through branch circuit wiring.

### DIMMING & DRIVER INFORMATION

**DIM10** - 0-10V dimming on either MVOLT 120, 277 or 347V. Dimmable down to 1% of initial lumens, standard.

**DIMTR** - Triac & Electronic low voltage dimming. Available in 120V, and up to 4000 lumens only.

**LUT2W** - Lutron LTEA2W Hi-Lume 1%. 2-wire LED Driver Forward Phase Control, 1% dimming in 120V only. Available on all luminaires up to 3000 lumens.

**LUTH** - Lutron LDE1 Hi-Lume Eco System. 1% dimming with Soft in Fade to Black dimming technology. Available on all luminaires up to 3000 lumens.

**LUTFB** - Lutron PEQ0 Hi-Lume Premier Eco System. 0.1% dimming with Soft in Fade to Black dimming technology. Available on all luminaires up to 1500 lumens.

**ELDO10.1** - EldoLED SoloDrive 0-10V. Dimming down to 0.1%.

**DALI** - DALI DT6, DT8 dimming down to 1%.

**ELDODMX** - EldoLED PowerDrive dimming down to 0.1%.

Please see EldoLED website for wiring diagrams and a list of compatible DMX and DALI control systems.

### WARRANTY

Five-year warranty for parts and components. (Labor not included)

### LED DYNAMIC PLATFORM OPTIONS



**Tunable White with Smart White Technology** utilizing the Lumenetix Platform allows you to color tune the luminaire via various controls. Create the perfect environment for the desired use of the space, while maintaining a CRI of 90+ across the tunable range of 8000 to 1650K. (Click here for more details)



**Dims to Warm with Smart Dimming Technology.** At 100% full brightness the luminaire is at 3000K. When dimmed to 1%, the light transitions to 1800K, creating a warm ambiance within the space. (Click here for more details)



**RGB+White with Smart Hue Technology** provides full color mixing of RGB and white colors. Utilizing the Lumenetix Platform allows you to choose from unlimited RGB color options, via various controls. Ideal for Circadian Rhythm applications or to create the perfect human centric environment. (Click here for more details)

### LISTINGS

c-UL-us - Listed for Wet Location except if used with MOS-6601 Trim.

c-UL-us - Listed for Feed Through Wiring.

U.S Patent No. - D685,118S

Energy Star and California Title 24 compliant

Optional Black color trim is not ENERGYSTAR certified and won't meet the requirement.

Example: HH6SQ-LED-2000L-DIM10-MVOLT-MD-40K-90-MOS-6601-CL-WH

SERIES	LUMENS	DRIVER	VOLTAGE	CCT	EMERGENCY	TRIM TYPE	REFLECTOR/FLANGE COLORS
HH6SQ-LED	<input type="checkbox"/> 900L <input type="checkbox"/> 1200L <input type="checkbox"/> 1500L <input type="checkbox"/> 2000L <input type="checkbox"/> 3000L <input type="checkbox"/> 4000L	<input type="checkbox"/> DIM10 <input type="checkbox"/> DIMTR <sup>1</sup> <input type="checkbox"/> LUTH <sup>2</sup> <input type="checkbox"/> LUT2W <sup>1</sup> <input type="checkbox"/> LUTFB <sup>5</sup> <input type="checkbox"/> ELDO10-1 <sup>2</sup> <input type="checkbox"/> ELDODALI-1 <sup>2</sup> <input type="checkbox"/> ELDODMX-1 <sup>2</sup>	<input type="checkbox"/> 120 <input type="checkbox"/> 277 <input type="checkbox"/> MVOLT <input type="checkbox"/> 347 (DIM10 only)	<input type="checkbox"/> 27K <input type="checkbox"/> 30K <input type="checkbox"/> 35K <input type="checkbox"/> 40K <input type="checkbox"/> 50K <sup>3</sup>	<input type="checkbox"/> EMG-LED-10W <input type="checkbox"/> EMG-LED-20W <input type="checkbox"/> EMG-LED-G2-10W-SDT*  Typical lumen output of the luminaire is up to 1000L with EMG-LED-10W option & 2000L with EMG-LED-20W option in emergency mode. Contact the factory for details. Remote mounted installation * Consult Factory for Self Diagnostic	<input type="checkbox"/> MOS-6601 Open Reflector <input type="checkbox"/> MOS-6607 Wall Wash Reflector with Diffuse Lens <input type="checkbox"/> MOS-6614 Reflector with Frosted Glass Lens  <b>TRIMLESS</b> <input type="checkbox"/> EX-TL-6601 Trimless Open Reflector <input type="checkbox"/> EX-TL-6607 Trimless Wall Wash Reflector with Diffuse Lens <input type="checkbox"/> EX-TL-6614 Trimless Reflector with Frosted Glass Lens	<input type="checkbox"/> CL-WH <input type="checkbox"/> CL-SCH <input type="checkbox"/> SHZ-WH <input type="checkbox"/> SHZ-SHZ <input type="checkbox"/> WT-WH <input type="checkbox"/> WH-WH <input type="checkbox"/> MB-WH* <input type="checkbox"/> MB-BK*
			<b>OPTICS</b>	<b>CRI</b>			
			<input type="checkbox"/> MD	<input type="checkbox"/> 90+ <input type="checkbox"/> 98+ <sup>4</sup>			

<sup>1</sup> DIMTR and LUT2W are available in 120V only

<sup>2</sup> LUTH, ELDO10-1, ELDODALI-1, and ELDODMX-1 are available in 120V and 277V

<sup>3</sup> 50K series are available with 85+ CRI only

<sup>4</sup> 98+ CRI is available in 27K, 30K and 40K only

<sup>5</sup> LUTFB Available for luminaires up to 1500L

-Reference last page for Control Options

DIMTR Available for luminaires up to 4000L

**HH6SQ-LED-2000L-DIM10-MVOLT-MD-40K-90-MOS-6601-CL-WH**

INPUT WATTS: **17.4**

LUMENS: **1872**

CRI: **90**


EFFICACY: **108**

CCT: **4000K**

TEST NO.: **EL011929**

SPACING CRITERIA: **0.74**

**Candle Power Distribution (Candelas)**



**Zonal Lumens Summary**

Zone	Lumens	%Lamp	%Fixt
0-20	874.66	46.70	46.70
0-30	1452.64	77.60	77.60
0-40	1754.72	93.70	93.70
0-60	1863.75	99.50	99.50
0-80	1871.18	99.90	99.90
0-90	1872.39	100.00	100.00

**Luminance (Average candela/M²)**

Angle in Degrees	Average 0°	Average 45°	Average 90°
45	919	5691	15567
55	509	819	1036
65	330	483	769
75	171	406	602
85	89	760	987

**Lumens Per Zone**

Zone	Lumens
0-10	267.01
10-20	607.64
20-30	577.99
30-40	302.08
40-50	96.31
50-60	12.71
60-70	4.98
70-80	2.45
80-90	1.22

**Candela Tabulation**

Q	
0	2979.43
5	2842.39
15	1954.33
25	1076.96
35	138.68
45	15.10
55	6.79
65	3.24
75	1.03
85	0.18
90	0.04

**Coefficients of Utilization - Zonal Cavity Method**

Effective Floor Cavity Reflectance 0.20

Cone of Light			
2	745	1.7	1.7
4	186	3.4	3.4
6	82.8	5.1	5.1
8	46.6	6.8	6.8
10	29.8	8.4	8.5
12	20.7	10.1	10.1
(FT.) Distance to Plane	(FC.) Initial Footcandle at Nadir	(FT.) Beam Vert. Spread	(FT.) Beam Horiz. Spread

BEAM DIA. MEASURED AT 50% OF NADIR F.C.

	RC	80%				70%				50%				30%				10%				0%
	RW	70%	50%	30%	10%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%			
ROOM CAVITY RATIO	0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
	1	114	111	109	107	111	109	107	105	105	103	102	101	100	99	98	97	96	94			
	2	109	104	100	97	106	102	99	96	99	96	94	96	94	92	93	92	90	88			
	3	104	97	93	89	102	96	92	88	94	90	87	88	86	86	89	86	84	83			
	4	99	92	86	82	97	91	86	82	88	84	81	87	86	83	80	85	82	79			
	5	94	86	81	77	93	85	80	76	84	79	76	82	78	75	81	77	75	73			
	6	90	82	76	72	88	81	76	72	79	75	71	78	74	71	77	73	70	69			
	7	86	77	72	68	85	77	71	67	75	71	67	74	70	67	73	69	66	65			
	8	82	73	68	64	81	73	67	64	72	67	63	71	66	63	70	66	63	61			
	9	79	69	64	60	77	69	64	60	68	63	60	67	63	60	66	62	60	58			
10	75	66	61	57	74	66	61	57	65	60	57	64	60	57	63	59	57	55				

RC - Ceiling Cavity Reflectance

RW - Wall Reflectance

1- Luminaire will be shipped with Powerpacks pre-installed, ready to be integrated to designated control systems

2- Luminaire will be shipped with Sensors installed on the luminaire, allowing for individual luminaire control. Luminaires will be ready to be integrated with designated control systems

3- Luminaire will be shipped with Sensors to be remotely installed on the ceiling. Luminaires will be ready to be integrated with designated control systems

BRAND	EASYFIT by EnOcean	LUTRON	enlighted	LEVITON®	OSRAM	PHILIPS EasySense	legrand®
CONTROL UNIT	<input type="checkbox"/> LEDRU LED Relay Zone Controller 0-10V <sup>1</sup>	<input type="checkbox"/> FCJS-010 Lutron Vive 0-10V Individual Pow Pak (Luminaire is shipped Vive Enabled) <sup>14</sup>	<input type="checkbox"/> CU-4E-FMH Fixture Mount Control Unit <sup>15</sup>	<input type="checkbox"/> ZL027 –NOW Intellect Power Control Module <sup>16</sup>	<input type="checkbox"/> EN-WCM2-ZB-DR Wireless Control Module <sup>17</sup>	<input type="checkbox"/> SBR -BS Xitanium SR Bridge <sup>18</sup>	<input type="checkbox"/> LMFC-011 ON/OFF/0-10V dimming fixture controller <sup>19</sup>
	<input type="checkbox"/> LEDDU LED Zone Controller 0-10V <sup>1</sup>	<input type="checkbox"/> FCJS-ECO Lutron Vive Eco-system Pow Pak (Luminaire is shipped Vive Enabled) <sup>14</sup>		<input type="checkbox"/> ZL027 –NOW Intellect Power Control Module <sup>16</sup>	<input type="checkbox"/> EN- ALC-ZB-BK-DR Wireless Area Lighting Control Module <sup>17</sup>  <input type="checkbox"/> ZBHA-CLM-DIM-ENC Connected Lighting Module DIM <sup>17</sup>		
INTEGRAT SENSOR	N/A	N/A	N/A	N/A	N/A	N/A	N/A
*WIRELESS OCCUPANCY SENSOR	<input type="checkbox"/> EOSCU-W-EO Occupancy Sensor - Ceiling Mounted (Must be specified with LEDRU or LEDDU control unit) <sup>3</sup>	N/A	N/A	N/A	N/A	N/A	<input type="checkbox"/> LMDC-100 Dual technology PIR Ceiling Mount Occupancy Sensor <sup>3</sup>
*WIRELESS DAYLIGHT SENSOR	<input type="checkbox"/> ELLSU-W-EO Light Level Sensor - Ceiling Mounted (Must be specified with LEDRU or LEDDU control unit) <sup>3</sup>	N/A	N/A	N/A	N/A	N/A	<input type="checkbox"/> LMLS-400 Single zone switching and dimming digital photosensor <sup>3</sup>
*WIRELESS OCCUPANCY & DAYLIGHT SENSOR	N/A	N/A	<input type="checkbox"/> SU-5E-IoT IoT Node Micro Sensor <sup>3</sup> <input type="checkbox"/> SU-5E-CL Connected Lighting Micro Sensor <sup>3</sup> <input type="checkbox"/> SU-5E-IL Independent Lighting / Enlighted One Micro Sensor <sup>3</sup> <input type="checkbox"/> SU-5S-H-(IoT/CL/IL) Surface Mount Sensor <sup>3</sup>  (Must be specified with CU 4E-FMH Control Unit)	<input type="checkbox"/> ZL00J -TOW Intellect Intelligent Fixture Control System <sup>3</sup>  (Must be specified with ZL027 –NOW Control Unit)	<input type="checkbox"/> EN-CLM-PIR-DD-ZB SensiLUM™ Wireless Integrated Sensor <input type="checkbox"/> EN-SCPPH-1500-ZB Wireless Passive Infrared Occupancy and Photo Sensors <sup>3</sup>  (Must be specified with EN-WCM2-ZB-DR or EN- ALC-ZB-BK-DR Control Unit)	<input type="checkbox"/> SNS200- CMP SNS200 for grouping <sup>3</sup>	N/A
ACCESSORIES	N/A	N/A	<input type="checkbox"/> TMC-SU-5E Tile Mount Carrier <input type="checkbox"/> CBL-5E-CU4-30N 30 inch Sensor Cable for CU-4 and IoT Ready™ drivers <input type="checkbox"/> CBL-5E-CU4-7F 7 foot Sensor Cable for CU-4 and IoT Ready™ drivers	N/A	N/A	N/A	N/A
NOTES	N/A	4- Luminaire will be compatible with Lutron LRF2-OCR2B-P-WH Ceiling mount 360° occupancy/vacancy sensor & LRF2-DCRB-WH Ceiling-mount daylight sensor. Sensors must be ordered through Lutron.	5- Luminaire will be compatible with ENLIGHTED SU-5E-IoT, SU-5E-CL, SU-5E-IL, SU-5S-H, Sensors.	6-Luminaire will be compatible with Leviton Intellect App & Keypad Room Controller	7-Luminaire will be compatible with EN-SCPPH-1500-ZB Wireless Passive Infrared Occupancy and Photo Sensors	8-Luminaire will be compatible with Philips field and wireless switch.	9-Luminaire will be compatible with DLM Room control system LMPB-100. DLM control system must be orderd through Legrand.