


# HVJ8-LED 8" ARCHITECTURAL LED RETROFIT DOWNLIGHT



**2000  
LUMENS**



- A** Height = 9"
- B** Trim Aperture = 8"
- C** Cut-out = 8-1/2"
- D** Trim Outside Dia. = 9-1/8"

INPUT VOLT.	INPUT FREQ.	INPUT CUR.	THD	POWER FACTOR	INPUT POWER	LUMENS
120/277	50/60Hz	333mA/144mA	<20%	>0.9	40W(+/-5%)	2000
120/277	50/60Hz	283mA/123mA	<20%	>0.9	34W(+/-5%)	1500
120/277	50/60Hz	180mA/76mA	<20%	>0.9	21W(+/-5%)	1100
120/277	50/60Hz	133mA/57mA	<20%	>0.9	16W(+/-5%)	800

**DESCRIPTION** - 8" LED dedicated Architectural Retrofit Downlight with integral LED heat management casting and driver. Available in 800 lumens, 1100 lumens, 1500 lumens and 2000 lumens. Lighting is smooth and comfortable while using 50% less energy than the common 26W & 32W CFL downlight. Plus the eco-friendly MAXILUME LED system features 70% lumen maintenance at 50,000hrs of life, with California Title-24 (compliances pending). Designed to install into an existing downlights mounting frame and convert them into energy efficient LED downlights to save anywhere from 35% up to 75% on energy cost. Fits all downlights with 8-1/2" aperture. Custom size and aperture, LED retrofit and reflectors are available, please consult factory for further details.

**FEATURES** - Greater light output than a 26W & 32W CFL. MAXILUME LED luminaires are ideally suited for use in hospitality, health care, commercial, academic institutions, retail and other architectural applications.



**OPTICS** - MAXILUME LED Optilux technology combines unmatched performance with visual comfort. Spun 0.05" thick reflector has been designed to gather the light scattered by the LED chip and shape it into functional beams that minimize brightness and glare, while eliminating lamp image. Proprietary dual level upper and lower reflector design allows for optimum glare control. Elite engineered superior quality, light engine; producing 800 lumens, 1100 lumens, 1500 lumens and 2000 lumens.

**PERFORMANCE** - Operating system delivers 800, 1100, 1500 & 2000 lumens. All MAXILUME LED luminaires are rated at 85+, 90+ and 98+ CRI, and are binned to within 3 MacAdam ellipses. Elite's highly selective LED chips produce zero ultraviolet and virtually no infrared light. All LED luminaires are rated and tested to LM-79 and LM-80 standards by an independent laboratory.

**THERMAL MANAGEMENT SYSTEM** - Using a proprietary coolLED Advanced Thermodynamic Design, Die-cast aluminum housing and heat management system are engineered for extremely long life and service period. Heat sink is attached to top of housing. The LED light engine is attached to the die-cast heat sink and is easily replaceable and upgradable. Life tests have shown the MAXILUME light engine output will be maintained at 70% of initial at 50,000hrs of operation.

**DIMMABLE** - The MAXILUME LED system is shipped standard with a 0-10V driver which can be dimmed down to 1% of initial light output with a 0-10V dimmer when ordered with the following options (DIM10-120, DIM10-277). Fixtures can also be shipped with a Lutron Hi-lume A series driver which can be dimmed with Lutron Dimming Systems when ordered with the following options (LUTH-120, LUTH-277), or EldoLed 0-10V 1% Dimming, consult factory for other EldoLed driver and other driver options. Triac & Electronic Low Voltage dimming driver also available when ordered with the following options (DIMTR-120). All fixtures with 3000L and below are dimmable down to 1% and the fixtures with 4000L and above can be dimmed down to 10%.

**INSTALLATION** - The installation time is less than 10 minutes.

**LED DRIVER/JUNCTION BOX** - The LED driver is rated for 50 to 60Hz at 120V /277V input, produces less than 20%THD, and has a power factor between 90% and 100% and is thermally protected for additional safety. MAXILUME's LED driver is installed on the junction box cover so it may be serviced from below the ceiling. UL Listed for through-branch circuit wiring, provided with four 1/2" knockouts, one 3/4" knockout and four Romex knockouts with true pryout slots and strain clamps. Designed for straight through conduit runs.

**MOUNTING** - Our retrofit is designed to install into an existing downlights mounting frame and convert them into energy efficient LED downlights. Flex is designed to attach into existing junction box.

**OUR WORD** - The MAXILUME LED lighting system carries a five-year carefree warranty for parts and components. (Labor not included.)

## DIMMING INFORMATION

**DIM10** (0-10V 1% Dimming)

**LUTH** (Lutron® Hi-Lume A-Series 3-Wire or Eco System 1% Dimming up to 4000 lumens only)

**ELDO10** (EldoLed 0-10V 1% Dimming up to 3000 lumens only, consult factory for the EldoLed driver options)

**DIMTR** (Triac & Electronic Low Voltage Dimming)

LED Driver options:



Example: HVJ8-LED-1100L-DIM10-120-MD-30K-LED-6101-CL-WH

TYPE	800L SERIES	1100L SERIES	1500L SERIES	2000L SERIES	VOLTAGE	OPTICS	CCT	CRI	EMERGENCY	TRIM TYPE		REFLECTOR/ RING FINISH	DISC
HVJ8-LED	<input type="checkbox"/> 800L-DIMTR* <input type="checkbox"/> 800L-LUTH <input type="checkbox"/> 800L-DIM10 <input type="checkbox"/> 800L-ELDO10	<input type="checkbox"/> 1100L-DIMTR* <input type="checkbox"/> 1100L-LUTH <input type="checkbox"/> 1100L-DIM10 <input type="checkbox"/> 1100L-ELDO10	<input type="checkbox"/> 1500L-LUTH <input type="checkbox"/> 1500L-DIM10 <input type="checkbox"/> 1500L-ELDO10	<input type="checkbox"/> 2000L-LUTH <input type="checkbox"/> 2000L-DIM10 <input type="checkbox"/> 2000L-ELDO10	<input type="checkbox"/> 120 <input type="checkbox"/> 277 <input type="checkbox"/> 347	<input type="checkbox"/> MD (Medium)	<input type="checkbox"/> 27K <input type="checkbox"/> 30K <input type="checkbox"/> 35K <input type="checkbox"/> 40K <input type="checkbox"/> 50K (85+CRI only)	<input type="checkbox"/> 85+ <input type="checkbox"/> 90+ <input type="checkbox"/> 98+**	<input type="checkbox"/> EMG-LED  Typical lumen output of the fixture is up to 1000L in emergency mode. Contact the factory for details.	<input type="checkbox"/> LED-8101 <input type="checkbox"/> LED-8102 <input type="checkbox"/> LED-8107 <input type="checkbox"/> LED-8109 <input type="checkbox"/> LED-8110 <input type="checkbox"/> LED-8128 <input type="checkbox"/> LED-8123	<input type="checkbox"/> LED-8112 <input type="checkbox"/> LED-8113 <input type="checkbox"/> LED-8114 <input type="checkbox"/> LED-8115 <input type="checkbox"/> LED-8121 <input type="checkbox"/> LED-8122 <input type="checkbox"/> LED-8125	<input type="checkbox"/> CL-WH <input type="checkbox"/> CL-SCH <input type="checkbox"/> SHZ-SHZ <input type="checkbox"/> SHZ-WH <input type="checkbox"/> W-WH <input type="checkbox"/> MB-WH <input type="checkbox"/> WT-WH	<input type="checkbox"/> BLUE <input type="checkbox"/> RED <input type="checkbox"/> GREEN <input type="checkbox"/> FROST <input type="checkbox"/> AL <input type="checkbox"/> BZ <input type="checkbox"/> WH

\* DIMTR option only available in 120 Volt.

\*\* 98+ CRI is available in 27K, 30K and 40K only

**MAXILUME**

WWW.MAXILUME.COM • TEL 1-877-375-5555 • FAX 1-877-375-3333

ISSUE 16H11 Rev. 0.5

LED  
8"

8 INCH ARCHITECTURAL LED RETROFIT DOWNLIGHT

# 8" LED OPTICS




**EXAMPLE:** LED-8101-CL-WH

**LED-8101 - REFLECTOR**

**REFLECTOR/RING FINISH:**

CL-WH CL-SCH WT-WH SHZ-WH W-WH SHZ-SHZ MB-WH



A= 7-1/2"  
B= 9-1/8"




**EXAMPLE:** LED-8102-CL-WH

**LED-8102 - BAFFLE W/ REFLECTOR**

**REFLECTOR/RING FINISH:**

W-CL-WH P-CL-WH



A= 7-1/2"  
B= 9-1/8"  
C= 1"




**EXAMPLE:** LED-8107-CL-WH

**LED-8107 - WALL WASH REFLECTOR**

**REFLECTOR/RING FINISH:**

CL-WH CL-SCH WT-WH SHZ-WH W-WH SHZ-SHZ MB-WH



A= 7-1/2"  
B= 9-1/8"




**EXAMPLE:** LED-8112-CL-WH


**LED-8112 - BAFFLE W/ FROSTED GLASS LENS**

**BAFFLE/ RING FINISH:**

W-CL-WH P-CL-WH



A= 7-1/2"  
B= 9-1/8"  
C= 1"




**EXAMPLE:** LED-8114-CL-WH

**LED-8114 - REFLECTOR W/ FROSTED GLASS LENS**

**REFLECTOR/RING FINISH:**

CL-WH CL-SCH WT-WH SHZ-WH W-WH SHZ-SHZ MB-WH



A= 7-1/2"  
B= 9-1/8"  
C= 1"




**EXAMPLE:** LED-8113-CL-WH

**LED-8113 - BAFFLE W/ TEMPERED CLEAR GLASS**

**BAFFLE/ RING FINISH:**

W-WH P-WH



A= 7-1/2"  
B= 9-1/8"  
C= 1"




**EXAMPLE:** LED-8115-CL-WH

**LED-8115 - REFLECTOR W/ TEMPERED CLEAR GLASS**

**REFLECTOR/RING FINISH:**

CL-WH CL-SCH WT-WH SHZ-WH W-WH SHZ-SHZ MB-WH



A= 7-13/16"  
B= 9-1/8"  
C= 1"




**EXAMPLE:** LED-8121-CL-WH

**LED-8121 - STARDUST DECO RING GLASS**

**REFLECTOR/RING FINISH:**

CL-WH CL-SCH WT-WH SHZ-WH W-WH SHZ-SHZ MB-WH



A= 7-13/16"  
B= 9-1/8"  
C= 1"




**EXAMPLE:** LED-8122-CL-WH

**LED-8122 - EURO DECO RING GLASS**

**REFLECTOR/RING FINISH:**

CL-WH CL-SCH WT-WH SHZ-WH W-WH SHZ-SHZ MB-WH



A= 7-1/2"  
B= 9-1/8"  
C= 1"




**EXAMPLE:** LED-8123-CL-WH

**LED-8123 - PRISM DECO RING GLASS**

**REFLECTOR/RING FINISH:**

CL-WH CL-SCH WT-WH SHZ-WH W-WH SHZ-SHZ MB-WH



A= 7-1/2"  
B= 9-1/8"  
C= 1"



**EXAMPLE:** LED-8109-CL-WH


**LED-8109 - DECO GLASS REFLECTOR**

**REFLECTOR/RING FINISH:**

CL-WH CL-SCH WT-WH SHZ-WH W-WH SHZ-SHZ MB-WH

**GLASS FINISH:**

BLUE, RED, GREEN, FROST



A= 7-1/2"  
B= 9-1/8"  
C= 1"



**EXAMPLE:** LED-8110-CL-WH


**LED-8110 - DOUBLE RING GLASS**

**REFLECTOR/RING FINISH:**

CL-WH CL-SCH WT-WH SHZ-WH W-WH SHZ-SHZ MB-WH

**GLASS FINISH:**

BLUE, RED, GREEN, FROST



A= 7-1/2"  
B= 9-1/8"  
C= 1-7/8"



**EXAMPLE:** LED-8128-CL-WH-AL


**LED-8128 - DECO GLASS REFLECTOR WITH ALUMINIUM DISC**

**REFLECTOR/RING FINISH:**

CL-WH CL-SCH WT-WH SHZ-WH W-WH SHZ-SHZ MB-WH

**DISC FINISH:**

AL, WH, BZ



A= 7-1/2"  
B= 9-1/8"  
C= 1"




**EXAMPLE:** LED-8125-CL-WH

**LED-8125 - CENTRAL ETCHED FLOAT GLASS**

**REFLECTOR/RING FINISH:**

CL-WH CL-SCH WT-WH SHZ-WH W-WH SHZ-SHZ MB-WH



A= 7-1/2"  
B= 9-1/8"  
C= 1"

LED  
8"

8 INCH ARCHITECTURAL LED OPTICS