

Lumi-PRO/ RGB Tunable White LED Strip Light



FEATURES

The LB4000-RGBTWH Lumi-Pro Strip Light is an extremely versatile color performance LED lighting solution designed for indoor applications. It offers RGB and Tunable White Color range of 2700K to 6500K options, providing flexibility to create the desired ambiance and lighting effects in various indoor spaces.

Designed for use with our Lumi-Pro Extrusions, the LB4000-RGBTWH LED Strip Light seamlessly integrates into diverse indoor settings. It is mountable on different surfaces, including walls, ceilings, or furniture, making it suitable for residential, commercial, or hospitality environments.

May win in to 11/ft	
Max run up to 11/ft	
Indoor Location (IP22	.)
RGBTWH 5 in 1	
Field cuttable every 3.	94"
Warranty: 3 years limit	ted warranty
• •	ĺ
Color	3.7 W/ft.
Red	25 lm/ft
Green	55 lm/ft
Blue	15 lm/ft
2700K/6500K	130 lm/ft
№ RGBTWH	220lm/ft

WIRING ACCESSORIES

TT12-6



Tape-to-Tape Connector 0.95L x 0.62W x 0.27H TW12-6



Power Connector

0.95L x 0.62W x 0.27H

JP12-6



Tape-toTape Jumper

0.95L x 0.62W x 0.27H 6" L jumper SL-6



Soldered Lead

4 ft standard length (custom length sizes available)

JPSL-6



Soldered Jumper

6" L jumper (custom length sizes available)


TECHNICALS DETAILS

Power	3.7W/ft
3.4 II.	0.417
Voltage	24V
CRI	80+
Oiti	OUT
Technology	RGBTWH
recimology	NOB I WII
LED Qty	18/ft
	446
Max Run(ft)	11ft
Cutting Length	3.94"
Cutting Length	3.94
Dimensions	W0.47" X H0.1"
Working Temp.	-4F / +122F
•	

www.iuseelite.com

Experience unparalleled performance with our precision-engineered, high-quality Lumi-PRO LB4000-RGBTWH LED Strip Light, meticulously designed to meet the demands of the most challenging applications.

DIMENSIONS







It Can be ordered in 3 different ways.

1. Everything will be shipped separately

 Tape light, cover, extrusion and accessories will be cut and shipped to your desired length.



Accessories if ordered.



2. Pre-assembled and shipped separately as two units

- Tape light, cover, extrusion and accessories will be cut and shipped to your desired length.
- · Wiring accessories will be attached to the tape light.
- Cover, end caps and clips will be assembled to the channel.



Wiring accessories attached to the tape light.




3. Fully assembled and shipped as a single unit

- Tape light, cover, extrusion and accessories will be cut and shipped to your desired length.
- Wiring accessories will be attached to the tape light.
- Tape light will be installed into the channel and ready to use.



Refer to the next page for **COMPATIBLE** channels.

ORDERING SELECTION









COMPATIBLE CHANNELS








LP-SHC-CM-075/ Surface





ASB- Assembled SEP - Separated

SEP - Separated





LP-MDC-CM-075/ Surface






LP-LGC-CM-075/ Surface





www.iuseelite.com

LP-SHC-SC-MG-075/ Surface






COMPATIBLE CHANNELS















LP-SHC-CM-1/ Surface







LP-MDC-CM-1/ Surface






LP-LGC-CM-1/ Surface










COMPATIBLE CHANNELS














LP-SHC-RFT-075/ Recessed



0.70" 0.53" **SERIES EXT. LENGTH FINISH** 2 - 2ft LP-MDC-RFT-075 SI - Silver 1.06" 4 - 4ft BK - Black1 8 - 8ft WH - White C - Custom


LP-MDC-RFT-075/ Recessed






LP-LGC-RFT-075/ Recessed







SEP - Separated






COMPATIBLE CHANNELS














LP-LGC-RFT-1/ Recessed







LP-SHC-RFT-2/ Recessed

SERIES EXT. LENGTH **FINISH OPTICAL LENS TAPE LIGHT** LP-SHC-RFT-2 2 - 2ft SI - Silver FTD - Flat Diffuser INS - Installed BK - Black1 **4** - 4ft FTO - Flat Opal 1 SEP - Separated 8 - 8ft WH - White FTT - Flat Transparent1 FTB - Flat Black1 C - Custom **CHANNEL** ASB- Assembled



LP-MDC-RFT-2/ Recessed





SERIES EXT. LENGTH FINISH **OPTICAL LENS TAPE LIGHT** INS - Installed LP-LGC-RFT-2 2 - 2ft FTD - Flat Diffuser SI - Silver SEP - Separated FTO - Flat Opal 1 4 - 4ft BK - Black1 8 - 8ft WH - White1 FTT - Flat Transparent 1 FTB - Flat Black 1 C - Custom **CHANNEL** ASB- Assembled



COMPATIBLE CHANNELS











CHANNEL

ASB- Assembled




LP-LGC-RTL-075/ Trimless




2.42"


LP-MDC-RTL-1/ Trimless

SERIES	EXT. LENGTH	FINISH	OPTICAL LENS	TAPE LIGHT
LP-MDC-RTL-1	2 - 2ft 4 - 4ft 8 - 8ft C - Custom	SI - Silver BK - Black ¹ WH - White ¹	FTD - Flat Diffuser FTO - Flat Opal ¹ FTT - Flat Transparent ¹ FTB - Flat Black ¹	INS - Installed SEP - Separated




LP-SHC-RTL-2/ Trimless





LP-MDC-RTL-2/ Trimless



ASB- Assembled **SEP** - Separated







COMPATIBLE CHANNELS










LP-LGC-RTL-2/ Trimless







LP-LGC-WM-RTL-050/Wall Mount/Trimless





LP-MDC-WM-RTL-050/Wall Mount/Trimless





EXT. LENGTH TAPE LIGHT SERIES FINISH OPTICAL LENS INS - Installed LP-MDC-PR-050 2 - 2ft SI - Silver FTD - Flat Diffuser SEP - Separated **4** - 4ft FTO - Flat Opal 1 FTT - Flat Transparent 1 BK - Black 1 8 - 8ft WH - White C - Custom FTB - Flat Black **CHANNEL** ASB- Assembled



COMPATIBLE CHANNELS









Consult factory for colors and optical lenses options








LP-MDC-WW-RTL-075/ Wall Washer




ASB- Assembled SEP - Separated



LP-MDC-S90-075/ Surface Corner


SERIES	EXT. LENGTH	FINISH	OPTICAL LENS	TAPE LIGHT
LP-MDC-S90-075	2 - 2ft 4 - 4ft 8 - 8ft C - Custom	SI - Silver BK - Black ¹ WH - White ¹	FTD - Flat Diffuser FTO - Flat Opal ¹ FTT - Flat Transparent ¹ FTB - Flat Black ¹	INS - Installed SEP - Separated
				ASB - Assembled SEP - Separated



LP-LGC-S90-075/ Surface Corner



SEP - Separated



LP-LGC-S90-1/ Surface Corner



ASB-Assembled SEP - Separated





LB4000-RGBTWH

RGB Tunable White LED Strip Light

COMPATIBLE CHANNELS












ASB-Assembled

SEP - Separated




LP-LGC-S90-2/ Surface Corner







LP-MDC-SPD-1/ Suspended


SERIES	EXT. LENGTH	FINISH	OPTICAL LENS	CLIP	TAPE LIGHT
LP-MDC-SPD-1	2 - 2ft 4 - 4ft 8 - 8ft C - Custom	SI - Silver BK - Black ¹ WH - White ¹	FTD - Flat Diffuser FTO - Flat Opal ¹ FTT - Flat Transparent ¹ FTB - Flat Black ¹	PC - Pendant Cable SC - Surface Clip	INS - Installed SEP - Separated



LP-SHC-SPD-2/ Suspended























LP-MDC-WM-DI-1/ Surface / Up & Down Light






LP-MDC-WW-RTL-2/ Cove







Click on the picture for detailed information.

LB-2834-5C RGB+CCT Color Wall Panel Controller

- Double touch sliders, one for RGB and the other one for CCT adjustment.
- Control 1 zone with endless receivers in each zone.
- Save up to 3 colors/scenes for each zone.
- 10 built-in color changing effects are available with pause function.
- · Remote control over 20 meters.
- Receivers can work with the WiFi-RF converter using the "Easylighting" or "Easyhome" app on IOS and Android systems.

Compatible with: LB2817-DMX - LB2108B-M6-3 - LB-1009EWI-5CH - LED25W-24

TECHNICAL DETAILS

Output Signal	RF Signal
Power Supply	12-24 VDC
Power Consumption	< 20 mA
Operating Temperature	0-40°C / 32°F-104°F
Dimensions	4.7"X2.9"X1"
Color	White/Black

Certifications	FCC / RoHS
Zones	Control 1 zone of RF receiver
Frequency	916.5MHz
Surface	Glass
Control	RGB/CCT controller
Warranty	5-years limited warranty



Click on the picture for detailed information.

LB-2858Z4-5C RGB + CCT Remote Controller

- Enable 5 channel control of RGB and dual color (warm white and cold white).
- Ultra-sensitive tempered glass touch color wheel.
- RGB and CCT channels can be controlled separately.
- Programmable function by choosing colors(max 5 colors) and touch the "P" key.
- Four running modes, including jump, flash, fade, and strobe, are available for the programmed colors.
- · Set 4 scenes.
- Enable dimming of the brightness for each R, G, B, W channel, allowing the mixing of millions of colors.
- One receiver can be paired with a maximum of 8 different remote controls.
- Receivers can work with the WiFi-RF converter using the "Easylighting" or "Easyhome" app on IOS and Android systems.

Compatible with: LB2817-DMX - LB2108B-M6-3 - LB-1009EWI-5CH

TECHNICAL DETAILS

Output Signal	RF Signal
Power Supply	4.5V (3xAAA battery)
Operating Temperature	0-40°C / 32°F-104°F
Dimensions	6"X2"X0.7"
Color	Black

Certifications	FCC / RoHS
Zones	Control 4 Zones of RF receivers
Frequency	869.5/916.5/434MHz
Warranty	5-years limited warranty







Click on the picture for detailed information.

LB-2817DMX DMX Converter

The **LB-2817DMX master** is a controller that receives RF or WiFi wireless signals from remote controllers, iOS, or Android mobile devices, and sends out **DMX512 signals to DMX decoders**, enabling remote or WiFi control of DMX controllers.

The master converts RF or WiFi signals to DMX signals, enabling wireless control. Easier and more convenient control can be achieved by pairing this RF and WiFi to DMX master with the RF remote or WiFi controller LB2819S, iOS, and Android devices.

- Control up to 8 zones.
- · Set 8 scenes at each zone.
- Preset 10 changing modes, with pause function.
- Control synchronously after installing app on iPhone, iPad and android.
- Memory function to remember the last color/scene
- Enable dimming of the brightness for each R, G, B, W channel, allowing the mixing of millions of colors

TECHNICAL DETAILS

Output Signal	DMX512 Signal
Voltage	110-220 VAC
Operating Temperature	0-40°C / 32°F-104°F
Dimensions	7"X1.8"X0.8"

Certifications	FCC / RoHS
Color	White
Warranty	5 Years limited warranty



Click on the picture for detailed information.

LB-1009EWI-5CH RF+WiFi RGB+CCT Controller

The RF LED receiver LB-1009EWI-5CH is a 5-channel, fully functional constant voltage LED controller available with 12-36VDC and a maximum output of 5A per channel. It can drive RGB and dual-color (warm white and cold white) LED lighting with a single receiver when paired with an RGB and CCT remote.

In addition to RGB and CCT LEDs, the 5-channel RF receiver also supports monochrome, dual-color, RGB, and RGB lighting when paired with the corresponding remote or wall-mounted control.

It offers not only smooth brightness dimming function but also accurate color temperature and RGB color tone adjustment with PWM output. **Multiple zones can be controlled separately or synchronously with endless receivers in each zone.** Built-in changing patterns are available and can be saved to each zone. The brightness of each zone's R, G, B, W channels can be adjusted separately to achieve millions of colors.

When working with WiFi-RF converters, the RF receiver can be WiFi-controlled by an app installed on iOS or Android mobile devices.

TECHNICAL DETAILS

12-36 VDC
5x5A
5x(60-180)W
6.6"X2.3"X1.1"

Frequency	869.5/916.5/434MHz
Certifications	FCC / RoHS
Color	White
Warranty	5-years limited warranty





LB-2108B-M6-3 DMX512 & RDM Decoder

The LB-2108B-M6-3 is an Ultra-Pro 6CH RDM DMX512 decoder equipped with master and decoder modes and RDM functionality. Encased in a metal housing and featuring a digital display, it can directly display data and easily set and show DMX addresses.

This device offers multiple types of DMX input/output ports, including RJ45, XLR, and standard screws. It provides a total of 6 PWM output channels, all with common anode configuration. **The DMX channel quantity can be configured as either 1CH or 6CH, and the PWM output resolution ratio can be set to 8-bit or 16-bit.** With adjustable decoding modes, the output PWM frequency ranges from 500Hz to 35KHz, and the output dimming curve gamma value can be adjusted from 0.1 to 9.9.

Click on the picture for detailed information.

TECHNICAL DETAILS

Input Voltage	12-24 VDC
Output Current	6x6A
Output Power	6x(72-144)W
Dimensions	7.3"X3.3"X1.6"

Output PWM Frequency	500HZ - 35K HZ settable
Certifications	FCC / RoHS
Color	Black
Warranty	5-years limited warranty



LED25W-24 (Power Supply) Optional for wall controller

Total Power: 25 Watts
Input Voltage: 100-277 VAC
UL Dry & Damp Location Rated
IP66
High Efficiency
High Power Factor

Analog Dimming (0-10V)


Black Magic Thermal Advantage, Plastic Housing


Compatible with: LB2817-DMX - LB-2834-5C




GUIDE DIAGRAM


RGB-TWH Wireless Control Options (DMX)

















GUIDE DIAGRAM

RGB-TWH Wireless Control Options VIA RF Conveter and Wired DMX.





GUIDE DIAGRAM

RGB-TWH Wireless Control Options VIA RF Conveter and Wired DMX.

