



APPLICATION:

Ideal for mounting height of 20 feet and above in applications such as factories, foundries, machine shops, warehouses and large retail stores.

CONSTRUCTION

Heavy-duty die-cast aluminum ballast housing with white powder coat finish. Fixture includes 3/4" threaded hole on top for hook mount or pendant mount. Refractor is high-grade polycarbonate with UV diffuser. HID & HPS fixtures have porcelain 4KV pulse-rated mogul-base socket with nickel-plated screw shell sockets and come with pulse-start ballast standard.

LENS

Choice of flat acrylic lens, tempered clear glass lens, or acrylic conical lens.

INSTALLATION

Mount with included hook or remove for pendant mounting.

LISTINGS

UL/C-UL for damp location.

All specifications are subject to change without notice

Ordering Information > Example: OHB-16-MH-400-120-QRS-OZB-16-ADL

OHB	16				
SERIES	DIAMETER	WATTAGE	VOLTAGE	OPTIONS	ACCESSORIES
OHB - Oracle HID High Bay	16 22	HPS, MH HPS-250 - (250W High Pressure Sodium) HPS-400 - (400W High Pressure Sodium) MH-250 - (250W Metal Halide) MH-400 - (400W Metal Halide)	HPS, MH^{1,2} - 120 - MVOLT (120/208/240/277) - 347 ³ - 480 ³	QRS - Quartz Restrike	OZB-16-ADL - Acrylic Drop Lens OZB-16-CAL - Conical Bottom Lens OZB-16-SGL - Safety Glass Lens OZB-16-WG - Steel Wire Guard OZB-22-ADL - Acrylic Drop Lens OZB-22-CAL - Conical Bottom Lens OZB-22-SGL - Safety Glass Lens OZB-22-WG - Steel Wire Guard
		INDUCTION IND-70-50K ⁴ - (70W Induction) IND-80-50K ⁴ - (80W Induction) IND-100-50K ⁴ - (100W Induction) IND-120-50K ⁴ - (120W Induction) IND-150-50K ⁴ - (150W Induction) IND-200-50K ⁴ - (200W Induction)	INDUCTION⁴ - MVOLT(120/277)		

NOTES:

1. Pulse-Start standard on all fixtures above 175W.
2. (Consult factory) for other wattages and options.
3. 347 & 480 Volt not available on 50 & 70W fixture.
4. Induction fixtures shipped with 5000K lamp standard please contact factory for other color options.