
## **OPR-R-LED**







APPLICATION- OPR-R-LED recessed offer direct ambient illumination. Its clean, classic look provides light over any environment including schools, boardrooms, office areas, hotels, lobbies, restaurants, etc. OPR-R-LED is suitable for any design application with its variety in sizes.

**CONSTRUCTION** - Rigid aluminum design ensures longevity and endurance. A high quality, high transmission, glare free lens offers smooth illumination.

PERFORMANCE - The OPR-R-LED is rated at 85+ CRI and is available in multiple CCTs: 3000K, 3500K and 4000K. Rated and tested to LM-79 and LM-80 standards. The LEDs are also binned to a 3-step MacAdam ellipse to achieve consistent color from fixture to fixture.

**ELECTRICAL** - Powered by high-quality constant-current power LED drivers which are rated for 50 to 60Hz at 120-277V input, produce less than 20% THD, and have a power factor of .90 to 1.00.

DIMMING - The OPR-R-LED comes standard with 0-10V dimming on either 120, in and 277V. 347V please consult factory. Dimmable down to 1% of initial lumens. Also available in Lutron dimming options. Consult factory for dimmer compatibility.

MOUNTING - Comes standard as recessed mount. Consult factory for additional mounting options.

QUALITY CONTROL - Every ixture is rigorously tested by our QC Department before shipping.

**WARRANTY** - Limited 5 Year Warranty

## EXAMPLE: OPR-R-LED-3000L-DIM10-MV0LT-40K-WH

SERIES	SIZE	LUMENS	DIMMING	CCT	CRI	EMERGENCY	COLOR
OPR-R-LED	2'	□ 3000L □ 4000L □ 5000L	DIM10-MVOLT LUTH-MVOLT DIMTR-120	□ 30K □ 35K □ 40K	□85+	Remote Mounted for Surface Mount	□ WH ( Matt White) □ BK ( Black) □ SI ( Silver)
	3'	□ 4000L □ 6000L □ 8000L					Custom color available, please consult factory. Must provide RAL#
	4'	□ 6000L □ 8000L □ 10000L					