



OSS-12
A & B = 12-1/2"
C = 3"
OSS-14
A & B = 14-1/2"
C = 3-1/2"
OSS-19
A & B = 19-1/2"
C = 4"



PRODUCT FEATURES:

- Heavy-gauge metal housing
- Housing suitable for mounting to standard splice box
- Lens is UV stable white acrylic
- Available with circline T9 or double twin tube lamps (see available chart below)
- Ballast is electronic, UL listed - Class P and thermally protected
- Suitable for damp location
- Twist-off diffuser is easily removable for lamp replacement
- NEC required ballast disconnect is standard

LISTING

UL/C-UL listed to US and Canadian standard

WARRANTY

Guaranteed for one year against mechanical defects

Ordering Information > Example: OSS-14-32W-120

SERIES	FIXTURE SIZE	WATTAGE	VOLTAGE
OSS Oracle Surface Mount Square Fixture	12 - 12" 14 - 14" 19 - 19"	12" FIXTURE 22W - (1) 22W FC8T9 Lamp ¹	120 277
		14" FIXTURE 32W - (1) 32W FC12T9 Lamp 54W - (1) 22W FC8T9 Lamp and (1) 32W FC12T9 Lamp ¹	
		19" FIXTURE 72W - (1) 32W FC12T9 Lamp and (1) 40W FC16T9 Lamp ¹	

Notes:

1. Energy Star rated fixture