

OVR-203-LED

LED Medium Round Canopy CT/Lumen
select LED Series

Catalog Number:


Project Name:

Note:


Type:



DIMENSION:



PHOTOMETRICS:



B	U	G
1	3	2

APPLICATIONS:

The Oracle LED Canopy Light is designed to provide an aesthetically pleasing low-profile luminaire that produces a high light output while keeping energy and maintenance costs low. Easily access field-adjustable 3-Color SeleCCT from 3000K - 4000K - 5000K, ideal for parking garages, walkways, storage areas, underpasses, and stairwells.

FEATURES:

- Sealed die-casting profile for outdoor applications.
- Input Voltage MVOLT
- Lumen output from 4000 - 8000Lm with efficacy up to 141 lm/W.
- Increase energy savings with optional bi-level motion sensor.
- Replacing 100W MH and 175 W MH saving over 75% energy consumption.
- Operating temperature is -40°C to 40°C (-40°F to 104°F).
- UL/cUL wet location.
- CCT Option Easily access field-adjustable 3-Color SeleCCT from 3000K-4000K-5000K or switch without lowering the luminaire from the ceiling.
- Surface mount with J-BOX; Pendant installation with 3/4 inch conduit.

SPECIFICATIONS:

LUMENS 4000 / 6000 / 8000 lumens

WATTAGE 28W / 40W / 60W

CCT 30K-40K-50K

CRI 80

LIGHT EFFICIENCY 130 lumens/watt

VOLTAGE MVOLT

POWER FREQUENCY 50/60 Hz

FINISH Bronze, White, Black

APPLICABLE ENVIRONMENT Dry/Damp/Wet location

WORKING TEMPERATURE -40°C to 40°C



* For list of qualified DLC fixture, please consult factory

Ordering Guide > Example: **OVR-203-LED-4000/6000/8000L-DIM10-MVOLT-30K/40K/50K**

OVR-203-LED							
SERIES	PERFORMANCE	DIMMING	VOLTAGE	CCT	FINISH	EMERGENCY	OPTION
OVR-203-LED	4000L/6000L/8000L	DIM10 - 0-10V Dimming	MVOLT	30K/40K/50K	BZ - Bronze WH - White BK - Black	O-EMG-LED-10W	Blank Without function PC Photocell SPD 10KVSPD MS Motion sensor

** DesignLights Consortium® (DLC) qualified product. Not all versions of this product may be DLC qualified. Please check the DLC Qualified Products List at www.designlights.org to confirm which versions are qualified.



Submittal form is available @ www.oraclelighting.com
Tel: 323-888-1973 • Fax: 323-888-1977

Specifications and Dimensions
subject to change without notice.






Issued-B1118-Rev. 1

OVR-203-LED

LED Medium Round Canopy CCT/Lumen
select LED Series

Catalog Number:	
Project Name:	
Note:	Type:

ACCESSORY

MODEL	SPD	Photocell	Motion Sensor	Motion Sensor	EM Driver
IMAGE					

** DesignLights Consortium® (DLC) qualified product. Not all versions of this product may be DLC qualified.
Please check the DLC Qualified Products List at www.designlights.org to confirm which versions are qualified.