SQUARE WALL MOUNT MEDALLION HALF-CUTOFF FRAME





APPLICATION

For areas where security and facade lighting is required. Applications include industrial buildings, universities, schools, apartment buildings, institutions, and government buildings. Fixture is ideal for outdoor wall wash applications.

CONSTRUCTION

Die cast aluminum housing and half cutoff front frame, textured powdercoat finish over a chromate conversion coating. The one-piece silicone gasket effectively limits outside contaminants by sealing off the optical chamber.

FINISH - Dark bronze corrosion- and UV-resistant polyester powder finish is standard.

LENS - Standard opal polycarbonate lens.

INSTALLATION - Convenient, easy mount over standard 4" outlet box or use 1/2" surface conduit.


LISTINGS - CSA: Listed for wet locations, wall mount only

WARRANTY - Limited 1 Year Warranty.

All specifications are subject to change without notice



Dimensions:



House Side 1.75 2.75

Distance In Units Of Mounting Height Values Based On 10 Foot Mounting Height 1/2 Maximum Candela Trace Shown As Dashed Curve

2 2.25

(+) = Maximum Candela Point


Ordering Information: Example: OWM-S-202-2-26-32-42-MVOLT-50K-BZ

OWM-S-202

4

5

SERIES OWM-S-202-Oracle Square Wall Mount Medallion Half-Cutoff Frame



2-26-32-42 - (2x26/32/42W CFL)



CCT **50K** - (5000K) * For more CCT option, consult factory



CRI



BZ - Bronze WH - White

CUS - Custom color,

consult factory

OPTION PHC - Photo cell BK - Black