

OPTICS

No UV or IR in the beam. Light is soft and uniform, safe to eyes. Stripe glass Diffuser.

CONSTRUCTION

Constructed from one-piece, die-cast aluminum housing, featuring an open front frame with a textured powder-coat finish over a chromate conversion coating. Chromate conversion coating provides excellent corrosion resistance and a higher electrical surface resistance. The housing is sealed with a one-piece silicone gasket that protects the optical assembly from outside contaminants.

MOUNTING

Wall mounted for area light delivering uniform, widespread high output.

OPTIONS & ACCESSORIES

Options and Accessories

Optional emergency battery back-up (EMG) option for emergency egress lighting

Optional photocell (PHC) detects changing light levels and saves energy by turning off during the day

DRIVER ELECTRICAL INFORMATION

Powered by high-quality constant-current power LED drivers which are rated for 50 to 60Hz at 120/277V input. Produce less than 20% THD, and have a power factor of .90 to 1.00.

DIMMING & DRIVER INFORMATION

DIM10 - Flicker Free 1% Dimming Standard (DIM10) 0-10V dimming on either MVOLT 120 or 277.

WARRANTY

Five-year warranty for parts and components (labor not included).

LISTING

cULus Listed
Wet Location Listed
Dark Sky Compliant

Example: **OWP-FC-201-LED-4500/6000L-DIM10-MVOLT-30K/40K/50K-BZ**

OWP-FC-201-LED						
SERIES	LUMENS	DIMMING	VOLTAGE	CCT	FINISH	OPTION
EPP1SYR0PP4EG0	4500/6000L	DIM10 - 0-10V Dimming	MVOLT	30K/40K/50K	BZ - Bronze	PHC - Photocell EMG - Emergency PIR - PIR Sensor FS-305RC . Xbuutppqfs! OpujpoIT fotps