



NOMINAL LUMENS	DELIVERED LUMENS	WATTAGE
8000	8643	72 W
6000	6010	50 W
4000	3611	30 W
2000	1802	15 W

Based on 4000K, 85+ CRI. Actual wattage may vary +/- 5%

FEATURES

The OWS-FC-202-LED is an architectural LED wall sconce with a curved, low-profile design that complements contemporary interiors and durable, corrosion-resistant construction suitable for outdoor applications. The OWS is wet location rated and full cutoff meets Dark Sky requirements. Stainless steel hardware and an enclosed-and-gasketed silicon construction protects from dust, corrosion, and environments prone to moisture – making the OWS the choice for robust, long-lasting, efficient wallwash and façade lighting. A 50W power consumption replaces 200W MH. Available in four finishes, up/downlight, and standard downlight.

LUMENS	Selectable: 2000L/4000L/6000L/8000L
CCT	40K, 50K
CRI	70+ Standard
COLOR QUALITY	3 Step MacAdam Ellipse
MOUNTING	Surface
DIMMING	DIM10 (0-10 dimming)
FINISH	Black, Bronze
WORKING TEMPERATURE	-30°C to 40°C (-22°F to 104°F)
LIFETIME	L70 at 50,000 Hours
PHOTOMETRIC TESTS	In Accordance with IES LM79-08, LM80 and TM-30, TM-21

CONSTRUCTION

Constructed from one-piece, die-cast aluminum housing, featuring an open front frame with a textured powder-coat finish over a chromate conversion coating. Chromate conversion coating provides excellent corrosion resistance and a higher electrical surface resistance. The housing is sealed with a one-piece silicone gasket that protects the optical assembly from outside contaminants. Faceplate is secured to housing by four (4) captive, tamper-resistant, stainless-steel screws.

OPTICS

High-impact UV-stabilized polycarbonate lens provides uniform illumination and high output. Type II distribution – area lighting used for wide walkways, ramps and entrance roadways, jogging paths, and other larger areas typically near roadside.

MOUNTING

Wall mounted for area light delivering uniform, widespread high output.

OPTIONS & ACCESSORIES

Options and Accessories

Optional emergency battery back-up (EMG) option for emergency egress lighting

Optional photocell (PHC) detects changing light levels and saves energy by turning off during the day

DRIVER ELECTRICAL INFORMATION

Powered by high-quality constant-current power LED drivers which are rated for 50 to 60Hz at 120/277V input. Produce less than 20% THD, and have a power factor of .90 to 1.00.

DIMMING & DRIVER INFORMATION

DIM10 - Flicker Free 1% Dimming Standard (DIM10) 0-10V dimming on either MVOLT 120 or 277.

WARRANTY

Five-year warranty for parts and components (labor not included).

LISTING

cULus Listed
Wet Location Listed
Dark Sky Compliant

Example: **OWS-FC-202-LED-2000L/4000L/6000L/8000L-DIM10-MVOLT-40K-BZ**

OWS-FC-202-LED					
SERIES	LUMENS	DIMMING	VOLTAGE	CCT	FINISH
Wall Mount Wall Pack	2000L/4000L/6000L/8000L	DIM10 - 0-10V Dimming	MVOLT	40K 50K	BK - Black BZ - Bronze