


**DIMENSIONS**



**Recommended Hole Cut-out Size: 10"**

NOMINAL LUMENS	DELIVERED LUMENS	WATTAGE
3000L	3357L	30W
2500L	2707L	25W
2000L	2264L	20W

Based on 4000K, 90+ CRI. Actual wattage may vary +/- 5%

**INSTALLATION**

Cut hole in ceiling. Insert luminaire into opening by squeezing spring clips on both sides of luminaire. The width in ceiling needed for the driver to fit is 3".

For wet location application, you **MUST** seal all gaps between the ceiling and fixture with weatherproof silicone sealant. This deters moisture and water from damaging fixtures and other mechanical ceiling elements. Installation hole size: 10"

**FEATURES**

This 10" LED "Canless" downlight is engineered for new construction, remodel, or retrofit applications. It accommodates insulated and dropped ceilings, and features switchable multi-lumen and multi-CCT and dual dimming for versatile function. Recessed housing not required.

Ideal for improved general lighting in corporate, commercial, retail, and hospitality spaces. Suitable for both indoor and shower use.

IC rated, airtight, and ready to be in contact with insulation.

LUMENS	2000L/2500L/3000L
CCT	27K/30K/35K/40K/50K
CRI	90+ Standard
COLOR QUALITY	3-Step MacAdam Ellipse
MOUNTING	Recessed
DIMMING	DIM10 - 0-10V 1% Flicker-free Dimming, DIMTR - 5% Triac Dimming at 120V
BEAM ANGLE	Very Wide (VWD) at 90°
FINISH	White (W) Standard
TRIM FINISH	Black (BK), Satin Haze (SH), White (WH), Clear (CL)
WORKING TEMP.	-25°C (-13°F) to 40°C (104°F)
UGR	UGR<19
EMERGENCY	EMG-LED-G-16W-HV-FLEX (Remote) EMG-LED-G-25W-HV-FLEX (Remote)
LIFETIME	L70 at 50,000 Hours
PHOTOMETRIC	In accordance with IES LM79-08, LM80 and TM-30, TM-21



**OPTICS**

Features a regressed, frosted polycarbonate lens for optimal beam diffusion and a reflector for smooth, glare-free illumination. Features a UGR<19, and a wide (WD) distribution.

Highly effective, micro-power LEDs allow for excellent and energy efficient performance.

Five selectable color temperatures of 27K/30K/35K/40K/50K enable different warm to cool moods and atmospheres. A selectable lumen package of 2000L/2500L/3000L allows for customizable intensity, for a variety of uses.

CCT factory set to 5000K; lumen factory set to 3000L.

**CONSTRUCTION**

Housing built from spun aluminum for a lightweight durability and optimal heat conduction.

IC rated, air-tight, and ready for contact with insulation. Completely sealed for use in wet locations.

Pre-installed spring clips allow for easy and fast "snap-in" recessed installation.

Multi-lumen and multi-CCT switches located on remote driver box.

Available in a white finish.

**MAINTENANCE**

Fixture can be regularly and safely wiped down to ensure optimal fixture performance.

**MOUNTING**

Suitable for Recessed Mounting in remodel and new construction applications. Meant to be installed in 10" hole. No recessed housing necessary.

**OPTIONS & ACCESSORIES**

1.9 ft power cable and remote driver included.

Available to order separately:

- Various colored Baffle, Reflector, and Trim options
- 16W and 25W Emergency Battery Back-up options

Extension cable options:

- RL-ACC-SLIM-1-10F (10-ft)
- RL-ACC-SLIM-1-20F (20-ft)

Rough Plate options:

- RL-UNV-1/2/3/4/5/6/8/10 - Universal Mounting Plate for 1", 2", 3", 4", 5", 6", 8" and 10" downlights

See order chart for details.

**DRIVER & ELECTRICAL INFORMATION**

Powered by high-quality constant-current power LED drivers which are rated for 50 to 60Hz at 120V-347V input, produce less than 20% THD, and have a power factor of .90 to 1.00.

**DIMMING**

Available with dual dimming:

DIM10 - Flicker-free 1% dimming at 120-347V.

DIMTR - 5% Triac & electronic low voltage dimming. Available in 120V.

**WARRANTY**

5-year warranty for parts and components (labor not included).

**LISTINGS**

ETL listed.

Energy Star certified.

JA8 and Title 20 compliant.

Wet location suitable.

IC-Rated, air-tight ready, and may be in direct contact with insulation.

**MULTI-LUMEN & MULTI-CCT SWITCH**



**TRIM OPTIONS**

**BAFFLE TRIMS**



RL1043-BT-MB-BK  
Black - Black



RL1043-BT-SHZ-SHZ  
Satin Haze - Satin Haze



RL1043-BT-SHZ-WH  
Satin Haze - White

**REFLECTOR TRIMS**



RL1043-RT-MB-BK  
Black - Black



RL1043-RT-SHZ-SHZ  
Satin Haze - Satin Haze



RL1043-RT-SHZ-WH  
Satin Haze - White



RL1043-RT-CL-WH  
Clear - White

**OPTION & ACCESSORIES**




**RL-ACC-SLIM-1-10F**  
10-ft long extension

**RL-ACC-SLIM-1-20F**  
20-ft long extension

**RL-UNV-1/2/3/4/5/6/8/10**

For use with 1", 2", 3", 4", 5", 6", 8" and 10" downlights




Example: **RCL1043-2000L/2500L/3000L-DIMTR/120-DIM10/120-347V-27K/30K/35K/40K/50K-W-WH**

<b>RCL1043</b>						
SERIES	LUMENS	DIMMING	CCT	CRI	FINISH	OPTION
RCL1043	2000L/2500L/3000L	DIMTR/120-DIM10/120-347V (Triac-0-10V)	27K/30K/35K/40K/50K	90	W-WH - White	<b>RL-ACC-SLIM-1-10F</b> - 10-ft long extension <b>RL-ACC-SLIM-1-20F</b> - 20-ft long extension <b>RL-UNV-1/2/3/4/5/6/8/10</b> - Universal Mounting Plate for 1", 2", 3", 4", 5", 6", 8" and 10" <b>O-EMG-LED-16W-FLEX</b> - 16W Emergency Back up (Remote) <b>O-EMG-LED-25W-FLEX</b> - 25W Emergency Back up (Remote)
<b>TRIM OPTION</b>						
<b>RL1043-BT-MB-BK</b> <b>RL1043-BT-SHZ-SHZ</b> <b>RL1043-BT-SHZ-WH</b> <b>RL1043-RT-MB-BK</b> <b>RL1043-RT-SHZ-SHZ</b> <b>RL1043-RT-SHZ-WH</b> <b>RL1043-RT-CL-WH</b>						

RCL1043- 2000L-2500L-3000L-DIMTR-120-DIM10-120-347V-27K-30K-35K-40K-50K-W-WH(2000L)

TEST NO.: EL08052509


INPUT WATTS:19.6 LUMENS:2264 EFFICACY: 116 BEAM ANGLE:88 SPACING CRITERIA: 1.15 x 1.15



RCL1043- 2000L-2500L-3000L-DIMTR-120-DIM10-120-347V-27K-30K-35K-40K-50K-W-WH(2500L)

TEST NO.: EL08052509

INPUT WATTS:23.8 LUMENS:2707 EFFICACY: 114 BEAM ANGLE:88 SPACING CRITERIA: 1.15 x 1.15



RCL1043- 2000L-2500L-3000L-DIMTR-120-DIM10-120-347V-27K-30K-35K-40K-50K-W-WH(3000L)

TEST NO.: EL08052509

INPUT WATTS:30.2 LUMENS:3357 EFFICACY: 111 BEAM ANGLE:88 SPACING CRITERIA: 1.15 x 1.15

